

# **Safety Data Sheet**

Revision Date: 06/04/19 www.restek.com

2 Letter ISO country code/language code: US/EN

#### **1. IDENTIFICATION**

Catalog Number / Product Name: Company: Address:

Phone#: Fax#: Emergency#:

Email: **Revision Number:** Intended use:

31639 / Alternate BP/CN Distribution Marker Stock Solution **Restek Corporation** 110 Benner Circle Bellefonte, Pa. 16823 814-353-1300 814-353-1309 800-424-9300 (CHEMTREC) 703-527-3887 (Outside the US) www.restek.com 12 For Laboratory use only

## 2. HAZARD(S)IDENTIFICATION

**Emergency Overview:** 

Symbols:



GHS Classification:	Flammable Liquid Category 2 Hazardous to the aquatic environment - Chronic Category 2 Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 3						
GHS Signal Word:	Danger						
GHS Hazard:	Highly flammable liquid and vapour. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.						
GHS Precautions:							
Safety Precautions:	Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilation and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.						
First Aid Measures:	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. In case of fire: Use extinguishing media in section 5 for extinction. Collect spillage.						
Storage:	Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.						
Disposal:	Dispose of contents/container according to section 13 of the SDS.						
Single	Specific target organ toxicity - Single exposure - STOT SE 3: H336 May cause drowsiness or dizziness.						

Repeated<br/>ExposureSpecific target organ toxicity - Repeated exposure - STOT RE 2: H373 May cause damage to organs through<br/>prolonged or repeated exposure. (C >= 5 %; Minimum classification, No information to prove exclusion of certain<br/>routes of exposure)

Chemical Name	CAS #	EINEC #	% Composition
Pentane	109-66-0	203-692-4	99.82
hexane	110-54-3	203-777-6	0.02
Hexadecane	544-76-3	208-878-9	0.02
hexatriacontane	630-06-8	211-127-8	0.02
n-Octane	111-65-9	203-892-1	0.02
decane	124-18-5	204-686-4	0.02
n-Dodecane	112-40-3	203-967-9	0.02
pentatriacontane	630-07-9		0.02
heneicosane	629-94-7	211-118-9	0.02
octacosane	630-02-4	211-125-7	0.02

### 4. FIRST-AID MEASURES

Inhalation:	Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately
Eyes:	Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.
Skin Contact:	Wash with soap and water. Get medical attention if irritation develops or persists.
Ingestion:	Do not induce vomiting and seek medical attention immediately. Drink two glasses of water or milk to dilute. Provide medical care provider with this SDS. Induce vomiting as a last measure. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.

### 5. FIRE- FIGHTING MEASURES

Extinguishing Media: Fire and/or Explosion Hazards:	Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agents. Water spray or fog may also be effective for extinguishing if swept across the base of the fire. Water can also be used to absorb heat and keep exposed material from being damaged by fire. Water may be ineffective in fire fighting due the material (or component(s) low flash point, low solvent density, and limited miscibility with water. Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back. Vapors may be ignited by heat, sparks, flames or other sources of			
Fire Fighting Methods and Protection: Hazardous Combustion Products:	ignition at or above the low flash point giving rise to a Class B fire. Vapors are heavier than air and may travel to a source of ignition and flash back Empty containers that retain product residue (liquid, solid/sludge, or vapor) can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an explosion that may lead to injury or death. Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Flammable component(s) of this material may be lighter than water and burn while floating on the surface. Carbon dioxide, Carbon monoxide			

#### 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions and Equipment:	Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section 8 of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.
Methods for Clean-up:	Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation.

# 7. HANDLING AND STORAGE

Handling Technical Measures and Precautions:	Mildly irritating material. Avoid unnecessary exposure. Use spark-proof tools and explosion-proof equipment Avoid contact with material. Ground and bond containers when transferring material Do not enter storage area unless adequately ventilated				
Storage Technical Measures and Conditions:	Store in a cool dry ventilated location. Isolate from incompatible materials and conditions. Keep container(s) closed. Keep away from heat, sparks, and flame Store in a cool place in original container and protect from sunlight Limit quantity of material stored.				

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

United States:							
Chemical Name			ACGIH STEL	ACGIH TLV-TWA	OSHA Exposure Limit		
Pentane	109-66-0	1500 ppm IDLH (10% LEL)	None Known	600 ppm TWA; 1770 mg/m3 TWA	1000 ppm TWA; 2950 mg/m3 TWA		
Personal Protection: Engineering Measures: Respiratory Protection:			Local exhaust ventilation or other engineering controls are normally required when handling or using this product to avoid overexposure. Explosion proof exhaust ventilation should be used. Engineering controls must be designed to meet the OSHA chemical specific standard in 29 CFR 1910. Respiratory protection will be required when handling this product. Use respirators only if ventilation cannot be used to eliminate symptoms or reduce the exposure to below acceptable levels.Wear a NIOSH approved respirator if any exposure is possible. Follow a respiratory protection program that meets 29 CFR 1910.134 and ANSI Z88.2 requirements whenever work place conditions warrant				
Eye Protection:			the use of a respirator. Wear chemically resistant safety glasses with side shields when handling this product. Do not wear contact lenses.Wear goggles and a Face shield				
Skin Protection: Medical Conditions Aggravated By Exposure:			Avoid skin contact by wearing chemically resistant gloves, an apron and other protective equipment depending upon conditions of use. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.				

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance, color:	Colorless
Odor:	Mild
Physical State:	No data available
pH:	Not applicable
Vapor Pressure:	No data available
Vapor Density:	2.5 (air = 1)
Boiling Point (°C):	36.1 °C (HSDB)
Melting Point (°C):	<-50 °C
Flash Point (°F):	-56
Flammability:	Highly Flammable Extremely Flammable
Upper Flammable/Explosive Limit, % in air:	7.8

	losive Limit, % in air: 1	
Autoignition Temperat		260 deg C
Decomposition Tempe		No data available
Specific Gravity:		630 kg/m3 at 15 °C
Evaporation Rate: Odor Threshold:		No data available
Solubility:		No data available
Partition Coefficient: n		Negligible; 0-1% No data available
VOC % by weight:		99.82
Molecular Weight:		No data available
10. STABILITY AND RE	ACTIVITY	
Stability:		Stable under normal conditions.
Conditions to Avoid:		None known.
	emical Incompatiability	
Hazardous Decompos	ition Products:	No data available
11. TOXICOLOGICAL I	NFORMATION	
Routes of Entry:		Inhalation Ingestion Skin contact Eye contact
Target Organs Potenti	ally Affected By Exposu	
Chamical Interactions	That Change Taviaite	Respiratory Tract, Skin
Chemical Interactions	That Change Toxicity:	None Known
mmediate (Acute) Heal	th Effects by Route of E	Exposure:
Inhalation Irritation:		espiratory irritation, dizziness, weakness, fatigue, nausea
		oncentrations may be fatal.
Skin Contact:		irritation, defatting, and dermatitis.
Eye Contact:		rritation, tearing and reddening, but not likely to
	permanently injure eye	
Ingestion Irritation:		pat, and stomach. Can cause abdominal discomfort,
	chemical pneumonitis	diarrhea.Aspiration of material into the lungs can cause which can be fatal
Long-Term (Chronic) H	ealth Effects:	
Carcinogenicity:		No data.
Reproductive and Dev	elopmental loxicity:	No data available to indicate product or any components
Inhalation:		present at greater than 0.1% may cause birth defects.
		Upon prolonged and/or repeated exposure, can cause moderate respiratory irritation, dizziness, weakness, fatigue,
		nausea and headache.
Skin Contact:		Upon prolonged or repeated contact, can cause minor
okin oontaol.		skin irritation, defatting, and dermatitis.
Component Toxicologi	cal Data:	
NIOSH:		
Chemical Name	CAS No.	LD50/LC50
Pentane	109-66-0	Inhalation LC50 Rat : 364 gm/m3/4H
Component Carcinoge	nic Data:	
OSHA: Chemical Name	CAS No.	
No data available	CA3 NO.	
ACGIH:		
Chemical Name	CAS No.	
No data available	CA3 NO.	
NIOSH:		
Chemical Name	CAS No.	
No data available		
NTP:		
Chemical Name	CAS No.	
No data available		

IARC:

Chemical Name	CA	S No.				Group	No.		
12. ECOLOGICAL INFO	RMATION								
Overview: Mobility: Persistence: Bioaccumulation: Degradability: Ecological Toxicity Dat	a:		ma No No No		ngerou	is to plants a	h concentrations, nd/or wildlife.	this product	
13. DISPOSAL CONSID	ERATIONS								
Waste Description of Spent Product: Disposal Methods: Waste Disposal of Packaging:			sp rei wa Di or	Spent or discarded material is a hazardous waste.Mixing spent or discarded material with other materials may render the mixture hazardous. Perform a hazardous waste determination on mixtures. Dispose of by incineration following Federal, State, Local, or Provincial regulations. Comply with all Local, State, Federal, and Provincial					
			Er	vironme	ntal Re	egulations.	,		
14. TRANSPORTATION	INFORMATIO	ON							
United States: DOT Proper Shipping N UN Number: Hazard Class: Packing Group:	Name:			entanes N1265					
International: IATA Proper Shipping UN Number: Hazard Class: Packing Group:	Name:			entanes N1265					
Marine Pollutant: No Chemical Name		CAS#	Mar	rine Poll	utant	Sovoro	Marine		
onennear Name		540#	iviai		atam		utant		
No data available									
15. REGULATORY INFO									
United States:									
Chemical Name	CAS#	CERCL	CERCLA S		SARA 313		SARA EHS 313	TSCA	
Pentane	109-66-0	-			-		-	Х	
The following chemic	als are listed	on CA Prop	65:						
Chemical Name		CAS #		Reg	ulation	า			
State Right To Know I	istina:								
Chemical Name	CAS#	New Je	ersev	I	Mass	sachusetts	Pennsylvania	California	]
Pentane	109-66-0	X	,		X		X	X	1
hexane	110-54-3								1
Hexadecane	544-76-3								1
hexatriacontane	630-06-8								]
n-Octane	111-65-9						-		]
decane	124-18-5								
n-Dodecane	112-40-3								ļ
pentatriacontane	630-07-9							<u>_</u>	
heneicosane	629-94-7								
octacosane	630-02-4								J

# 16. OTHER INFORMATION

Prior Version Date:	06/18/18
Other Information:	Any changes to the SDS compared to previous versions are marked by a vertical
	line in front of the concerned paragraph.
References:	No data available
Disclaimer:	Restek Corporation provides the descriptions, data and information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. It is provided for your guidance only. Because many factors may affect processing or application/use, Restek Corporation recommends you perform an assessment to determine the suitability of a product for your particular purpose prior to use. No warranties of any kind, either expressed or implied, including fitness for a particular purpose, are made regarding products described, data or information set forth. In no case shall the descriptions, information, or data provided be considered a part of our terms and conditions of sale. Further, the descriptions, data and information furnished hereunder are given gratis. No obligation or liability for the description, data and information given are assumed. All such being given and accepted at your risk.