

## SAFETY DATA SHEET

#### 1. Identification

Product identifier LPS® 3 (Aerosol)

Other means of identification

Part Number 00316

Recommended use A specialized soft-film spray coating designed to prevent rust and corrosion on steel, aluminum

and other metals.

**Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer Manufacturer

Company name ITW Pro Brands

**Address** 4647 Hugh Howell Rd.

Tucker, GA 30084

Country (U.S.A.)

Tel: +1 770-243-8800

In Case of Emergency 1-800-424-9300 (inside U.S.)

+001 703-527-3887 (outside U.S.)

Website www.lpslabs.com

E-mail lpssds@itwprobrands.com

## 2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1

Gases under pressure Compressed gas

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2A

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin

irritation. Causes serious eye irritation.

**Precautionary statement** 

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open

flame or other ignition source. Do not pierce or burn, even after use. Wash thoroughly after

handling. Wear protective gloves and eye/face protection.

Response If swallowed: Call a poison center/doctor if you feel unwell. Rinse mouth. If in eyes: Rinse

cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. Specific treatment (see

this label). If skin irritation occurs: Get medical advice/attention.

Storage Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

**Supplemental information** None known.

Material name: LPS® 3 (Aerosol)

#### 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Distillates Petroleum Hydrotreate Light	d	64742-47-8	50 - 60
1-butoxy-2-propanol		5131-66-8	1 - 10
Acetone		67-64-1	1 - 10
Distillates Petroleum Hydrotreate Heavy	d	64742-54-7	1 - 10
Hydrodesulferized Heavy Petrole Naptha	um	64742-82-1	0.1 - 1
Petrolatum		8009-03-8	0.1 - 1

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

#### 4. First-aid measures

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or Inhalation

> artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a POISON CENTER or doctor/physician if you feel unwell.

In case of contact, immediately flush skin with plenty of water for at least 15 minutes while Skin contact

removing contaminated clothing and shoes. Get medical attention if irritation develops and

persists.

Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Eye contact

Get medical attention if irritation develops and persists.

Call a physician or poison control center immediately. Only induce vomiting at the instruction of Ingestion

medical personnel. Never give anything by mouth to an unconscious person. If vomiting occurs,

keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and delayed

Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Defatting of the skin. Rash. Symptoms of overexposure can include shortness of breath, drowsiness, headaches, confusion, decreased coordination, visual disturbances and vomiting, and

are reversible if exposure is stopped.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. In case of shortness of breath, give oxygen. Keep victim under observation. Symptoms may be delayed.

General information In the case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

#### 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Powder. Alcohol resistant foam. Carbon dioxide (CO2).

Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from

the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Special protective equipment and precautions for firefighters

Fire fighting equipment/instructions

Specific methods

General fire hazards

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Water runoff can cause

environmental damage. Use standard firefighting procedures and consider the hazards of other involved materials. Move

container from fire area if it can be done without risk. In the event of fire and/or explosion do not breathe fumes.

Extremely flammable aerosol.

## Accidental release measures

Personal precautions. protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.

# Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. The product is immiscible with water and will spread on the water surface. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Collect spillage. Use water spray to reduce vapors or divert vapor cloud drift. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

#### **Environmental precautions**

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

## Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Avoid breathing gas. Avoid contact with skin. Avoid contact with eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Wash hands thoroughly after handling. Avoid release to the environment.

# Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store locked up.

## 8. Exposure controls/personal protection

## Occupational exposure limits

U.S. - OSHA

Components	Туре	Value	Form
Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)	PEL	5 mg/m3	Oil mist
US. OSHA Table Z-1 Limits for Air Con	taminants (29 CFR 1910.1000)		
Components	Туре	Value	
Acetone (CAS 67-64-1)	PEL	2400 mg/m3	
		1000 ppm	
ACGIH			
Components	Туре	Value	Form
Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)	TWA	5 mg/m3	Oil mist
US. ACGIH Threshold Limit Values			
Components	Туре	Value	
Acetone (CAS 67-64-1)	STEL	500 ppm	
	TWA	250 ppm	
US. NIOSH: Pocket Guide to Chemical	Hazards		
Components	Туре	Value	
Acetone (CAS 67-64-1)	TWA	590 mg/m3	
		250 ppm	

#### **Biological limit values**

ACGIH Biological Exposure Indices				
Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine	*

<sup>\* -</sup> For sampling details, please see the source document.

Material name: LPS® 3 (Aerosol) SDS US

## Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

## Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Eye wash fountain is recommended.

Skin protection

**Hand protection** Chemical resistant gloves are recommended.

Other Avoid contact with clothing. Wear suitable protective clothing. Chemical resistant gloves.

**Respiratory protection** No personal respiratory protective equipment normally required. Use a positive-pressure

air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate

protection.

Thermal hazards Not applicable.

General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

### 9. Physical and chemical properties

Appearance Cloudy. Liquid.

Physical state Gas.
Form Aerosol.
Color Brown.

Odor Mild. Cherry.
Odor threshold Not available.
PH Not applicable
Melting point/freezing point Not available.
Initial boiling point and boiling Not available.

range

Flash point 64.4 °F (18.0 °C) Tag Closed Cup

**Evaporation rate** 151 (Ethyl Ether) **Flammability (solid, gas)** Flammable gas.

### Upper/lower flammability or explosive limits

Flammability limit - lower

0.6 %

6%

(%)

Flammability limit - upper

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 446 °F (230 °C)

Decomposition temperature Not available.

Viscosity Not available.

Other information

Density7.28 lb/galPercent volatile63 - 82 %Specific gravity0.87

62.8 % per U.S. State and Federal Consumer Product Regulations

## 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

VOC

Conditions to avoid Avoid temperatures exceeding the flash point.

**Incompatible materials** Strong oxidizing agents.

Hazardous decomposition Upon decomposition

products

Upon decomposition this product emits acrid dense smoke with carbon dioxide, carbon monoxide,

water and other products of combustion.

## 11. Toxicological information

### Information on likely routes of exposure

**Inhalation** Prolonged inhalation may be harmful.

**Skin contact** Causes skin irritation.

**Eye contact** Causes serious eye irritation.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms related to the physical, chemical and toxicological characteristics

LD50

Irritating to eyes, respiratory system and skin. Symptoms may include stinging, tearing, redness,

swelling, and blurred vision.

#### Information on toxicological effects

#### **Acute toxicity**

Components	Species	Test Results
1-butoxy-2-propanol (CAS 5	5131-66-8)	
<u>Acute</u>		
Dermal		
LD50	Rabbit	1400 mg/kg, 24 Hours
Oral		
LD50	Rat	> 2000 mg/kg
Acetone (CAS 67-64-1)		
<u>Acute</u>		
Inhalation		
LC50	Rat	50 mg/l, 8 Hours
Oral		
LD50	Rat	5800 mg/kg
Distillates Petroleum Hydrot	treated Light (CAS 64742-47-8)	
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
Vapor	5 .	
LC50	Rat	> 0.1 mg/l, 8 Hours
Oral		
LD50	Rat	> 5000 mg/kg
· •	etroleum Naptha (CAS 64742-82-1)	
Acute		
Dermal	D-LL:	4000
LD50	Rabbit	> 1900 mg/kg, 24 Hours
Oral		

Material name: LPS® 3 (Aerosol)
00316 Version #: 10 Revision date: 11-04-2019 Issue date: 10-14-2015

Rat

4800 mg/kg

Components **Species Test Results** 

Petrolatum (CAS 8009-03-8)

**Acute** Dermal

LD50 Rabbit > 2000 mg/kg, 24 Hours

Oral

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye

Causes serious eye irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Carcinogenicity

**ACGIH Carcinogens** 

Acetone (CAS 67-64-1) A4 Not classifiable as a human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** Not likely, due to the form of the product. **Chronic effects** Prolonged inhalation may be harmful.

**Further information** None known.

## 12. Ecological information

Not expected to be harmful to aquatic organisms. **Ecotoxicity** 

Components		Species	Test Results
Acetone (CAS 67-64-1)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	10294 - 17704 mg/l, 48 hours
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours
Distillates Petroleum Hydrot	reated Light (	(CAS 64742-47-8)	
Aquatic			
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)	2.9 mg/l, 96 hours
sistence and degradability	Not inhere	ently biodegradable.	

Per Bioaccumulative potential No data available for this product.

Partition coefficient n-octanol / water (log Kow)

-0.24Acetone

Mobility in soil Not available. Other adverse effects None known.

Material name: LPS® 3 (Aerosol)

## 13. Disposal considerations

**Disposal instructions**Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Hazardous waste code D001: Waste Flammable material with a flash point <140 F

D003: Waste Reactive material

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Do not re-use empty containers.

## 14. Transport information

#### DOT

UN number UN1950

UN proper shipping name Transport hazard class(es)

Aerosols, flammable

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not available.

**Environmental hazards** 

Marine pollutant No

Special precautions for user Not available.

Special provisionsN82Packaging exceptions306Packaging non bulkNonePackaging bulkNone

**IATA** 

UN number UN1950

UN proper shipping name

Transport hazard class(es)

Aerosols, flammable

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not available.

Environmental hazards No.

Special precautions for user Not available.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only

Allowed with restrictions.

**IMDG** 

UN number UN1950

**UN proper shipping name** Aerosols, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not available.

**Environmental hazards** 

Marine pollutant No

EmS Not available.

Special precautions for user Not available.

Transport in bulk according to Not available.

Annex II of MARPOL 73/78 and

the IBC Code



IATA; IMDG



## 15. Regulatory information

**US federal regulations** 

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

**Toxic Substances Control Act (TSCA)** 

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Acetone (CAS 67-64-1)

Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

categories

SARA 311/312 Hazardous

chemical

Yes

Classified hazard

Flammable (gases, aerosols, liquids, or solids)

Gas under pressure

Skin corrosion or irritation

Serious eye damage or eye irritation

SARA 313 (TRI reporting)

Not regulated.

#### Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1) 6532

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 %WV

Material name: LPS® 3 (Aerosol) SDS US

## **DEA Exempt Chemical Mixtures Code Number**

Acetone (CAS 67-64-1) 6532

#### FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Acetone (CAS 67-64-1) Low priority

#### US state regulations

#### US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1)

### California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

# US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Acetone (CAS 67-64-1)

Distillates Petroleum Hydrotreated Heavy (CAS 64742-54-7) Hydrodesulferized Heavy Petroleum Naptha (CAS 64742-82-1)

Inventory name

Petrolatum (CAS 8009-03-8)

#### International Inventories

Country(s) or region

Country(s) or region	inventory name	On inventory (yes/no)
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	No

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

 Issue date
 10-14-2015

 Revision date
 11-04-2019

Version # 10

United States & Puerto Rico

**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge,

Toxic Substances Control Act (TSCA) Inventory

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

**Revision information** Hazard(s) identification: Hazard statement

Hazard(s) identification: Response Hazard(s) identification: Storage

Composition / Information on Ingredients: Disclosure Overrides

GHS: Classification

Material name: LPS® 3 (Aerosol) SDS US

Yes

On inventory (yes/no)\*