

## SAFETY DATA SHEET

# **RECTORSEAL<sup>®</sup> TRU-BLU<sup>™</sup>**

Vibration resistant pipe thread sealant

### Section 1 - Product and Company Information

Product Name Rectorseal Tru-Blu

Product Codes 31300, 31431, 31551, 31631, 31780, 31782, 31001, 31002, 31003

Chemical Family Organic

Use

Pipe thread sealant

Manufacturer's Name RectorSeal LLC 2601 Spenwick Drive Houston, Texas 77055 USA

Date of validation September 2, 2021

Date of Preparation June 14, 2016 HMIS Codes

- Health 1
- Flammability 2
  - Reactivity 0

PPI B

Emergency Telephone No. Chemtrec 24 Hours (800) 424-9300 USA (703) 527-3887 International

Technical Service Telephone No. (800) 231-3345 or (713) 263-8001

## SECTION 2 - HAZARDS IDENTIFICATION

#### **Emergency Overview**

OSHA Hazards None

Target Organs Not classified

#### **GHS Classification**

**Physical Hazards** Combustible liquid (Category 4)

Health Hazards Not classified

Not classified

Acute Toxicity: Oral: Not Classified Dermal: Not Classified Inhalation: Not Classified Skin Corrosion/Irritation: Not Classified Serious Eye Damage/Eye Irritation: Not Classified

Vibration resistant pipe thread sealant

## SECTION 2 - HAZARDS IDENTIFICATION

Respiratory or Skin Sensitization: Not Classified Germ Cell Mutagenicity: Not Classified Carcinogenicity: See Section 11 Reproductive Toxicology: Not Classified Target Organ Systemic Toxicity - Single Exposure: Not Classified Target Organ Systemic Toxicity - Repeated Exposure: Not Classified

Aspiration Toxicity: Not Classified

#### GHS Label elements, including precautionary statements



GHS07: Exclamation Mark

Signal Word: Warning

Hazard Statements:

H303 - May be harmful if swallowed.

H313 - May be harmful in contact with skin.

H335 + H336 - May cause respiratory irritation, and drowsiness or dizziness.

**Precautionary Statements:** 

- P102 Keep out of reach of children.
- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking

P240 - Ground/Bond container and receiving equipment

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P262 - Do not get in eyes, on skin, or on clothing.

P264 - Wash hands thoroughly after handling.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P362 - Take off contaminated clothing and wash before reuse.

EUH066 - Repeated exposure may cause skin dryness or cracking. Precautionary Statements - EU No. 1272/2008

#### **Summary of Acute Hazards**

Irritation to eyes, nose and throat; drowsiness, narcosis, tremors and other CNS effects at high concentration.

#### **Route of Exposure, Signs And Symptoms**

**INHALATION** - Nasal and respiratory irritation, dizziness, narcosis, headache, nausea, CNS depression and unconsciousness. **EYE CONTACT** - Watering, blurred vision, inflammation and irritation which can result in corneal injury.

SKIN CONTACT - Irritation, dermatitis.

**INGESTION -** Nausea, vomiting; CNS depression; irritation of gastrointestinal tract, liver and peritoneal wall; lung congestion. **SUMMARY OF CHRONIC HAZARDS -** Skin irritation and dermatitis. Possible liver and kidney damage.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE -** Individuals with pre-existing or chronic diseases of the eyes, skin, respiratory system, cardiovascular system, gastrointestinal system, liver or kidneys may have increased susceptibility to excessive exposures.

Vibration resistant pipe thread sealant

## SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient:	Diacetone Alcohol
Percentage By Weight:	20-30
CAS Number:	123-42-2
EINEC:	204-626-7

## SECTION 4 - FIRST AID MEASURES

IF INHALED:	If overcome by exposure, remove victim to fresh air immediately. Give oxygen or artificial respiration as needed. Obtain emergency medical attention. Prompt action is essential.
IF ON SKIN:	Wash with soap and water. If irritation occurs, seek medical attention.
IF IN EYES:	Flush eyes with large amounts of water for 15 minutes. Get medical attention.
IF SWALLOWED:	If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person.

## Section 5 - Fire Fighting Measures

150°F (65°C)
N/D
N/D

#### **Extinguishing media**

Foam, dry chemical, CO<sub>2</sub>, or water fog.

#### Special fire fighting procedures

Wear self-contained breathing apparatus (SCBA) and other protective clothing. Hazardous decomposition products possible (see Section 10).

#### Unusual fire and explosion hazards

Combustible – moderate flash point. Vapors heavier than air and may travel along the ground or to low spots at considerable distances to a source of ignition resulting in potential flashback. Burning liquid may float on water. Heat may build up pressure and rupture containers.

## SECTION 6 - ACCIDENTAL RELEASE MEASURES

#### Steps to be taken in case material is released or spilled:

Remove all sources of ignition. Use absorbent materials to prevent footing hazard and to contain. Ventilate area with natural or explosion-proof, forced air ventilation. Avoid flushing into sewers, drains, waterways, and soil. Wear protective clothing and respiratory protection during cleanup.

Vibration resistant pipe thread sealant

#### SECTION 7 - HANDLING AND STORAGE

#### Precautions to be taken in handling and storing:

Units

Keep container closed and upright when not in use. Do not store near heat, sparks, or open flames.

#### **Other precautions:**

Avoid prolonged or repeated contact with skin or clothing. Empty containers may contain residues; treat as if full and observe all products precautions. Do not reuse empty containers. KEEP OUT OF REACH OF CHILDREN.

## SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Diacetone Alcohol

ACGIH TLV	50 ppm
OSHA PEL	50 ppm

RESPIRATORY PROTECTION (SPECIFY TYPE): In confined, poorly ventilated areas, use NIOSH/MSHA approved air purifying or supplied air respirators. VENTILATION - LOCAL EXHAUST: Acceptable SPECIAL: Explosion-proof equipment MECHANICAL (GENERAL): Preferable OTHER: N/A PROTECTIVE GLOVES: Wear rubber gloves. EYE PROTECTION: Safety glasses (ANSI Z-87.1 or equivalent) OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Coveralls recommended. WORK/HYGIENIC PRACTICES: Where use can result in skin contact, wash exposed areas thoroughly before eating, drinking, smoking, or leaving work area. Launder contaminated clothing before reuse.

#### SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: 322°F (161°C) @ 760mm Hg

SPECIFIC GRAVITY (H20 = 1): 1.38

VAPOR PRESSURE (MMHG): 0.3 @ 68°F (20°C)

MELTING POINT: N/A

VAPOR DENSITY (AIR = 1): 1.1

EVAPORATION RATE (ETHYL ACETATE = 1): 0.14

APPEARANCE/ODOR: Blue paste/Mild odor

SOLUBILITY IN WATER: 23%

VOLATILE ORGANIC COMPOUNDS (VOC) CONTENT (theoretical percentage by weight): 23% or (317 g/L)

Vibration resistant pipe thread sealant

## SECTION 10 - STABILITY AND REACTIVITY

## Stability:

Stable

**Conditions to avoid:** Heat, sparks, open flames, and strong oxidizing. Temperatures above 500°F (260°C).

**Incompatibility (materials to avoid):** Gaseous oxygen, strong oxidizing materials, molten alkali metals.

**Hazardous decomposition products:** CO, CO<sub>2</sub> and fragmented hydrocarbons.

Hazardous polymerization: Will not occur.

#### SECTION 11 - TOXICOLOGY INFORMATION

#### **Chronical Health Hazards:**

No ingredient in this product is an IARC, NTP, or OSHA listed carcinogen

#### **Toxicology Data:**

Ingredient name

Diacetone Alcohol

Oral-Rat LD50:	4000 mg/kg
Inhalation-Rat LC50:	100 ppm

### SECTION 12 - ECOLOGICAL INFORMATION

#### **Ecology Data:**

Ingredient name

#### **Diacetone Alcohol**

Food Chain Concentration Potential	N/A
Waterfowl Toxicity	N/A
BOD	N/A
Aquatic Toxicity	N/A

#### Section 13 - Disposal Considerations

#### Waste Classification: Non-regulated solid waste

#### Disposal Method: Approved landfill

Waste from this product is not considered hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Dispose of in accordance with Federal, State, and Local regulation regarding pollution.

Vibration resistant pipe thread sealant

## SECTION 14 - TRANSPORTATION INFORMATION

DOT: Non-Regulated OCEAN (IMDG): Non-Regulated AIR (IATA): Non-Regulated WHMIS (CANADA): Non-Regulated

### SECTION 15 - REGULATORY INFORMATION

## **Regulatory Data**

Ingredient	Diacetone Alcohol
SARA 313	N/A
TSCA Inventory	Yes
CERCLA RQ	N/A
RCRA Code	N/A

## Section 16 - Other Information

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). The information herein is given in good faith, but no warranty, expressed or implied is made. Consult RectorSeal for further information: (713) 263-8001