

**A00173 MST HD CARPET SPOT RMVR 20NET19**

Version 4.1

Revision Date 03/18/2019

Print Date 07/31/2020

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Material name : A00173 MST HD CARPET SPOT RMVR 20NET19

Material number : 00000000001001611

**Manufacturer or supplier's details**

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE  
Emerson, GA 30137

Telephone : 404-352-1680

**Emergency telephone numbers****For SDS Information** : Compliance Services 1-877-428-9937**For a Medical Emergency** : 877-541-2016 Toll Free - All Calls Recorded**For a Transportation Emergency** : CHEMTREC: 800-424-9300 - All Calls Recorded.  
In the District of Columbia 202-483-7616**Recommended use of the chemical and restrictions on use**Recommended use : Cleaner  
Carpet Care**SECTION 2. HAZARDS IDENTIFICATION****Emergency Overview**

Appearance	Aerosol containing a liquefied gas
Colour	clear
Odour	characteristic

**GHS Classification**

Gases under pressure : Liquefied gas

Eye irritation : Category 2A

Skin sensitisation : Category 1

**GHS label elements**

Hazard pictograms :



Signal word : Warning

Hazard statements : H280 Contains gas under pressure; may explode if heated.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.Precautionary statements : **Prevention:**  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
P264 Wash skin thoroughly after handling.

**A00173 MST HD CARPET SPOT RMVR 20NET19**

Version 4.1

Revision Date 03/18/2019

Print Date 07/31/2020

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/ eye protection/ face protection.

P251 Pressurized container: Do not pierce or burn, even after use.

**Response:**

P302 + P352 IF ON SKIN: Wash with plenty of water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P363 Wash contaminated clothing before reuse.

**Storage:**

P410 + P403 Protect from sunlight. Store in a well-ventilated place.

P412 Do not expose to temperatures exceeding 50 °C/ 122 °F.

**Disposal:**

P501 Dispose of contents/container in accordance with local regulation.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Hazardous components**

Chemical name	CAS-No.	Concentration [%]
propan-2-ol	67-63-0	>= 5 - < 10
2-(2-butoxyethoxy)ethanol	112-34-5	>= 5 - < 10
butane	106-97-8	>= 5 - < 10
acetone	67-64-1	>= 3 - < 5
D-Glucopyranose, oligomers, decyl octyl glycosides	68515-73-1	>= 1 - < 3
1-phenoxypropan-2-ol	770-35-4	>= 1 - < 3
propane	74-98-6	>= 1 - < 3
D-Glucopyranose, oligomeric, C10-16-alkyl glycosides	110615-47-9	>= 1 - < 3
sodium nitrite	7632-00-0	>= 0.1 - < 1
Oils, sweet orange (terpenes and terpenoids)	68647-72-3	>= 0.1 - < 1

The exact percentages of disclosed substances are withheld as trade secrets.

**SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

**A00173 MST HD CARPET SPOT RMVR 20NET19**

Version 4.1

Revision Date 03/18/2019

Print Date 07/31/2020

- advice.  
If symptoms persist, call a physician.
- In case of skin contact : In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
Wash contaminated clothing before re-use.  
Call a physician if irritation develops or persists.
- In case of eye contact : Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.  
If in eyes, rinse with water for 15 minutes.
- If swallowed : Keep respiratory tract clear.  
Never give anything by mouth to an unconscious person.  
DO NOT induce vomiting unless directed to do so by a physician or poison control center.  
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Effects are immediate and delayed.  
Symptoms may include irritation, redness, pain, and rash.  
Effects are dependent on exposure (dose, concentration, contact time).  
Causes serious eye irritation.  
May cause an allergic skin reaction.  
Review section 2 of SDS to see all potential hazards.
- Notes to physician : Treat symptomatically. Symptoms may be delayed.

---

**SECTION 5. FIREFIGHTING MEASURES**

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical  
Water spray jet
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon dioxide (CO<sub>2</sub>)  
Carbon monoxide  
Smoke
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : Standard procedure for chemical fires.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**A00173 MST HD CARPET SPOT RMVR 20NET19**

Version 4.1

Revision Date 03/18/2019

Print Date 07/31/2020

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.  
Evacuate personnel to safe areas.  
Remove all sources of ignition.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions : Prevent further leakage or spillage if safe to do so.  
Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Sweep up or vacuum up spillage and collect in suitable container for disposal.

**SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Always replace cap after use.  
Dispose of rinse water in accordance with local and national regulations.  
Do not breathe vapours or spray mist.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.  
No smoking.  
Observe label precautions.  
Keep in a dry, cool and well-ventilated place.  
Electrical installations / working materials must comply with the technological safety standards.

Materials to avoid : Strong oxidizing agents

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**
**Components with workplace control parameters**

Components	CAS-No.	Value type	Control	Basis
------------	---------	------------	---------	-------

## A00173 MST HD CARPET SPOT RMVR 20NET19

Version 4.1

Revision Date 03/18/2019

Print Date 07/31/2020

		(Form of exposure)	parameters / Permissible concentration	
propan-2-ol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m <sup>3</sup>	NIOSH REL
		ST	500 ppm 1,225 mg/m <sup>3</sup>	NIOSH REL
		TWA	400 ppm 980 mg/m <sup>3</sup>	OSHA Z-1
		TWA	400 ppm 980 mg/m <sup>3</sup>	OSHA P0
		STEL	500 ppm 1,225 mg/m <sup>3</sup>	OSHA P0
		PEL	400 ppm 980 mg/m <sup>3</sup>	CAL PEL
		STEL	500 ppm 1,225 mg/m <sup>3</sup>	CAL PEL
2-(2-butoxyethoxy)ethanol	112-34-5	TWA (Inhalable fraction and vapor)	10 ppm	ACGIH
butane	106-97-8	TWA	800 ppm 1,900 mg/m <sup>3</sup>	NIOSH REL
		TWA	800 ppm 1,900 mg/m <sup>3</sup>	OSHA P0
		PEL	800 ppm 1,900 mg/m <sup>3</sup>	CAL PEL
acetone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm 590 mg/m <sup>3</sup>	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m <sup>3</sup>	OSHA Z-1
		TWA	750 ppm 1,800 mg/m <sup>3</sup>	OSHA P0
		STEL	1,000 ppm 2,400 mg/m <sup>3</sup>	OSHA P0
		STEL	750 ppm 1,780 mg/m <sup>3</sup>	CAL PEL
		C	3,000 ppm	CAL PEL
		PEL	500 ppm 1,200 mg/m <sup>3</sup>	CAL PEL
propane	74-98-6	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,800 mg/m <sup>3</sup>	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m <sup>3</sup>	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m <sup>3</sup>	OSHA P0
		PEL	1,000 ppm 1,800 mg/m <sup>3</sup>	CAL PEL

## Biological occupational exposure limits

**A00173 MST HD CARPET SPOT RMVR 20NET19**

Version 4.1

Revision Date 03/18/2019

Print Date 07/31/2020

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
PROPAN-2-OL	67-63-0	Acetone	Urine	End of shift at end of workweek	40 mg/l	ACGIH BEI
2-PROPANONE	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI

**Engineering measures** : effective ventilation in all processing areas

**Personal protective equipment**

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.

Hand protection

Material

Remarks

: Protective gloves

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Tightly fitting safety goggles

Ensure that eyewash stations and safety showers are close to the workstation location.

Skin and body protection

: Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures

: When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : Aerosol containing a liquefied gas

Colour : clear

Odour : characteristic

Odour Threshold : No data available

pH : 9.5 - 10

Melting point/freezing point : No data available

Boiling point : No data available

Flash point :

**A00173 MST HD CARPET SPOT RMVR 20NET19**

Version 4.1

Revision Date 03/18/2019

Print Date 07/31/2020

	Not applicable
Evaporation rate	: 1 n-Butyl Acetate = 1.0
Flammability (solid, gas)	: The product is not flammable.
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: 4,136 hPa (21 °C)
Relative vapour density	: No data available
Density	: 0.985 g/cm <sup>3</sup>
Solubility(ies)	
Water solubility	: soluble
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: not determined
Thermal decomposition	: No data available
Viscosity	
Viscosity, kinematic	: No data available
Heat of combustion	: 10.46 kJ/g

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	: Carbon dioxide (CO <sub>2</sub> ) Carbon monoxide Nitrogen oxides (NO <sub>x</sub> )

**SECTION 11. TOXICOLOGICAL INFORMATION****Potential Health Effects**

## A00173 MST HD CARPET SPOT RMVR 20NET19

Version 4.1

Revision Date 03/18/2019

Print Date 07/31/2020

Aggravated Medical Condition : None known.  
 Symptoms of Overexposure : Effects are immediate and delayed.  
 Symptoms may include irritation, redness, pain, and rash.  
 Effects are dependent on exposure (dose, concentration, contact time).

**Carcinogenicity:**

**IARC** Group 2A: Probably carcinogenic to humans  
 sodium nitrite 7632-00-0

**ACGIH** No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

**OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP** No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Acute toxicity****Product:**

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg  
 Method: Calculation method

**Components:****propan-2-ol:**

Acute oral toxicity : LD50 Oral Rat: 4,396 mg/kg  
 Method: Calculation method

**acetone:**

Acute oral toxicity : LD50 Rat: 5,800 mg/kg

Acute inhalation toxicity : LC50 Rat: 132 mg/l  
 Exposure time: 3 h

LC50 Rat: 50.1 mg/l

Acute dermal toxicity : LD50 Guinea pig: > 7,426 mg/kg

LD50 Rabbit: > 7,426 mg/kg

**Skin corrosion/irritation****Product:**

Remarks: May cause skin irritation and/or dermatitis.

**Serious eye damage/eye irritation**



**A00173 MST HD CARPET SPOT RMVR 20NET19**

Version 4.1

Revision Date 03/18/2019

Print Date 07/31/2020

**Product:**

Remarks: Severe eye irritation

**Respiratory or skin sensitisation**

No data available

**Germ cell mutagenicity**

No data available

**Carcinogenicity**

No data available

**Reproductive toxicity**

No data available

**STOT - single exposure**

No data available

**STOT - repeated exposure**

No data available

**Aspiration toxicity**

No data available

**Further information****Product:**

Remarks: No data available

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential****Product:**Partition coefficient: n- : Remarks: No data available  
octanol/water**Components:****2-(2-butoxyethoxy)ethanol :**Partition coefficient: n- : Pow: 1  
octanol/water**butane :**Partition coefficient: n- : Pow: 2.89  
octanol/water

**A00173 MST HD CARPET SPOT RMVR 20NET19**

Version 4.1

Revision Date 03/18/2019

Print Date 07/31/2020

**D-Glucopyranose, oligomeric, C10-16-alkyl glycosides :**

 Partition coefficient: n-  
 octanol/water : Pow: 0.07

**Mobility in soil**

No data available

**Other adverse effects**

No data available

**Product:**

Regulation	40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks	This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).
Additional ecological information	: No data available

**SECTION 13. DISPOSAL CONSIDERATIONS**
**Disposal methods**

Waste from residues	: Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of in accordance with local regulations.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

**SECTION 14. TRANSPORT INFORMATION**

 Transportation Regulation: 49 CFR (USA):  
 UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

 Transportation Regulation: IMDG (Vessel):  
 UN1950, AEROSOLS, 2.2, - Limited quantity

 Transportation Regulation: IATA (Cargo Air):  
 UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

 Transportation Regulation: IATA (Passenger Air):  
 UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: TDG (Canada):

**A00173 MST HD CARPET SPOT RMVR 20NET19**

Version 4.1

Revision Date 03/18/2019

Print Date 07/31/2020

UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity
--

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

---

**SECTION 15. REGULATORY INFORMATION**

**TSCA list** : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

**EPCRA - Emergency Planning and Community Right-to-Know Act**
**CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
sodium nitrite	7632-00-0	100	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Gases under pressure  
 Serious eye damage or eye irritation  
 Respiratory or skin sensitisation

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

2-(2-butoxyethoxy)ethanol	112-34-5	6.3434 %
2-butoxyethanol	111-76-2	0.0966 %

**California Prop. 65**

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

**The components of this product are reported in the following inventories:**

**DSL** All components of this product are on the Canadian DSL

## A00173 MST HD CARPET SPOT RMVR 20NET19

Version 4.1

Revision Date 03/18/2019


Print Date 07/31/2020

TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

**Inventory Acronym and Validity Area Legend:**

TSCA (USA), DSL (Canada), NDSL (Canada)

**SECTION 16. OTHER INFORMATION****Further information****NFPA:****HMIS III:**

<b>HEALTH</b>	<b>3</b>
<b>FLAMMABILITY</b>	<b>1</b>
<b>PHYSICAL HAZARD</b>	<b>2</b>

0 = not significant, 1 = Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

**OSHA - GHS Label Information:**

Hazard pictograms



Signal word

: **Warning:**

Hazard statements

: Contains gas under pressure; may explode if heated. May cause an allergic skin reaction. Causes serious eye irritation.

Precautionary statements

**Prevention:** Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/ eye protection/ face protection. Pressurized container: Do not pierce or burn, even after use.

**Response:** IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Wash contaminated clothing before reuse.

**Storage:** Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50 °C/ 122 °F.

**Disposal:** Dispose of contents/container in accordance with local regulation.

Version:	4.1
Revision Date:	03/18/2019
Print Date:	07/31/2020

**A00173 MST HD CARPET SPOT RMVR 20NET19**

Version 4.1

Revision Date 03/18/2019

Print Date 07/31/2020

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®, Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®, Rexodan®, Mykal™, and a number of private labeled brands.