		Page: 1
<b>SAFETY DATA SHEET</b>		Revision Date: 06/07/2018
		Print Date: 9/3/2019
		SDS Number: R0382635
Valvoline™ Full Synthetic ATF+4 Automatic Transmission Fluid ™ Trademark, Valvoline or its subsidiaries, registered in various countries 822348		Version: 1.6

29 CFR 1910.1200 (OSHA HazCom 2012)

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

**Product identifier**

Trade name : Valvoline™ Full Synthetic ATF+4 Automatic Transmission Fluid

™ Trademark, Valvoline or its subsidiaries, registered in various countries

**Relevant identified uses of the substance or mixture and uses advised against**

Recommended use : Engine, gear & lubricating oil.

<b>Details of the supplier of the safety data sheet</b> Valvoline LLC 100 Valvoline Way Lexington, KY 40509 United States of America (USA) 1-800-TEAMVAL (1-800-832-6825)	<b>Emergency telephone number</b> 1-800-VALVOLINE (1-800-825-8654)  <b>Regulatory Information Number</b> 1-800-TEAMVAL (1-800-832-6825)  <b>Product Information</b> 1-800-TEAMVAL (1-800-832-6825)
--	---

**SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification**

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

**GHS label elements**

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

Chemical nature : Defatter

**Hazardous components**

Chemical name	CAS-No.	Classification	Concentration (%)
---------------	---------	----------------	-------------------

**SAFETY DATA SHEET**

Revision Date: 06/07/2018

Print Date: 9/3/2019

SDS Number: R0382635


Version: 1.6

Valvoline™ Full Synthetic ATF+4 Automatic Transmission Fluid  
 ™ Trademark, Valvoline or its subsidiaries, registered in various  
 countries  
 822348

HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).	>=50.00 - < 60.00
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	Asp. Tox. 1; H304	>=30.00 - < 40.00
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	Asp. Tox. 1; H304	>=1.50 - < 5.00
Mineral Oil		Asp. Tox. 1; H304	>=1.50 - < 5.00
DODECYL HYDROXYPROPYL SULFIDE	67124-09-8	Skin Sens. 1; H317	>=0.50 - < 1.00

**SECTION 4. FIRST AID MEASURES**

- General advice : No hazards which require special first aid measures.
- If inhaled : If breathed in, move person into fresh air.  
If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : Remove contact lenses.  
Protect unharmed eye.
- If swallowed : Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes

	Page: 3
<b>SAFETY DATA SHEET</b>	Revision Date: 06/07/2018
	Print Date: 9/3/2019
	SDS Number: R0382635
Valvoline™ Full Synthetic ATF+4 Automatic Transmission Fluid ™ Trademark, Valvoline or its subsidiaries, registered in various countries 822348	Version: 1.6

appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:  
acne  
stomach or intestinal upset (nausea, vomiting, diarrhea)  
irritation (nose, throat, airways)

Notes to physician : No hazards which require special first aid measures.

---

## SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Water spray  
Foam  
Carbon dioxide (CO2)  
Dry chemical
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon dioxide and carbon monoxide  
Hydrocarbons  
Aldehydes
- Specific extinguishing methods :  
  
Product is compatible with standard fire-fighting agents.
- Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

---

## SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

**SAFETY DATA SHEET**

Revision Date: 06/07/2018

Print Date: 9/3/2019

SDS Number: R0382635

Version: 1.6

Valvoline™ Full Synthetic ATF+4 Automatic Transmission Fluid  
 ™ Trademark, Valvoline or its subsidiaries, registered in various  
 countries  
 822348

emergency procedures

Environmental precautions : Prevent product from entering drains.  
 Prevent further leakage or spillage if safe to do so.  
 If the product contaminates rivers and lakes or drains inform  
 respective authorities.

Methods and materials for : Soak up with inert absorbent material (e.g. sand, silica gel,  
 containment and cleaning up acid binder, universal binder, sawdust).  
 Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

**SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Smoking, eating and drinking should be prohibited in the  
 application area.  
 For personal protection see section 8.

Conditions for safe storage : Containers which are opened must be carefully resealed and  
 kept upright to prevent leakage.

Materials to avoid : No materials to be especially mentioned.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	TWA	5 mg/m3 Mist	OSHA Z-1



**SAFETY DATA SHEET**

Revision Date: 06/07/2018

Print Date: 9/3/2019

SDS Number: R0382635

Version: 1.6

Valvoline™ Full Synthetic ATF+4 Automatic Transmission Fluid  
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries  
 822348

		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL

**Engineering measures** : General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

**Personal protective equipment**

Respiratory protection : No personal respiratory protective equipment normally required.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Wear resistant gloves (consult your safety equipment supplier).  
 Wear as appropriate:  
 Safety shoes

Hygiene measures : General industrial hygiene practice.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

**SAFETY DATA SHEET**

Revision Date: 06/07/2018

Print Date: 9/3/2019

SDS Number: R0382635

Version: 1.6

Valvoline™ Full Synthetic ATF+4 Automatic Transmission Fluid  
™ Trademark, Valvoline or its subsidiaries, registered in various  
countries  
822348

Physical state : liquid

Colour : red

Odour : No data available

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : No data available

Flash point : > 390 °F / > 199 °C  
Method: Cleveland open cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit : 6 %(V)  
Calculated Explosive Limit

Lower explosion limit : 1 %(V)  
Calculated Explosive Limit

Vapour pressure : 0.0133333 hPa (21.11 °C)  
Calculated Vapor Pressure

Relative vapour density : No data available

Relative density : 0.854 (15.6 °C)

Density : 0.8508 g/cm<sup>3</sup> (15.56 °C)

Solubility(ies)

Water solubility : Not applicable

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : < 10,000 mPa.sMethod: Brookfield

**SAFETY DATA SHEET**

Revision Date: 06/07/2018

Print Date: 9/3/2019

SDS Number: R0382635

Version: 1.6

Valvoline™ Full Synthetic ATF+4 Automatic Transmission Fluid  
™ Trademark, Valvoline or its subsidiaries, registered in various  
countries  
822348

Viscosity, kinematic : ca. 34 mm<sup>2</sup>/s (40 °C)

Oxidizing properties : No data available

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Product will not undergo hazardous polymerization.

Conditions to avoid : excessive heat

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : carbon dioxide and carbon monoxide  
Hydrocarbons

**SECTION 11. TOXICOLOGICAL INFORMATION**

Information on likely routes of exposure : Inhalation  
Skin contact  
Eye Contact  
Ingestion

**Acute toxicity**

Not classified based on available information.

**Components:**

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: Not classified as acutely toxic by inhalation under GHS.  
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Remarks: No mortality observed at this dose.

**SAFETY DATA SHEET**

Revision Date: 06/07/2018

Print Date: 9/3/2019

SDS Number: R0382635

Version: 1.6

Valvoline™ Full Synthetic ATF+4 Automatic Transmission Fluid  
™ Trademark, Valvoline or its subsidiaries, registered in various  
countries  
822348

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:  
Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

**DODECYL HYDROXYPROPYL SULFIDE:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
GLP: yes

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Assessment: Not classified as acutely toxic by dermal  
absorption under GHS.

**Skin corrosion/irritation**

Not classified based on available information.

**Components:****HYDROTREATED LIGHT PARAFFINIC DISTILLATE:**

Species: Rabbit

Result: No skin irritation

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Result: Slight, transient irritation

**HYDROTREATED LIGHT PARAFFINIC DISTILLATE:**

Result: Slight, transient irritation

**DODECYL HYDROXYPROPYL SULFIDE:**

Species: Rabbit

Result: No skin irritation

**Serious eye damage/eye irritation**

Not classified based on available information.

**Product:**

Result: Slight, transient irritation

Remarks: Expected based on components.

Remarks: Unlikely to cause eye irritation or injury.

**Components:****HYDROTREATED LIGHT PARAFFINIC DISTILLATE:**

Species: Rabbit

Result: No eye irritation

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Result: No eye irritation

**HYDROTREATED LIGHT PARAFFINIC DISTILLATE:**

Result: Slight, transient irritation



**SAFETY DATA SHEET**

Revision Date: 06/07/2018

Print Date: 9/3/2019

SDS Number: R0382635

Version: 1.6

Valvoline™ Full Synthetic ATF+4 Automatic Transmission Fluid  
™ Trademark, Valvoline or its subsidiaries, registered in various  
countries  
822348

**DODECYL HYDROXYPROPYL SULFIDE:**

Species: Rabbit

Result: No eye irritation

**Respiratory or skin sensitisation**

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

**Components:****HYDROTREATED LIGHT PARAFFINIC DISTILLATE:**

Test Type: Buehler Test

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

**DODECYL HYDROXYPROPYL SULFIDE:**

Test Type: Local lymph node assay

Species: Guinea pig

Assessment: May cause sensitisation by skin contact.

Method: OECD Test Guideline 429

**Germ cell mutagenicity**

Not classified based on available information.

**Components:****DODECYL HYDROXYPROPYL SULFIDE:**

Genotoxicity in vitro : Test Type: Ames test

Test species: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

**Carcinogenicity**

Not classified based on available information.

**Reproductive toxicity**

Not classified based on available information.

**STOT - single exposure**

Not classified based on available information.

**STOT - repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

**Components:****HYDROTREATED LIGHT PARAFFINIC DISTILLATE:**

May be fatal if swallowed and enters airways.

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

May be fatal if swallowed and enters airways.

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

Mineral Oil:

**SAFETY DATA SHEET**

Revision Date: 06/07/2018

Print Date: 9/3/2019

SDS Number: R0382635

Version: 1.6

Valvoline™ Full Synthetic ATF+4 Automatic Transmission Fluid  
 ™ Trademark, Valvoline or its subsidiaries, registered in various  
 countries  
 822348

May be fatal if swallowed and enters airways.

**Further information****Product:**

Remarks: No data available

**Carcinogenicity:****IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Product:**

Ecotoxicology Assessment

Acute aquatic toxicity : Acute aquatic toxicity Category 3; Harmful to aquatic life.

Chronic aquatic toxicity : Chronic aquatic toxicity Category 3; Harmful to aquatic life with long lasting effects.

**Components:**

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
 Exposure time: 96 h  
 Test Type: static test  
 Test substance: WAF  
 Method: OECD Test Guideline 203  
 Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l  
 Exposure time: 48 h  
 Test Type: static test  
 Test substance: WAF  
 Method: OECD Test Guideline 202

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l  
 End point: Growth inhibition  
 Exposure time: 72 h  
 Test Type: static test

**SAFETY DATA SHEET**

Revision Date: 06/07/2018

Print Date: 9/3/2019

SDS Number: R0382635

Version: 1.6

Valvoline™ Full Synthetic ATF+4 Automatic Transmission Fluid  
 ™ Trademark, Valvoline or its subsidiaries, registered in various  
 countries  
 822348

Test substance: WAF  
 Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOELR (Oncorhynchus mykiss (rainbow trout)): Calculated >= 1,000 mg/l  
 Exposure time: 14 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL (Daphnia (water flea)): 10 mg/l  
 Exposure time: 21 d  
 Test substance: WAF  
 Method: OECD Test Guideline 211

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:  
 Toxicity to fish : LL50 (Fish): > 100 mg/l  
 Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EL50 (Aquatic invertebrates): > 10,000 mg/l  
 Exposure time: 48 h

Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l  
 Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC (Fish): 10 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Aquatic invertebrates): 10 mg/l

DODECYL HYDROXYPROPYL SULFIDE:  
 Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.75 mg/l  
 Exposure time: 96 h  
 Test Type: semi-static test  
 Method: OECD Test Guideline 203  
 GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 0.58 mg/l  
 Exposure time: 48 h  
 Test Type: static test  
 Test substance: WAF

Toxicity to algae : EL50 (Desmodesmus subspicatus (green algae)): > 100 mg/l  
 Exposure time: 96 h  
 Test Type: static test  
 Test substance: WAF

M-Factor (Acute aquatic toxicity) : 1

Toxicity to daphnia and other : NOEL (Daphnia magna (Water flea)): 0.32 mg/l

**SAFETY DATA SHEET**

Revision Date: 06/07/2018

Print Date: 9/3/2019

SDS Number: R0382635

Version: 1.6

Valvoline™ Full Synthetic ATF+4 Automatic Transmission Fluid  
™ Trademark, Valvoline or its subsidiaries, registered in various  
countries  
822348

aquatic invertebrates  
(Chronic toxicity)

Exposure time: 21 d  
Test Type: semi-static test  
Method: OECD Test Guideline 211  
GLP: yes

M-Factor (Chronic aquatic toxicity) : 1

**Persistence and degradability****Components:****HYDROTREATED LIGHT PARAFFINIC DISTILLATE:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 2 - 4 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B

**DODECYL HYDROXYPROPYL SULFIDE:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 5 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

No data available

**Bioaccumulative potential****Components:****DODECYL HYDROXYPROPYL SULFIDE:**

Partition coefficient: n-octanol/water : log Pow: 4.7 - 6.5

No data available

**Mobility in soil****Components:**

No data available

**Other adverse effects**

No data available

**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.

**Components:****SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

General advice : Dispose of in accordance with all applicable local, state and federal regulations.

The product should not be allowed to enter drains, water courses or the soil.



**SAFETY DATA SHEET**

Revision Date: 06/07/2018

Print Date: 9/3/2019

SDS Number: R0382635

Version: 1.6

Valvoline™ Full Synthetic ATF+4 Automatic Transmission Fluid  
 ™ Trademark, Valvoline or its subsidiaries, registered in various  
 countries  
 822348

Contaminated packaging : Empty remaining contents.  
 Dispose of as unused product.  
 Empty containers should be taken to an approved waste  
 handling site for recycling or disposal.

**SECTION 14. TRANSPORT INFORMATION**

**International transport regulations**

**REGULATION**

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

**U.S. DOT - ROAD**

Not dangerous goods
---------------------

**CFR\_RAIL\_C**

Not dangerous goods
---------------------

**U.S. DOT - INLAND WATERWAYS**

Not dangerous goods
---------------------

**TDG\_ROAD\_C**

Not dangerous goods
---------------------

**TDG\_RAIL\_C**

Not dangerous goods
---------------------

**TDG\_INWT\_C**

Not dangerous goods
---------------------

**INTERNATIONAL MARITIME DANGEROUS GOODS**

Not dangerous goods
---------------------

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO**

Not dangerous goods
---------------------

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER**



**SAFETY DATA SHEET**

Revision Date: 06/07/2018

Print Date: 9/3/2019

SDS Number: R0382635

Version: 1.6

Valvoline™ Full Synthetic ATF+4 Automatic Transmission Fluid  
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries  
 822348

Not dangerous goods

**MX\_DG**

Not dangerous goods

**\*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

**SECTION 15. REGULATORY INFORMATION**

**EPCRA - Emergency Planning and Community Right-to-Know Act  
 CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
BENZENE	71-43-2	10	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
SULFUR DIOXIDE	7446-09-5	500	*
SULFUR DIOXIDE	7446-09-5		*

\*: Calculated RQ exceeds reasonably attainable upper limit.

**SARA 311/312 Hazards** : No SARA Hazards

**SARA 313** This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**California Prop 65** This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

**The components of this product are reported in the following inventories:**

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

ENCS : Not in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

**SAFETY DATA SHEET**

Revision Date: 06/07/2018

Print Date: 9/3/2019

SDS Number: R0382635

Version: 1.6

Valvoline™ Full Synthetic ATF+4 Automatic Transmission Fluid  
 ™ Trademark, Valvoline or its subsidiaries, registered in various  
 countries  
 822348

- PICCS : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory
- TSCA : On TSCA Inventory


**Inventories**

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

**SECTION 16. OTHER INFORMATION**

**Further information**

Revision Date: 06/07/2018

<p><b>NFPA:</b></p>  <p>Health: 0, Flammability: 1, Instability: 0, Special hazard.</p>	<p><b>HMIS III:</b></p> <table border="1"> <tr> <td style="background-color: blue; color: white;"><b>HEALTH</b></td> <td style="text-align: center;"><b>0</b></td> </tr> <tr> <td style="background-color: red; color: white;"><b>FLAMMABILITY</b></td> <td style="text-align: center;"><b>1</b></td> </tr> <tr> <td style="background-color: yellow; color: black;"><b>PHYSICAL HAZARD</b></td> <td style="text-align: center;"><b>0</b></td> </tr> </table> <p>0 = not significant, 1 =Slight,                  2 = Moderate, 3 = High                  4 = Extreme, * = Chronic</p>	<b>HEALTH</b>	<b>0</b>	<b>FLAMMABILITY</b>	<b>1</b>	<b>PHYSICAL HAZARD</b>	<b>0</b>
<b>HEALTH</b>	<b>0</b>						
<b>FLAMMABILITY</b>	<b>1</b>						
<b>PHYSICAL HAZARD</b>	<b>0</b>						


**NFPA Flammable and Combustible Liquids Classification**

Combustible Liquid Class IIIB

**Full text of H-Statements**

- H304 May be fatal if swallowed and enters airways.
- H317 May cause an allergic skin reaction.

Sources of key data used to compile the Safety Data Sheet  
 Valvoline internal data including own and sponsored test reports  
 The UNECE administers regional agreements implementing harmonised classification for  
 labelling (GHS) and transport.

		Page: 16
<b>SAFETY DATA SHEET</b>		Revision Date: 06/07/2018
		Print Date: 9/3/2019
		SDS Number: R0382635
Valvoline™ Full Synthetic ATF+4 Automatic Transmission Fluid ™ Trademark, Valvoline or its subsidiaries, registered in various countries 822348		Version: 1.6

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).


List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists  
BEI : Biological Exposure Index  
CAS : Chemical Abstracts Service (Division of the American Chemical Society).  
CMR : Carcinogenic, Mutagenic or Toxic for Reproduction  
FG : Food grade  
GHS : Globally Harmonized System of Classification and Labeling of Chemicals.  
H-statement : Hazard Statement  
IATA : International Air Transport Association.  
IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization  
ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"  
IMDG : International Maritime Code for Dangerous Goods  
ISO : International Organization for Standardization  
logPow : octanol-water partition coefficient  
LCxx : Lethal Concentration, for xx percent of test population  
LDxx : Lethal Dose, for xx percent of test population.  
ICxx : Inhibitory Concentration for xx of a substance  
Ecxx : Effective Concentration of xx  
N.O.S.: Not Otherwise Specified  
OECD : Organization for Economic Co-operation and Development  
OEL : Occupational Exposure Limit  
P-Statement : Precautionary Statement  
PBT : Persistent , Bioaccumulative and Toxic  
PPE : Personal Protective Equipment  
STEL : Short-term exposure limit  
STOT : Specific Target Organ Toxicity  
TLV : Threshold Limit Value  
TWA : Time-weighted average  
vPvB : Very Persistent and Very Bioaccumulative  
WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act  
DOT : Department of Transportation  
FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act  
HMIRC : Hazardous Materials Information Review Commission  
HMIS : Hazardous Materials Identification System  
NFPA : National Fire Protection Association  
NIOSH : National Institute for Occupational Safety and Health  
OSHA : Occupational Safety and Health Administration  
PMRA : Health Canada Pest Management Regulatory Agency



	Page: 17
<b>SAFETY DATA SHEET</b>	Revision Date: 06/07/2018
	Print Date: 9/3/2019
	SDS Number: R0382635
Valvoline™ Full Synthetic ATF+4 Automatic Transmission Fluid ™ Trademark, Valvoline or its subsidiaries, registered in various countries 822348	Version: 1.6

RTK : Right to Know

WHMIS : Workplace Hazardous Materials Information System