Valvoline.	Page: 1
SAFETY DATA SHEET	Revision Date: 02/05/2019
	Print Date: 2/4/2020
	SDS Number: R0412087
Valvoline™ Full Synthetic DEXRON VI and MERCON LV Automatic Transmission Fluid ™ Trademark, Valvoline or its subsidiaries, registered in various countries 822405	Version: 1.7

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Valvoline™ Full Synthetic DEXRON VI and MERCON LV

Automatic Transmission Fluid

™ Trademark, Valvoline or its subsidiaries, registered in

various countries

Details of the supplier of the safety data sheet

Valvoline LLC

100 Valvoline Way
Lexington, KY 40509
United States of America (USA)
1-800-TEAMVAL (1-800-832-6825)

SDS@valvoline.com

Emergency telephone number
1-800-VALVOLINE (1-800-825-8654)

Regulatory Information Number
1-800-TEAMVAL (1-800-832-6825)

Product Information
1-800-TEAMVAL (1-800-832-6825)

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	Asp. Tox. 1; H304	>=30.00 - < 40.00
MINERAL OIL		Not a hazardous	>=5.00 - < 10.00

Valvoline.	Page: 2
SAFETY DATA SHEET	Revision Date: 02/05/2019
	Print Date: 2/4/2020
	SDS Number: R0412087
Valvoline™ Full Synthetic DEXRON VI and MERCON LV Automatic Transmission Fluid ™ Trademark, Valvoline or its subsidiaries, registered in various countries 822405	Version: 1.7

		substance or mixture.	
METHACRYLATE COPOLYMER		Eye Irrit. 2A; H319	>=1.50 - < 5.00
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	Asp. Tox. 1; H304	>=1.00 - < 1.50

SECTION 4. FIRST AID MEASURES

General advice : No hazards which require special first aid measures.

If inhaled : If breathed in, move person into fresh air.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : First aid is not normally required. However, it is

recommended that exposed areas be cleaned by washing

with soap and water.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

If swallowed : Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

: No symptoms known or expected.

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray

Foam

Carbon dioxide (CO2)

Dry chemical

Specific hazards during : Do not allow run-off from fire fighting to enter drains or water

Valvoline.	Page: 3
SAFETY DATA SHEET	Revision Date: 02/05/2019
	Print Date: 2/4/2020
	SDS Number: R0412087
Valvoline™ Full Synthetic DEXRON VI and MERCON LV Automatic Transmission Fluid ™ Trademark, Valvoline or its subsidiaries, registered in various	Version: 1.7
countries 822405	

firefighting courses.

Hazardous combustion

products

: carbon dioxide and carbon monoxide

Hydrocarbons

Specific extinguishing

methods

: Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Conditions for safe storage : Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Materials to avoid : No materials to be especially mentioned.

Valvoline.	Page: 4
SAFETY DATA SHEET	Revision Date: 02/05/2019
	Print Date: 2/4/2020
	SDS Number: R0412087
Valvoline™ Full Synthetic DEXRON VI and MERCON LV Automatic Transmission Fluid ™ Trademark, Valvoline or its subsidiaries, registered in various countries 822405	Version: 1.7

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of	Control	Basis
		exposure)	parameters / Permissible concentration	
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL
MINERAL OIL		TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL

Engineering measures

: General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure

Valvoline.	Page: 5
SAFETY DATA SHEET	Revision Date: 02/05/2019
	Print Date: 2/4/2020
	SDS Number: R0412087
Valvoline™ Full Synthetic DEXRON VI and MERCON LV Automatic Transmission Fluid ™ Trademark, Valvoline or its subsidiaries, registered in various countries 822405	Version: 1.7

guidelines (if applicable) or below levels that cause known,

suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection No personal respiratory protective equipment normally

required.

Eye protection Not required under normal conditions of use. Wear splash-

proof safety goggles if material could be misted or splashed

into eyes.

Skin and body protection Wear as appropriate:

Safety shoes

Wear resistant gloves (consult your safety equipment

supplier).

Hygiene measures General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance liquid

Colour red

Odour No data available

Odour Threshold No data available

рΗ No data available

No data available Melting point/freezing point

Boiling point/boiling range No data available

> 356 °F / > 180 °C Flash point

Method: Cleveland open cup

Evaporation rate No data available

Flammability (solid, gas) No data available

Self-ignition No data available

Upper explosion limit / Upper

flammability limit

6 %(V)

GLP: Calculated Explosive Limit

Valvoline.	Page: 6
SAFETY DATA SHEET	Revision Date: 02/05/2019
	Print Date: 2/4/2020
	SDS Number: R0412087
Valvoline™ Full Synthetic DEXRON VI and MERCON LV Automatic Transmission Fluid	Version: 1.7
™ Trademark, Valvoline or its subsidiaries, registered in various countries	
822405	

Lower explosion limit / Lower : 1 %(V)

flammability limit GLP: Calculated Explosive Limit

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : 0.849 g/cm3 (60.01 °F / 15.56 °C)

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 29.5 mm2/s (104 °F / 40 °C)

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous

reactions

: Product will not undergo hazardous polymerization.

Conditions to avoid : excessive heat

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Valvoline.	Page: 7
SAFETY DATA SHEET	Revision Date: 02/05/2019
	Print Date: 2/4/2020
	SDS Number: R0412087
Valvoline™ Full Synthetic DEXRON VI and MERCON LV	Version: 1.7
Automatic Transmission Fluid	
™ Trademark, Valvoline or its subsidiaries, registered in various	
countries	
822405	

Information on likely routes of exposure

Inhalation Skin contact Eye Contact Ingestion

Acute toxicity

Not classified based on available information.

Product:

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: Not classified as acutely toxic by inhalation

under GHS.

Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Remarks: No mortality observed at this dose.

Skin corrosion/irritation

Not classified based on available information.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Species : Rabbit

Result : No skin irritation

MINERAL OIL:

Assessment : Slight, transient irritation Result : Slight, transient irritation

METHACRYLATE COPOLYMER:

Result : No skin irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Assessment : Slight, transient irritation Result : Slight, transient irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks : Unlikely to cause eye irritation or injury.

Valvoline.	Page: 8
SAFETY DATA SHEET	Revision Date: 02/05/2019
	Print Date: 2/4/2020
	SDS Number: R0412087
Valvoline™ Full Synthetic DEXRON VI and MERCON LV Automatic Transmission Fluid ™ Trademark, Valvoline or its subsidiaries, registered in various countries 822405	Version: 1.7

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Species : Rabbit

Result : No eye irritation

MINERAL OIL:

Result : Slight, transient irritation
Assessment : Slight, transient irritation

METHACRYLATE COPOLYMER:

Result : Irritating to eyes.

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result : Slight, transient irritation
Assessment : Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Test Type : Buehler Test Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Components: MINERAL OIL:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

IARC No component of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

OSHANo component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

Valvoline.	Page: 9
SAFETY DATA SHEET	Revision Date: 02/05/2019
	Print Date: 2/4/2020
	SDS Number: R0412087
Valvoline™ Full Synthetic DEXRON VI and MERCON LV Automatic Transmission Fluid ™ Trademark, Valvoline or its subsidiaries, registered in various countries 822405	Version: 1.7

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Short-term (acute) aquatic

hazard

: Acute aquatic toxicity Category 3; Harmful to aquatic life.

Long-term (chronic) aquatic

hazard

: Chronic aquatic toxicity Category 3; Harmful to aquatic life

with long lasting effects.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 203

Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other

aquatic invertebrates

: EL50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 48 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 202

Valvoline.	Page: 10
SAFETY DATA SHEET	Revision Date: 02/05/2019
	Print Date: 2/4/2020
	SDS Number: R0412087
Valvoline™ Full Synthetic DEXRON VI and MERCON LV Automatic Transmission Fluid ™ Trademark, Valvoline or its subsidiaries, registered in various countries 822405	Version: 1.7

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >=

100 mg/l

End point: Growth inhibition

Exposure time: 72 h
Test Type: static test
Test substance: WAF

Method: OECD Test Guideline 201

Toxicity to fish (Chronic

toxicity)

: NOELR (Oncorhynchus mykiss (rainbow trout)): Calculated >=

1,000 mg/l

Exposure time: 14 d

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: NOEL (Daphnia (water flea)): 10 mg/l

Exposure time: 21 d Test substance: WAF

Method: OECD Test Guideline 211

Persistence and degradability

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 2 - 4 % Exposure time: 28 d

Method: OECD Test Guideline 301B

No data available

Bioaccumulative potential

Components:
No data available
Mobility in soil
Components:
No data available
Other adverse effects
No data available

Product:

Additional ecological

information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life

with long lasting effects.

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Dispose of in accordance with all applicable local, state and

federal regulations.

The product should not be allowed to enter drains, water

Valvoline.	Page: 11
SAFETY DATA SHEET	Revision Date: 02/05/2019
	Print Date: 2/4/2020
	SDS Number: R0412087
Valvoline™ Full Synthetic DEXRON VI and MERCON LV Automatic Transmission Fluid ™ Trademark, Valvoline or its subsidiaries, registered in various countries 822405	Version: 1.7

courses or the soil.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Empty containers should be taken to an approved waste

handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT /
					LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods	

CFR_RAIL_C

Not dangerous goods		

U.S. DOT - INLAND WATERWAYS

Not dangerous goods	

TDG_ROAD_C

Not dangerous goods

TDG_RAIL_C

Not dangerous goods	

TDG_INWT_C

Not dangerous goods	

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods	MARINE POLLUTANT:(
	HETEROCYCL IC ETHER,
	OLEYLAMINE)

Valvoline.	Page: 12
SAFETY DATA SHEET	Revision Date: 02/05/2019
	Print Date: 2/4/2020
	SDS Number: R0412087
Valvoline™ Full Synthetic DEXRON VI and MERCON LV Automatic Transmission Fluid ™ Trademark, Valvoline or its subsidiaries, registered in various countries 822405	Version: 1.7

INTERNATIONAL	AIR TRANSPORT	ASSOCIATION - CARGO
---------------	---------------	----------------------------

Not dangerous goods	

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX DG

Not dangerous goods	

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : No SARA Hazards

California Prop. 65

This product contains a chemical that is at or below California Propositions 65's "safe harbor level" for carcinogenicity as determined via a risk assessment. Therefore, the chemical is not required to be listed as a Prop 65 chemical on the SDS or label.

This product contains a chemical that is at or below California Propositions 65's "safe harbor level" for reproductive/developmental toxicity as determined via a risk assessment. Therefore, the chemical is not required to be listed as a Prop 65 chemical on the SDS or label.

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

ENCS : Not in compliance with the inventory

Valvoline.	Page: 13
SAFETY DATA SHEET	Revision Date: 02/05/2019
	Print Date: 2/4/2020
	SDS Number: R0412087
Valvoline™ Full Synthetic DEXRON VI and MERCON LV Automatic Transmission Fluid ™ Trademark, Valvoline or its subsidiaries, registered in various countries 822405	Version: 1.7

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : On the inventory, or in compliance with the inventory

TSCA : On TSCA Inventory


TSCA list

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 02/05/2019



NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.

Valvoline.	Page: 14
SAFETY DATA SHEET	Revision Date: 02/05/2019
	Print Date: 2/4/2020
	SDS Number: R0412087
Valvoline™ Full Synthetic DEXRON VI and MERCON LV	Version: 1.7
Automatic Transmission Fluid	
™ Trademark, Valvoline or its subsidiaries, registered in various	
countries	
822405	

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH: American Conference of Industrial Hygienists

BEI: Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic

PPE: Personal Protective Equipment STEL: Short-term exposure limit STOT: Specific Target Organ Toxicity

TLV: Threshold Limit Value TWA: Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

DOT: Department of Transportation

FIFRA: Federal Insecticide, Fungicide, and Rodenticide Act

Valvoline.	Page: 15
SAFETY DATA SHEET	Revision Date: 02/05/2019
	Print Date: 2/4/2020
	SDS Number: R0412087
Valvoline™ Full Synthetic DEXRON VI and MERCON LV Automatic Transmission Fluid ™ Trademark, Valvoline or its subsidiaries, registered in various countries 822405	Version: 1.7

HMIRC : Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health OSHA: Occupational Safety and Health Administration

PMRA: Health Canada Pest Management Regulatory Agency

RTK: Right to Know

WHMIS: Workplace Hazardous Materials Information System