

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date November 5, 2015

Revision: November 5, 2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: Rubber Ball Blast Grenade - OC**
- **Article number:** 1095 (1012943)
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Crowd Control Device
- **Uses advised against** Contact manufacturer.
- **1.3 Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
Safariland, LLC
13386 International Parkway
Jacksonville, FL 32218
Customer Care (800) 347-1200
- **Further information obtainable from:** Customer Care Department
- **1.4 Emergency telephone number:**
ChemTel Inc.
+1 (800)255-3924, +1 (813)248-0585



SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



exploding bomb

Expl. 1.4 H204 Fire or projection hazard.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

- **Additional information:** 0 % of the mixture consists of component(s) of unknown toxicity.

- **2.2 Label elements**

- **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

- **Hazard pictograms**



GHS01 GHS07

(Cont'd. on page 2)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date November 5, 2015

Revision: November 5, 2015

Trade name: Rubber Ball Blast Grenade - OC

(Cont'd. from page 1)

- **Signal word** Warning

- **Hazard-determining components of labelling:**

tetra[carbonato(2-)]dihydroxypentamagnesium

- **Hazard statements**

H204 Fire or projection hazard.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

- **Precautionary statements**

The following Precautionary Statements are applicable only to the general GHS regulations and not the specific CLP regulation: P374.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P250 Do not subject to grinding/shock/friction.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P373 DO NOT fight fire when fire reaches explosives.

P374 Fight fire with normal precautions from a reasonable distance.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P372 Explosion risk in case of fire.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Additional information:**

Can become highly flammable in use.

- **NFPA ratings (scale 0 - 4)**



Health = 1

Fire = 0

Reactivity = 3

- **HMIS-ratings (scale 0 - 4)**



HEALTH 1 Health = 1

FIRE 0 Fire = 0

REACTIVITY 3 Reactivity = 3

Warning: Contains lead salt(s). Long-term health hazard.

- **2.3 Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Explosive Product Notice**

PREVENTION OF ACCIDENTS IN THE USE OF EXPLOSIVES - The prevention of accidents in the use of explosives is a result of careful planning and observance of the best known practices. The explosives user must remember that he is dealing with a powerful force and that various devices and methods have been developed to assist him in directing this force. He should realize that this force, if misdirected, may either kill or injure both him and his fellow workers.

WARNING - All explosives are dangerous and must be carefully handled and used following approved safety procedures either by or under the direction of competent, experienced persons in accordance with

(Cont'd. on page 3)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date November 5, 2015

Revision: November 5, 2015

Trade name: Rubber Ball Blast Grenade - OC

(Cont'd. from page 2)

all applicable federal, state, and local laws, regulations, or ordinances. If you have any questions or doubts as to how to use any explosive product, DO NOT USE IT before consulting with your supervisor, or the manufacturer, if you do not have a supervisor. If your supervisor has any questions or doubts, he should consult the manufacturer before use.

SECTION 3: Composition/information on ingredients

• 3.2 Mixtures

• **Description:** Mixture of substances listed below with nonhazardous additions.

• **Dangerous components:**

CAS: 1309-48-4 EINECS: 215-171-9 Index number: 025-199-09-0	magnesium oxide substance with a Community workplace exposure limit	40-60%
CAS: 7778-74-7 EINECS: 231-912-9 Index number: 017-008-00-5	potassium perchlorate ☠ Ox. Sol. 1, H271 ☠ Acute Tox. 4, H302	10-20%
CAS: 7429-90-5 EINECS: 231-072-3 Index number: 013-001-00-6	aluminium powder (pyrophoric) ☠ Pyr. Sol. 1, H250; Water-react. 2, H261	10-20%
CAS: 7439-95-4 EINECS: 231-104-6 Index number: 012-001-00-3	magnesium powder (pyrophoric) ☠ Pyr. Sol. 1, H250; Water-react. 1, H260	5-10%
CAS: 112945-52-5	Silicon Dioxide (Amorphous)	5-10%
CAS: 7757-79-1 EINECS: 231-818-8	potassium nitrate ☠ Ox. Sol. 2, H272	1-5%
CAS: 7440-50-8 EINECS: 231-159-6	copper substance with a Community workplace exposure limit	0,5-2%
CAS: 7440-66-6	zinc metal ☠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	0,5-2%
CAS: 9004-34-6 EINECS: 232-674-9	Cellulose substance with a Community workplace exposure limit	0,5-2%
CAS: 8023-77-6 EINECS: 288-920-0	Oleoresin Capsicum ☠ Eye Dam. 1, H318 ☠ Acute Tox. 4, H302; Skin Irrit. 2, H315	< 1,0%
CAS: 3811-04-9 EINECS: 223-289-7 Index number: 017-004-00-3	potassium chlorate ☠ Ox. Sol. 1, H271 ☠ Aquatic Chronic 2, H411 ☠ Acute Tox. 4, H302; Acute Tox. 4, H332	< 1,0%
CAS: 7704-34-9 EINECS: 231-722-6 Index number: 016-094-00-1	sulfur ☠ Skin Irrit. 2, H315	< 1,0%

(Cont'd. on page 4)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date November 5, 2015

Revision: November 5, 2015

Trade name: Rubber Ball Blast Grenade - OC

(Cont'd. from page 3)

CAS: 592-87-0 EINECS: 209-774-6 Index number: 082-001-00-6	lead dithiocyanate ----- ☠ Repr. 1A, H360Df; STOT RE 2, H373 ☠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410 ☠ Acute Tox. 4, H302; Acute Tox. 4, H332	< 1,0%
--	--	--------

- **Additional information:**

For the listed ingredient(s), the identity and exact percentages are being withheld as a trade secret.
For the wording of the listed Hazard Statements refer to section 16.

- **Notable Trace Components (≤ 0,1% w/w)**

CAS: 7758-97-6 EINECS: 231-846-0 Index number: 082-004-00-2	lead chromate ----- ☠ Carc. 1B, H350; Repr. 1A, H360Df; STOT RE 2, H373 ☠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410
CAS: 10294-40-3 EINECS: 233-660-5 Index number: 056-002-00-7	barium chromate ----- ☠ Acute Tox. 4, H302; Acute Tox. 4, H332

SECTION 4: First aid measures

- **4.1 Description of first aid measures**

- **General information:**

Immediately remove any clothing soiled by the product.
Take affected persons out into the fresh air.

- **After inhalation:**

Remove victim to fresh air.
Seek medical help for symptoms or if unconscious.

- **After skin contact:**

Brush off loose particles from skin.
If skin irritation continues, consult a doctor.

- **After eye contact:**

Remove contact lenses if worn.
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- **After swallowing:**

Rinse out mouth and then drink plenty of water.
Do not induce vomiting; call for medical help immediately.

- **4.2 Most important symptoms and effects, both acute and delayed**

Blast injury if mishandled.
Irritating to eyes, respiratory system and skin.
Breathing difficulty
Coughing
Irritant to eyes.

- **Hazards**

Danger of blast or crush-type injuries.
Danger of impaired breathing.

- **4.3 Indication of any immediate medical attention and special treatment needed**

Product may produce physical injury if mishandled. Treatment of these injuries should be based on the blast and compression effects.

(Cont'd. on page 5)

Safety Data Sheet
 according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
 OSHA GHS

Printing date November 5, 2015

Revision: November 5, 2015

Trade name: Rubber Ball Blast Grenade - OC

If necessary oxygen respiration treatment.

(Cont'd. from page 4)

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents:**

Flood area with water. If no water is available, carbon dioxide, dry chemical or earth may be used. If the fire reaches the cargo, withdraw and let fire burn.

· **For safety reasons unsuitable extinguishing agents:** None.

· **5.2 Special hazards arising from the substance or mixture**

During heating or in case of fire poisonous gases are produced.

Product may explode if burned in confined space. Individual cartridges may explode. Mass explosion of many cartridges at once is unlikely.

· **5.3 Advice for firefighters**

· **Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

· **Additional information**

Eliminate all ignition sources if safe to do so.

Cool endangered receptacles with water spray.

Evacuate area and fight fire from from the upwind side.

In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Flammability Classification: (defined by 29 CFR 1910.1200) Explosive. Can explode under fire conditions.

Individual devices will randomly explode. Will not mass explode if multiple devices are involved. Burning material may produce toxic and irritating vapors. In unusual cases, shrapnel may be thrown from exploding devices under containment. See 2008 Emergency response Guidebook for further information.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

FOR ALL TRANSPORTATION ACCIDENTS, CALL CHEMTEL AT 1-800-255-3924. Spills of this material should be handled carefully. Do not subject materials to mechanical shock or extreme heat. A spill of this material will normally not require emergency response team capabilities.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

Remove persons from danger area.

Ensure adequate ventilation

Protect from heat.

Isolate area and prevent access.

· **6.2 Environmental precautions:** No special measures required.

· **6.3 Methods and material for containment and cleaning up:**

Pick up mechanically.

Dispose contaminated material as waste according to section 13.

Send for recovery or disposal in suitable receptacles.

Clean the affected area carefully; suitable cleaners are:

Warm water and cleansing agent

(Cont'd. on page 6)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date November 5, 2015

Revision: November 5, 2015

Trade name: Rubber Ball Blast Grenade - OC

(Cont'd. from page 5)

- **6.4 Reference to other sections**

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**

Handle with care. Avoid jolting, friction and impact.
Use only in well ventilated areas.

- **Information about fire - and explosion protection:**

Protect from heat.
Keep respiratory protective device available.
Emergency cooling must be available in case of nearby fire.

- **7.2 Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:**

Avoid storage near extreme heat, ignition sources or open flame.

- **Information about storage in one common storage facility:**

Store away from foodstuffs.
Store away from flammable substances.

- **Further information about storage conditions:** Store in cool, dry conditions in well sealed receptacles.

- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see section 7.

- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

1309-48-4 magnesium oxide

PEL (USA)	Long-term value: 15* mg/m ³ fume; *total particulate
TLV (USA)	Long-term value: 10* mg/m ³ *as inhalable fraction
EL (Canada)	Short-term value: 10** mg/m ³ Long-term value: 10* 3** mg/m ³ *inhalable fume; **respirable dust and fume
EV (Canada)	Long-term value: 10 mg/m ³ inhalable

7429-90-5 aluminium powder (pyrophoric)

PEL (USA)	Long-term value: 15*; 15** mg/m ³ *Total dust; ** Respirable fraction
-----------	---

(Cont'd. on page 7)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date November 5, 2015

Revision: November 5, 2015

Trade name: Rubber Ball Blast Grenade - OC

(Cont'd. from page 6)

REL (USA)	Long-term value: 10* 5** mg/m ³ as Al*Total dust**Respirable/pyro powd./welding f.
TLV (USA)	Long-term value: 1* mg/m ³ as Al; *as respirable fraction
EL (Canada)	Long-term value: 1,0 mg/m ³ respirable, as Al
EV (Canada)	Long-term value: 5 mg/m ³ aluminium-containing (as aluminium)

7440-50-8 copper

PEL (USA)	Long-term value: 1* 0,1** mg/m ³ as Cu *dusts and mists **fume
REL (USA)	Long-term value: 1* 0,1** mg/m ³ as Cu *dusts and mists **fume
TLV (USA)	Long-term value: 1* 0,2** mg/m ³ *dusts and mists; **fume; as Cu
EL (Canada)	Long-term value: 1* 0,2** mg/m ³ *dusts and mists; **fume, as Cu
EV (Canada)	Long-term value: 0,2* 1** mg/m ³ as copper, *fume; **dust and mists

9004-34-6 Cellulose

PEL (USA)	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV (USA)	Long-term value: 10 mg/m ³
EL (Canada)	Long-term value: 10* 3** mg/m ³ *total dust, **respirable fraction
EV (Canada)	Long-term value: 10 mg/m ³ paper fibre, total dust

592-87-0 lead dithiocyanate

PEL (USA)	Long-term value: 5 mg/m ³ as CN; Skin
EV (Canada)	Long-term value: 0,05 mg/m ³ as Pb, Skin (organic compounds)

- **DNELs** No further relevant information available.
- **PNECs** No further relevant information available.

- **8.2 Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Do not inhale dust / smoke / mist.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

(Cont'd. on page 8)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date November 5, 2015

Revision: November 5, 2015

Trade name: Rubber Ball Blast Grenade - OC

(Cont'd. from page 7)

- **Respiratory protection:**

Wear positive pressure NIOSH or European EN149 vapor respirators when deploying product in large quantities.

Use suitable respiratory protective device when high concentrations are present.

- **Protection of hands:**



Protective gloves

Wear gloves when handling deployed rounds.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Safety glasses

- **Body protection:** Protective work clothing

- **Limitation and supervision of exposure into the environment**

No further relevant information available.

- **Risk management measures**

See Section 7 for additional information.

Organizational measures should be in place for all activities involving this product.

No further relevant information available.

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form: Solid metal container containing liquid and solid contents.

Colour: According to product specification

- **Odour:** Odourless

- **Odour threshold:** Not determined.

- **pH-value:** Not applicable.

- **Change in condition**

Melting point/Melting range: Not determined.

(Cont'd. on page 9)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date November 5, 2015

Revision: November 5, 2015

Trade name: Rubber Ball Blast Grenade - OC

(Cont'd. from page 8)

Boiling point/Boiling range:	Not determined.
· Flash point:	Not applicable.
· Flammability (solid, gaseous):	Not determined.
· Auto/Self-ignition temperature:	Not determined.
· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not self-igniting.
· Danger of explosion:	Heating may cause an explosion.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapour pressure:	Not applicable.
· Density:	Not determined.
· Relative density	Not determined.
· Vapour density	Not applicable.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with water:	Insoluble.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not applicable.
Kinematic:	Not applicable.
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions**
Danger of explosion.
Toxic fumes may be released if heated above the decomposition point.
Contact with acids releases toxic gases.
Acts as an oxidising agent on organic materials such as wood, paper and fats.
Reacts with strong alkali.
- **10.4 Conditions to avoid** Sources of ignition, open flame, incompatible materials.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
Carbon monoxide and carbon dioxide
Nitrogen oxides

(Cont'd. on page 10)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date November 5, 2015

Revision: November 5, 2015

Trade name: Rubber Ball Blast Grenade - OC

Sulphur oxides (SOx)

(Cont'd. from page 9)

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **LD/LC50 values relevant for classification:** None.
- **Primary irritant effect:**
- **Skin corrosion/irritation**
Not a skin irritant in unused form. Vapors/particles from used product are possibly irritating to skin.
Causes skin irritation.
- **Serious eye damage/irritation**
Not an eye irritant in unused form. Vapors/particles from delployed product are a serious eye irritant.
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
Normal handling of the undeployed product poses little or no health hazards, One should avoid inhalation by wearing appropriate respiratory protection when exposed to the chemical ingredients of the product above listed TLV's or when exposed to the post ignition by-products. This product is a cansister which contains the various components completely sealed within. Therefore, under normal handling of this product, no exposure to any harmful materials will occur. When the product is used, particles may be generated which may be irritating to the eyes and the respiratory tract.
- **Acute effects (acute toxicity, irritation and corrosivity):**
Inhalation may cause irritation to the respiratory system.
- **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction):**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause respiratory irritation.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** The product contains materials that are harmful to the environment.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** May be accumulated in organism
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

(Cont'd. on page 11)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date November 5, 2015

Revision: November 5, 2015

Trade name: Rubber Ball Blast Grenade - OC

(Cont'd. from page 10)

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

The product contains heavy metals. Avoid transfer into the environment. Specific preliminary treatments are necessary

Harmful to aquatic organisms

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

After prior treatment product has to be disposed of in an incinerator for hazardous waste adhering to the regulations pertaining to the disposal of particularly hazardous waste.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· **14.1 UN-Number**

· **DOT, ADR, IMDG, IATA** UN0452

· **14.2 UN proper shipping name**

· **DOT, IMDG, IATA** GRENADES, PRACTICE
· **ADR** 0452 GRENADES, PRACTICE

· **14.3 Transport hazard class(es)**

· **DOT, ADR, IMDG, IATA**



· **Class** 1.4

· **Label** 1.4G

(Cont'd. on page 12)

Safety Data Sheet


according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date November 5, 2015

Revision: November 5, 2015

Trade name: Rubber Ball Blast Grenade - OC

(Cont'd. from page 11)

- | | |
|---|---|
| <ul style="list-style-type: none"> · 14.4 Packing group · DOT, ADR, IMDG, IATA | II |
| <ul style="list-style-type: none"> · 14.5 Environmental hazards: · Marine pollutant: · Special marking (IATA): | <p>No</p> <p>Prohibited from Transport in Passenger Aircraft.</p> |
| <div style="display: flex; align-items: center;">  <p>Cargo Aircraft Only.</p> </div> | |
| <ul style="list-style-type: none"> · 14.6 Special precautions for user · EMS Number: | <p>Not applicable.</p> <p>F-B,S-X</p> |
| <ul style="list-style-type: none"> · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code | Not applicable. |
| <ul style="list-style-type: none"> · Transport/Additional information: | |
| <ul style="list-style-type: none"> · ADR · Limited quantities (LQ) · Excepted quantities (EQ) | |
| <p style="text-align: center;">0</p> <p style="text-align: center;">Code: E0</p> <p style="text-align: center;">Not permitted as Excepted Quantity</p> | |
| <ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) | |
| <p style="text-align: center;">0</p> <p style="text-align: center;">Code: E0</p> <p style="text-align: center;">Not permitted as Excepted Quantity</p> | |
| <ul style="list-style-type: none"> · UN "Model Regulation": | UN 0452 GRENADES, PRACTICE, 1.4G, II |

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**

- **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

- **Section 313 (Specific toxic chemical listings):**

7429-90-5	aluminium powder (pyrophoric)
7757-79-1	potassium nitrate
7440-50-8	copper
7440-66-6	zinc metal

- **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

(Cont'd. on page 13)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date November 5, 2015

Revision: November 5, 2015

Trade name: Rubber Ball Blast Grenade - OC

(Cont'd. from page 12)

· **Proposition 65 (California):**

· **Chemicals known to cause cancer:**

592-87-0	lead dithiocyanate
10294-40-3	barium chromate
7758-97-6	lead chromate

· **Chemicals known to cause reproductive toxicity for females:**

Present in trace quantities.

10294-40-3	barium chromate
7758-97-6	lead chromate

· **Chemicals known to cause reproductive toxicity for males:**

Present in trace quantities.

10294-40-3	barium chromate
7758-97-6	lead chromate

· **Chemicals known to cause developmental toxicity:**

Present in trace quantities.

10294-40-3	barium chromate
7758-97-6	lead chromate

· **Carcinogenic Categories**

· **EPA (Environmental Protection Agency)**

7778-74-7	potassium perchlorate	NL
7440-50-8	copper	D
7440-66-6	zinc metal	D, I, II

· **IARC (International Agency for Research on Cancer)**

None of the ingredients are listed.

· **TLV (Threshold Limit Value established by ACGIH)**

1309-48-4	magnesium oxide	A4
7429-90-5	aluminium powder (pyrophoric)	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients are listed.

· **Canada**

· **Canadian Domestic Substances List (DSL)**

All ingredients are listed.

· **Canadian Ingredient Disclosure list (limit 0.1%)**

None of the ingredients are listed.

· **Canadian Ingredient Disclosure list (limit 1%)**

1309-48-4	magnesium oxide
7429-90-5	aluminium powder (pyrophoric)
7440-50-8	copper

(Cont'd. on page 14)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date November 5, 2015

Revision: November 5, 2015

Trade name: Rubber Ball Blast Grenade - OC

(Cont'd. from page 13)

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I**

None of the ingredients are listed.

· **Other regulations, limitations and prohibitive regulations**

· **Substances of very high concern (SVHC) according to REACH, Article 57**

None of the ingredients are listed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H250 Catches fire spontaneously if exposed to air.
- H260 In contact with water releases flammable gases which may ignite spontaneously.
- H261 In contact with water releases flammable gases.
- H271 May cause fire or explosion; strong oxidiser.
- H272 May intensify fire; oxidiser.
- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H332 Harmful if inhaled.
- H360Df May damage the unborn child. Suspected of damaging fertility.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 ACGIH: American Conference of Governmental Industrial Hygienists
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 DNEL: Derived No-Effect Level (REACH)
 PNEC: Predicted No-Effect Concentration (REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 SVHC: Substances of Very High Concern
 vPvB: very Persistent and very Bioaccumulative
 Expl. 1.4: Explosives, Division 1.4

(Cont'd. on page 15)

Safety Data Sheet
according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date November 5, 2015

Revision: November 5, 2015

Trade name: Rubber Ball Blast Grenade - OC

(Cont'd. from page 14)

Pyr. Sol. 1: Pyrophoric Solids, Hazard Category 1

Water-react. 1: Substances and Mixtures which, in contact with water, emit flammable gases, Hazard Category 1

Water-react. 2: Substances and Mixtures which, in contact with water, emit flammable gases, Hazard Category 2

Ox. Sol. 1: Oxidising Solids, Hazard Category 1

Ox. Sol. 2: Oxidising Solids, Hazard Category 2

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Repr. 1A: Reproductive toxicity, Hazard Category 1A

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - Acute Hazard, Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

Sources

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com