



# Safety Data Sheet

Issue Date: 06-May-2013

Revision Date: 21-Mar-2016

Version 1

## SECTION 1. IDENTIFICATION

### Product Identifier

**Product Names** 1ST PRIORITY Passenger Car Motor Oil – All Grades

### Other means of identification

**SDS #** 7777-001

**Product Grades** 5W20 SN/GF-5, 5W30 SN/GF-5, 10W30 SN/GF-5, 10W40 SN, 20W50 SN

### Recommended use of the chemical and restrictions on use

**Recommended Use** Engine oils

### Details of the supplier of the safety data sheet

#### **Supplier Address**

LubeMark  
PO Box 5360  
Houston, TX 77325-5360

### Emergency Telephone Number

**Company Phone Number** 1-281-426-8800  
**Emergency Telephone (24 hr)** INFOTRAC 1-352-323-3500 (International)  
**1-800-535-5053 (North America)**

## SECTION 2. HAZARDS IDENTIFICATION

### Classification

Not Classified.

This chemical does not meet the hazardous criteria set forth by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). However, this Safety Data Sheet (SDS) contains valuable information critical to the safe handling and proper use of this product. This SDS should be retained and available for employees and other users of this product.

### GHS Label Elements

<b>Hazard pictograms</b>	None	<b>Physical State</b>	Liquid	<b>Odor</b>	Petroleum
<b>Signal Word</b>	None				
<b>Appearance</b>	Clear amber				
<b>Hazard statement</b>	None				

### Precautionary statements

**General** Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

### Potential Health Effects

**Principal Routes of Exposure** Eye contact, Skin contact, Inhalation, Ingestion

### **Acute Toxicity**

<b>Eyes</b>	Eye contact may result in slight irritation and redness.
<b>Skin</b>	Substance minimally irritating upon direct contact.
<b>Inhalation</b>	Low hazard at standard temperatures and pressures. Inhalation of oil mist or fumes can cause irritation of the nose, throat and upper respiratory tract.

<b>Ingestion</b>	Do not ingest. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
<b>Other</b>	On rare occasions, prolonged and repeated exposure to oil mist poses a risk of pulmonary disease such as chronic lung inflammation. This condition is usually asymptomatic as a result of repeated small aspirations.
<b>Chronic Effects</b>	Prolonged exposure may cause chronic effects.
<b>Aggravated Medical Conditions</b>	Personnel with pre-existing skin disorders should avoid contact with this product.
<b>Environmental Hazard</b>	See Section 12 for additional Ecological Information.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Mixture

Petroleum oil lubricant base stock with proprietary performance additives mixture.

Chemical Name	CAS No	Weight-%*
Base Oil – Highly Refined Hydrotreated Heavy Paraffinic Distillate	64742-54-7	95 – 99
Additive Mixture	Proprietary	0.40 – .15

This product does not contain known hazardous materials at the  $\geq 1\%$  level or known carcinogens at the  $\geq 0.1\%$  level as defined by 29 CFR 1910.1200.

\* If Chemical Name/CAS No is "Proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

### SECTION 4. FIRST-AID MEASURES

#### First Aid Measures

<b>General Advice</b>	No specific first aid measures are required. Get medical attention if irritation develops and persists.
<b>Eye Contact</b>	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention if irritation develops and persists. If material is hot, treat for thermal burns and take victim to the hospital immediately.
<b>Skin Contact</b>	Wash off immediately with soap and plenty of water for at least 15 minutes while removing all contaminated clothing and shoes. Get medical attention immediately if skin discoloration occurs.
<b>Inhalation</b>	This material is not expected to present an inhalation exposure at ambient conditions.
<b>Ingestion</b>	Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Get immediate medical attention or advice.
<b>Protection of first-aiders</b>	No action shall be taken involving any personal risk or without suitable training. Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Wear personal protective clothing.

#### Indication of any immediate medical attention and special treatment needed

<b>Notes to Physician</b>	Treat symptomatically.
---------------------------	------------------------

### SECTION 5. FIRE-FIGHTING MEASURES

#### Suitable Extinguishing Media

Use extinguishing media appropriate for surrounding fire.

**Unsuitable Extinguishing Media**

Do not use a heavy water stream. Use of heavy stream of water may spread fire.

**Special hazards arising from the chemical**

**Fire Hazard** Not flammable but will support combustion.  
**Explosion Hazard** Product is not explosive  
**Reactivity** Hazardous reactions will not occur under normal conditions.

**Protective equipment and precautions for firefighters**

**Precautionary Measures Fire** Exercise caution when fighting any chemical fire. Under fire conditions, hazardous fumes will be present.  
**Firefighting Instructions** Use water spray or fog for cooling exposed containers.  
**Protection During Firefighting** Do not enter fire area without proper protective equipment, including respiratory protection.  
**Hazardous Combustion Products** Under fire conditions, may produce fumes, smoke, oxides of carbon and hydrocarbons.  
**Other Information** Refer to Section 9 for flammability properties.

**Reference to Other Sections**

Refer to Section 9 for flammability properties.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions, protective equipment and emergency procedures**

**For Non-Emergency Personnel** Use personal protective equipment. Avoid contact with skin, eyes, and clothing. Ensure adequate ventilation. If spilled, take caution, as material can cause surfaces to become very slippery.

**For Emergency Responders** If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

**Methods and material for containment and cleaning up**

Dike far ahead of liquid spill for later disposal. Pick up free liquid for recycle and/or disposal. Residual liquid and/or solid can be absorbed on inert material.

**Large Spills** Consider initial downwind evacuate for at least 300 meters (1000 feet).

**Fire** If tank, rail car or tank car is involved in a fire, isolate for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions.

NOTE: If RQ (Reportable Quantity) is exceeded or if spills enter a body of water, report immediately to the USEPA's National Response Center at (800) 424-8802. Check with your local and state regulators regarding their reporting requirements.

**SECTION 7. HANDLING AND STORAGE**

**Precautions for safe handling**

**Protective Measures** Do not pressure, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode. See NFPA 30 and OSHA 1910.106 – flammable and combustible liquids.

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions** Store away from heat, sparks, open flame, or strong oxidizing agents in closed and properly labeled containers. Empty containers retain product residue (liquid, and/or vapor) and can be dangerous.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Control Parameters**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Base Oil – Highly Refined Hydrotreated Heavy Paraffinic Distillate 64742-54-7	TWA: 5 mg/m <sup>3</sup> (mist) STEL: 10 mg/m <sup>3</sup> (mist)	TWA: 5 mg/m <sup>3</sup> (mist) STEL: none estab	TWA: 5 mg/m <sup>3</sup> (mist) STEL: 10 mg/m <sup>3</sup> (mist)

**Exposure Controls**

**Appropriate Engineering Controls**

Ensure adequate ventilation, especially in confined areas. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed.

**Personal Protective Equipment**

Protective goggles. Gloves. Wear respiratory protection for insufficient ventilation



**Materials for Protective Clothing**

Chemically resistant materials and fabrics.

**Hand Protection**

Wear chemically resistant protective gloves.

**Eye Protection**

Chemical goggles or safety glasses.

**Skin and Body Protection**

Wear suitable protective clothing.

**Respiratory Protection**

Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.

**Environmental Exposure Controls**

Do not allow the product to be released into the environment.

**Consumer Exposure Controls**

Do not eat, drink or smoke during use.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

**Information on Basic Physical and Chemical Properties**

Physical State	Liquid
Appearance	Amber
Odor	Petroleum
Odor Threshold	Not determined

<u>Property</u>	<u>Values</u>
pH	Not determined
Evaporation Rate	Not determined
Melting Point	Not determined
Boiling Point	280C / 392F
Flash Point	226C (COC) / 438F
Auto-ignition Temperature	Not determined
Decomposition Temperature	Not determined
Flammability (solid, gas)	Not determined
Lower Flammable Limit	Not determined
Upper Flammable Limit	Not determined
Vapor Pressure	Not determined

Relative Vapor Density at 20 °C	Not determined
Relative Density	Not determined
Specific Gravity	0.87
Solubility	Negligible
Partition Coefficient: N-Octanol/Water	Not determined
Viscosity	Not determined
Viscosity, Kinematic	50 mm <sup>2</sup> /s @ 40C
Explosive Properties	Product is not explosive
Explosion Data – Sensitivity to Mechanical Impact	Not expected to present an explosion hazard due to mechanical impact
Explosion Data – Sensitivity to Static Discharge	Not expected to present an explosion hazard due to static discharge

## SECTION 10. STABILITY AND REACTIVITY

### Reactivity

Not reactive under normal conditions.

### Chemical Stability

Stable under recommended storage conditions.

### Possibility of Hazardous Reactions

None under normal processing.

#### **Hazardous Polymerization**

Hazardous polymerization does not occur.

### Conditions to Avoid

Heat, flames and sparks.

### Incompatible Materials

Oxidizing agents and open flames.

### Hazardous Decomposition Products

Decomposition and combustion products may include: smoke, fumes, oxides of phosphorus, boron, sulfur, nitrogen, carbon dioxide, carbon monoxide, and other low molecular weight hydrocarbons.

## SECTION 11. TOXICOLOGICAL INFORMATION

### Information on Toxicological Effects

#### **Substance Mixture**

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Base Oil – Highly Refined Hydrotreated Heavy Paraffinic Distillate 64742-54-7	>15000 mg/Kg (rat)	>5000 mg/Kg (rabbit)	2.18 mg/l (rat) 4h

### Acute Toxicity

Test on similar materials show a low order of acute oral and dermal toxicity.

#### **Acute Oral Effects**

Test on similar materials indicates low order of acute toxicity.

#### **Acute Inhalation Effects**

Low acute toxicity expected on inhalation.

#### **Skin Effects**

Practically non-toxic if absorbed. Other similar highly refined products have not shown skin tumors in mouse skin painting studies.

#### **Eye Irritation**

Minimal irritation on contact. Eye irritation slightly or practically non-irritating based on similar products.

### Chronic Toxicity

Prolonged exposure may cause chronic effects. On rare occasions, prolonged and repeated exposure to oil mist poses a risk of pulmonary disease such as chronic lung inflammation. This condition is usually asymptomatic as a result of repeated small aspirations.

#### **Carcinogenicity**

Not considered a potential carcinogen base on IP346 DMSO of less than 3.0 wt%

#### **Target Organ Effects**

Respiratory system, Eyes, Skin

**Genotoxicity**

This product is considered non-mutagenic and has negative potential for tumor development based from Modified Ames Assay, with Mutagenic Index of less than 1.0.

**SECTION 12. ECOLOGICAL INFORMATION**

The information is based on data available for the material, the components of the material, and similar materials.

**Ecotoxicity**

If applied to leaves, this product may kill grasses and small plants by interfering with transpiration and respiration. This product is not toxic to fish but may coat gill structures resulting in suffocation if spilled in shallow, running water. Product may be moderately toxic to amphibians by preventing dermal respiration. This product may cause gastrointestinal distress to birds and mammals through ingestion during pelage grooming.

**SECTION 13. DISPOSAL CONSIDERATIONS**

Disposal recommendations based on material supplied.

**Waste Treatment Methods**

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). Keep this product out of sewers and waterways. Consult the appropriate state, regional, or local regulations for additional requirements. The generation of waste should be avoided or minimized wherever possible.

**Contaminated Packaging**

Dispose of in accordance with local regulations.

**SECTION 14. TRANSPORT INFORMATION**

**General Information**

Petroleum Lubricating oil - Not regulated.

**DOT** Not regulated

**IATA** Not regulated

**IMDG/IMO** Not regulated

**Special Precautions for User**

Transport within user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**SECTION 15. REGULATORY INFORMATION**

**US Federal Regulations**

<b>SARA Section 311/312 Hazard Classes</b>	Not Classified
--	----------------

**US State Regulations**

None noted

**Canadian Regulations**

WHMIS Classification	Not Classified
<b>Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

**SECTION 16. OTHER INFORMATION**

<b>NFPA</b>	<b>Health Hazards</b>	<b>Flammability</b>	<b>Instability/Reactivity</b>
	1	1	0
<b>HMIS</b>	<b>Health Hazards</b>	<b>Flammability</b>	<b>Physical Hazards</b>
	1	1	0

(NFPA & HMIS Hazard Rating Key: 0 - Minimum Hazard; 1 - Slight Hazard; 2 - Moderate Hazard; 3 - High Hazard; 4 - Extreme Hazard; \* - Chronic Hazard Indicator, & PPE - Personal Protective Equipment Index A to L. These values are obtained using the guidelines or published evaluations prepared by the National Fire Protection Association (NFPA) or the National Paint and Coating Association (for HMIS or Hazardous Material Identification System).

**Key to abbreviations:**

- |  |   |
|--|---|
| OSHA = Occupational Safety and Health Administration                       | LogPow = logarithm of the octanol/water partition coefficient   |
| ACGIH= American Conference of Industrial Hygienists                        | OEL = Occupational Exposure Limit   |
| ATE = Acute Toxicity Estimate  | SDS = Safety Data Sheet   |
| BCF = Bioconcentration Factor  | STEL = Short term exposure Limit  |
| CAS = Chemical Abstracts Service Registry Number                           | UN = United Nations   |
| cSt = Centistroke (mm <sup>2</sup> /s)                                     | UN Number = United Nations Number, a four-digit number assigned by the United Nations Committee of Experts on the Transportation of Dangerous Goods |
| GHS = Global Harmonized System of Classification and Labeling of Chemicals |   |
| IATA = International Air Transport Association                             |   |
| IBC = Intermediate Bulk Container  |   |
| IMDG = International Maritime Dangerous Goods                              |   |

**Issue Date** May 6, 2013  
**Revision Date** March 21, 2016  
**Revision Note** New format. All Sections. First version in OSHA SDS format  
**Product Numbers**

UOM	1 <sup>st</sup> PRIORITY® Motor Oils				
	5W20	5W30	10W30	10W40	20W50
12/1 Qt	7777-02-10104	7777-02-10114	7777-02-10124	7777-02-10134	7777-02-10144
3/1 Gal					7777-02-10143
5 Gal Pail	7777-04-10002	7777-04-10012	7777-04-10022	7777-04-10032	7777-04-10042
55 Gal Drum	7777-04-10001	7777-04-10011	7777-04-10021	7777-04-10031	7777-04-10041
<b>BOTTLE UPC</b>	8 98359 00274 1	8 98359 00205 5	8 98359 00204 8	8 98359 00211 6	8 98359 00212 3 (12/1 Q) 8 98359 00252 9 (3/1 G)

**Disclaimer**

All reasonably practicable steps have been taken to ensure the information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This information is furnished upon condition that the person receiving it shall make their own determination of the suitability of the material for their particular purpose.

**End of Safety Data Sheet**