

Revision Date 14-May-2020

SAFETY DATA SHEET

Version 11

1. IDENTIFICATION

Product identifierProduct Name81844Other means of identification

81844 REARVIEW MIRROR ADHESIVE KIT PART 2

Other means of identificationProduct CodePTX394319X

Recommended use of the chemical and restrictions on useRecommended UseActivatorUses advised againstNo information available

Details of the supplier of the safety data sheet Manufacturer Address ITW Permatex 6875 Parkland Blvd. Solon, Ohio 44139 USA Telephone: 1-87-Permatex (866) 732-9502 24-hour emergency phone number Chem-Tel: 800-255-3924 International Emergency: 00+1+ 813-248-0585 Contract Number: MIS0003453

E-mail address: mail@permatex.com

May Also Be Distributed by: ITW Permatex Canada 101-2360 Bristol Circle Oakville, ON Canada L6H 6M5 Telephone: (800) 924-6994

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status


This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2A
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Specific target organ toxicity (single exposure)	Category 3
Flammable liquids	Category 2

Label elements

Emergency Overview

Signal word		
Danger		
Causes serious eye irritation May cause genetic defects May cause cancer May cause respiratory irritation May cause drowsiness or dizziness		



Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Wash face, hands and any exposed skin thoroughly after handling Wear eye/face protection Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area Keep away from heat/sparks/open flames/hot surfaces. - No smoking Keep container tightly closed Ground/bond container and receiving equipment Use explosion-proof electrical/ ventilating/ lighting/ equipment Use non-sparking tools Take precautionary measures against static discharge Keep cool

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing In case of fire: Use CO2, dry chemical, or foam to extinguish.

Precautionary Statements - Storage

Store locked up Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC) Not applicable

Other Information

Not applicable.

Unknown acute toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
2-PROPANOL	67-63-0	60 - 100
MINERAL SPIRITS	8052-41-3	0.1 - 1

4. FIRST AID MEASURES

Description of first aid measures

General advice	Call 911 or emergency medical service. Remove and isolate contaminated clothing and shoes.		
Eye contact	In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.		
Skin contact	Wash skin with soap and water.		
Inhalation	Move victim to fresh air. If breathing is irregular or stopped, administer artificial respiration. Administer oxygen if breathing is difficult.		
Ingestion	IF SWALLOWED:. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician.		
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.		
Most important symptoms and effects, both acute and delayed			
Symptoms	See section 2 for more information.		
Indication of any immediate medical attention and special treatment needed			
Note to physicians	Keep victim warm and quiet. Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed.		
5. FIRE-FIGHTING MEASURES			

Suitable extinguishing media

Dry chemical, CO2, water spray or alcohol-resistant foam, Water spray, fog or alcohol-resistant foam

Unsuitable extinguishing media

Do not use straight streams CAUTION: All these products have a very low flash point. Use of water spray when fighting fire may be inefficient Do not use dry chemical extinguishers to control fires involving nitromethane or nitroethane

Specific hazards arising from the chemical

Vapors may travel to source of ignition and flash back. Vapors may form explosive mixtures with air. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Those substances designated with a "P" may polymerize explosively when heated or involved in a fire. Runoff to sewer may create fire or explosion hazard.

Explosion data	
Sensitivity to Mechanical Impact	None.
Sensitivity to Static Discharge	None.

Protective equipment and precautions for firefighters

Move containers from fire area if you can do it without risk.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Stop leak if you can do it without risk.

Other Information	Water spray may reduce vapor; but may not prevent ignition in closed spaces.		
Environmental precautions			
Environmental precautions	Prevent entry into waterways, sewers, basements or confined areas.		
Methods and material for containm	ent and cleaning up		
Methods for containment	A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.		
Methods for cleaning up	Use clean non-sparking tools to collect absorbed material.		
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.		
7. HANDLING AND STORAGE			
Precautions for safe handling			
Advice on safe handling			
Advice on sure nanoling	Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Keep away from heat/sparks/open flames/hot surfaces No smoking.		
Conditions for safe storage, includ	vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Keep away from heat/sparks/open flames/hot surfaces No smoking.		
	vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Keep away from heat/sparks/open flames/hot surfaces No smoking.		

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
2-PROPANOL	STEL: 400 ppm	TWA: 400 ppm	IDLH: 2000 ppm
67-63-0	TWA: 200 ppm	TWA: 980 mg/m ³	TWA: 400 ppm
		(vacated) TWA: 400 ppm	TWA: 980 mg/m ³
		(vacated) TWA: 980 mg/m ³	STEL: 500 ppm
		(vacated) STEL: 500 ppm	STEL: 1225 mg/m ³
		(vacated) STEL: 1225 mg/m ³	
MINERAL SPIRITS	TWA: 100 ppm	TWA: 500 ppm	IDLH: 20000 mg/m ³
8052-41-3		TWA: 2900 mg/m ³	Ceiling: 1800 mg/m ³ 15 min
		(vacated) TWA: 100 ppm	TWA: 350 mg/m ³
		(vacated) TWA: 525 mg/m ³	_

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls	Showers Eyewash stations
	Ventilation systems

Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles).

Skin and body protection	Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.
Respiratory protection	Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.
General Hygiene Considerations	Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties				
Physical state	Liquid			
Appearance	Apple			
Odor	Alcoholic			
Odor threshold	No information available			
Property_	Values	Remarks • Method		
pH	No information available			
Melting point / freezing point	No information available			
Boiling point / boiling range	82 °C / 180 °F			
Flash point	12 °C / 54 °F	Tag Closed Cup		
Evaporation rate	7.7	Butyl acetate = 1		
Flammability (solid, gas)	No information available	-		
Flammability Limit in Air				
Upper flammability limit:	12.0%			
Lower flammability limit:	2.0%			
Vapor pressure	32 mm Hg @ 68°F			
Vapor density	2.1	Air = 1		
Relative density	0.79 @ 77°F			
Water solubility	Soluble in water			
Solubility(ies)	No information available			
Partition coefficient	No information available			
Autoignition temperature	No information available			
Decomposition temperature	No information available			
Kinematic viscosity	No information available			
Dynamic viscosity	No information available			
Explosive properties	No information available			
Oxidizing properties	No information available			
Other Information				
Softening point	No information available			
Molecular weight	No information available			
VOC Content (%)	96.5			
Density	No information available			
Bulk density	No information available			
SADT (self-accelerating	No information available			
decomposition temperature)				

10. STABILITY AND REACTIVITY

Reactivity No information available

<u>Chemical stability</u> Stable under normal conditions

Possibility of Hazardous Reactions

None under normal processing.

= 72600 mg/m3 (Rat) 4 h

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents

Hazardous Decomposition Products

Carbon oxides

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Ingestion	Ingestion may cause irritation to mucous membranes.		
Skin contact	May cause skin irritation and/or dermatitis.		
Eye contact	Contact with eyes may cause irritation. May cause redness and tearing of the eyes.		
Inhalation	May cause irritation of respiratory tract.		

12800 mg/kg

Information on toxicological effects

Symptoms

2-PROPANOL

67-63-0

No information available.

5050 mg/kg

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization	No information available.
Germ cell mutagenicity	No information available.
Carcinogenicity	No information available.
Target Organ Effects	Central nervous system, Eyes, kidney, Respiratory system, Skin.

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	5233 mg/kg
ATEmix (dermal)	13264 mg/kg
ATEmix (inhalation-dust/mist)	75.2 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

2.2 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Chemical Name	Partition coefficient
2-PROPANOL	0.05
67-63-0	

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods	
Disposal of wastes	This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).
Contaminated packaging	Do not reuse container.
US EPA Waste Number	D001

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
2-PROPANOL	Toxic
67-63-0	Ignitable

14. TRANSPORT INFORMATION

UN/ID No Ethanol Hazard Class Packing Group Emergency Response Guide Number	1219 Isopropyl alcohol, Limited Quantity (LQ) 3 II 129
IATA UN/ID No Ethanol Hazard Class ERG Code	ID 8000 Consumer commodity 9 9L
IMDG UN/ID No Ethanol Hazard Class Packing Group EmS-No	1219 Isopropyl alcohol, Limited Quantity (LQ) 3 II F-E, S-D

15. REGULATORY INFORMATION

what and Inventories

International Inventories	
TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Not Listed

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory **DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %	
2-PROPANOL - 67-63-0	1.0	
SARA 311/312 Hazard Categories		
Acute health hazard	Yes	
Chronic Health Hazard	No	
Fire hazard	Yes	
Sudden release of pressure hazard	No	
Reactive Hazard	No	

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
2-PROPANOL	Х	Х	Х
67-63-0			
MINERAL SPIRITS	Х	Х	Х
8052-41-3			
ORGANO-COPPER COMPOUND	Х	-	Х
22221-10-9			

U.S. EPA Label Information_ EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

B2 - Flammable liquid, D2B - Toxic materials

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA
HMIS

Health hazards 2 Health hazards 2

- Flammability 3 Flammability 3
- Instability 0 Physical hazards 0
- Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date

14-May-2020

Disclaimer

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled. However, Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of the information. User is responsible for evaluating whether such information or this product is fit for a particular purpose and suitable for a particular use or application. The information in this data sheet may not be valid if this product is used in combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims any liability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of this product. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site.

End of Safety Data Sheet