Printing date 01/05/2021 Revised On 01/05/2021

1 Identification of the substance and manufacturer

Trade name: **HIGH VIS YELLOW** 0000160676 Product code:

Recommended use: Paint and coatings application.

Uses advised against: Any that differs from the recommended use.

Manufacturer/Supplier: Seymour of Sycamore

917 Crosby Avenue Sycamore, IL 60178 USA phone: 815-895-9101

www.seymourpaint.com

1-800-255-3924 **Emergency telephone number:**

Seymour of Sycamore 3041 Dougall Avenue, Suite 503 Windsor, ONT N9E 1S3 CANADA phone: 800-435-4482

www.seymourpaint.com

2 Hazard(s) identification

Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.

Press. Gas H280 Contains gas under pressure; may explode if heated.

STOT SE 3 H335 May cause respiratory irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information:


GHS Hazard pictograms

Precautionary statements









Signal word

Hazard statements Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area. IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a poison center/doctor if you feel unwell.

Store in a well-ventilated place.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

This product is a mixture of the substances listed below with nonhazardous additions. Chemical Description:

Dangerous components:		
64742-89-8	VM&P Naphtha	15-25%
1317-65-3	Calcium Carbonate	10-15%
74-98-6	propane	10-15%
	n-butane	5-10%
	Mineral Spirits	1-5%
13463-67-7	titanium dioxide	1-5%

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

Rinse out mouth and then drink plenty of water. After swallowing: Rinse mouth with water. Do not induce vomiting.

Most important symptoms and

effects:

Dizziness

Indication of any immediate medical

attention needed: No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray. Special hazards: Can form explosive gas-air mixtures.

Protective equipment for

firefighters: A respiratory protective device may be necessary. Printing date 01/05/2021 Revised On 01/05/2021

Trade name: HIGH VIS YELLOW

(Contd. of page 1)

6 Accidental release measures

Personal precautions, protective

equipment and emergency

procedures:

Wear protective equipment. Keep unprotected persons away.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Methods and material for

containment and cleaning up:

Ensure adequate ventilation.

7 Handling and storage

Precautions for safe handling

Use only in well ventilated areas.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Storage requirements:

Store locked up.

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

74-98-6 propane

PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm REL (USA) Long-term value: 1800 mg/m³, 1000 ppm TLV (USA) refer to Appendix F inTLVs&BEIs book; D, EX

106-97-8 n-butane

REL (USA) Long-term value: 1900 mg/m³, 800 ppm TLV (USA) Short-term value: 2370 mg/m³, 1000 ppm (EX)

Keep away from foodstuffs and animal feed. Wash hands after use. Hygienic protection:

Wash hands after use.

Do not eat or drink while working.

Breathing equipment: A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn.

If you suspect overexposure conditions exist, please consult an authority on chemical hygeine.

Hand protection: Nitrile gloves.

The glove material must be impermeable and resistant to the substance. Tightly sealed goggles

Eye protection:

9 Physical and chemical properties

Appearance: Aerosol. Odor: Aromatic Odor threshold: Not determined. Not determined. Melting point/Melting range Undetermined. **Boiling point:** -44 °C (-47.2 °F) -19 °C (-2.2 °F) Flash point: Flammability (solid, gas): Extremely flammable.

Decomposition temperature: Not determined.

Product is not self-igniting. Auto igniting:

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: 1.7 Vol % **Upper Explosion Limit:** 10.9 Vol % Not determined. Vapor pressure:

Between 0.77 and 0.85 (Water equals 1.00) Relative Density:

Vapor density Not determined. Evaporation rate Not applicable. Partition coefficient: n-octonal/water: Not determined. Not determined. Solubility: Viscosity: Not determined. 28.6 % Water:

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures.

Chemical stability: Not fully evaluated.

Possibility of hazardous reactions: No dangerous reactions known.

Incompatible materials: No further relevant information available.

(Contd. on page 3)

Printing date 01/05/2021 Revised On 01/05/2021

Trade name: HIGH VIS YELLOW

Hazardous decomposition: No dangerous decomposition products known.

(Contd. of page 2)

11 Toxicological information

LD/LC50 values that are relevant for classification:

13463-67-7 titanium dioxide

 Oral
 LD50
 >20,000 mg/kg (rat)

 Dermal
 LD50
 >10,000 mg/kg (rbt)

 Inhalative
 LC50/4 h
 >6.82 mg/l (rat)

Information on toxicological effects: No data available.
Skin effects: No irritant effect.
Eye effects: No irritating effect.

Sensitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

Other information:

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated

solvents.

Bioaccumulative potential:
Mobility in soil:
Other adverse effects:

No further relevant information available.
No further relevant information available.
No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled. Water, if necessary with cleansing agents.

14 Transport information

 UN-Number
 UN1950

 DOT
 UN1950

 UN1950
 UN1950

DOT Aerosols, flammable 1950 Aerosols

Transport hazard class(es):

Class 2.1
Marine pollutant: No

Special precautions for user: Warning: Gases

EMS Number: F-D,S-U

Packaging Group: --

UN "Model Regulation": UN1950, Aerosols, 2.1

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

Toxic Substances Control Act

(TSCA): All hazardous ingredients are found on the inventory list of substances.

Canadian Domestic Substances List

(DSL): All ingredients are listed or exempted.

Consumer Product Safety

Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

13463-67-7 titanium dioxide 100-41-4 ethyl benzene

Prop 65 chemicals known to cause birth defects or reproductive harm:

None of the ingredients is listed.

EPA:

None of the ingredients is listed.

16 Other information

Contact: Regulatory Affairs