

Safety Data Sheet

Section 1: Identification

Product identifier

Product Name

- **Ultra Low Sulfur Diesel (ULSD)**

Synonyms

- Clear ULSD, Dyed or Undyed ULSD with 0-20% Bio and/or 0-5% Renewable, Ultra Low Sulfur Heating Oil, See Section 16.

SDS Number/Grade

- D0102

Relevant identified uses of the substance or mixture and uses advised against

Recommended use

- Fuel for automotive diesel engines, Fuel for off-road diesel engines, Heating oil.

Restrictions on use

- This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the supplier

Details of the supplier of the safety data sheet

Manufacturer

- Motiva Enterprises LLC
PO BOX 4540 Houston,
TX 77210-4540
United States
www.Motiva.com
Email: SDS@motiva.com

Telephone (General) • 1-800-339-8714

Emergency telephone number

Manufacturer

- 1-800-424-9300 - CHEMTREC

Section 2: Hazard Identification

United States (US)

According to: OSHA 29 CFR 1910.1200 HCS

Classification of the substance or mixture

OSHA HCS 2012

- Flammable Liquids 3
Aspiration 1
Skin Irritation 2
Acute Toxicity Inhalation 4
Carcinogenicity 2
Specific Target Organ Toxicity Repeated Exposure 2
Hazardous to the aquatic environment Chronic 2

Label elements

OSHA HCS 2012

DANGER



- Hazard statements** • Flammable liquid and vapour
May be fatal if swallowed and enters airways
Causes skin irritation
Harmful if inhaled
Suspected of causing cancer.

May cause damage to organs - blood, thymus, liver through prolonged or repeated exposure
Toxic to aquatic life with long lasting effects

Precautionary statements

- Prevention** • Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking.
Keep container tightly closed.
Ground and/or bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe mist, vapours and/or spray.
Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.

- Response** • In case of fire: Use to extinguish.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTER/doctor if you feel unwell.
If on skin: Wash with plenty of water.
Take off contaminated clothing and wash before reuse.
Specific treatment, see supplemental first aid information.
If skin irritation occurs: Get medical advice/attention.
IF SWALLOWED: Immediately call a POISON CENTER/doctor.
Do NOT induce vomiting.
IF exposed or concerned: Get medical advice/attention.
Get medical advice/attention if you feel unwell.

- Storage/Disposal** • Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

HCS 2012 Other Information


- May ignite on surfaces at temperatures above auto-ignition temperature
Vapor in the headspace of tanks and containers may ignite and explode at temperatures exceeding auto-ignition temperature, where vapor concentrations are within the flammability range
This material is a static accumulator. Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapor mixtures can occur.
This product is intended for use in closed systems only

Other hazards

OSHA HCS 2012

- Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

Other information



Section 3 - Composition/Information on Ingredients

Substances

- Material does not meet the criteria of a substance.

Mixtures

Composition		
Chemical Name	Identifiers	%
Diesel fuels	CAS:68334-30-5	80% TO 100%
Naphthalene [0% TO 0.5%]	CAS:91-20-3	0% TO 0.5%
1-Methylethylbenzene [0% TO 0.5%]	CAS:98-82-8	0% TO 0.5%
Fatty acids, C16-18 and C18-unsatd., Me esters	CAS:67762-38-3	0% TO 20%
Alkanes, C10-20 branched and linear	CAS:928771-01-1	0% TO 5%

The product may contain several additives at <0.1% v/v each. Dyes and markers can be used to indicate tax status and prevent fraud.

Section 4: First-Aid Measures

Description of first aid measures

Inhalation

- Move victim to fresh air. Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing. Do not use mouth-to-mouth method if victim inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If signs/symptoms continue, get medical attention.

Skin

- In case of contact with substance, immediately flush skin with running water for at least 20 minutes. Remove contaminated clothing and shoes. Wash skin with soap and water. If irritation develops and persists, get medical attention.

Eye

- In case of contact with substance, immediately flush eyes with running water for at least 20 minutes. If eye irritation persists: Get medical advice/attention.

Ingestion

- Do not use mouth-to-mouth method if victim ingested the substance. Do NOT induce vomiting. Obtain medical attention immediately if ingested. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

Most important symptoms and effects, both acute and delayed

- Refer to Section 11 - Toxicological Information.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

- All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

Section 5: Fire-Fighting Measures

Extinguishing media

- Suitable Extinguishing Media** • LARGE FIRES: Water spray, fog or alcohol-resistant foam.
SMALL FIRES: Dry chemical, CO₂, water spray or alcohol-resistant foam.

Unsuitable Extinguishing Media

- Do not use direct water jets on the burning product as they could cause a steam explosion and spread of the fire.

Special hazards arising from the substance or mixture

Unusual Fire and Explosion Hazards

- HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames. Containers may explode when heated. Many liquids are lighter than water.

Vapors may form explosive mixtures with air.
 Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks).
 Vapors may travel to source of ignition and flash back.
 Vapor explosion hazard indoors, outdoors or in sewers.
 Runoff to sewer may create fire or explosion hazard.

Hazardous Combustion Products

- Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Oxides of sulphur. Unidentified organic and inorganic compounds. Carbon monoxide may be evolved if incomplete combustion occurs.

Advice for firefighters

- Structural firefighters' protective clothing will only provide limited protection. Wear positive pressure self-contained breathing apparatus (SCBA). Move containers from fire area if you can do it without risk.
LARGE FIRES: Cool containers with flooding quantities of water until well after fire is out.
 If the fire cannot be extinguished the only course of action is to evacuate immediately.

Section 6 - Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Personal Precautions

- Ventilate the area before entry. CAUTION: Victim may be a source of contamination. Do not walk through spilled material. Use appropriate Personal Protective Equipment (PPE) Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Emergency Procedures

- As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. **LARGE SPILL:** Consider initial downwind evacuation for at least 300 meters (1000 feet) **ELIMINATE** all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharge. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Monitor area with combustible gas meter. Do not operate electrical equipment.

Environmental precautions

- Prevent entry into waterways, sewers, basements or confined areas.

Methods and material for containment and cleaning up

Containment/Clean-up Measures

- Stop leak if you can do it without risk.
 For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal.
 For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal.
 Dike far ahead of spill for later disposal.
 Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.
 A vapor suppressing foam may be used to reduce vapors.
 All equipment used when handling the product must be grounded.
LARGE SPILLS: Water spray may reduce vapor; but may not prevent ignition in closed spaces.
 Do not flush away residues with water. Retain as contaminated waste.

Section 7 - Handling and Storage

Precautions for safe handling

Handling

- Keep away from heat, sparks, and flame. Do not use sparking tools. Take precautionary measures against static charges. All equipment used when handling the product must be grounded. The vapour is heavier than air, spreads along the ground and distant ignition is possible. Never siphon by mouth. Wear appropriate personal protective equipment, avoid direct contact. Do not breathe mist, vapours and/or spray. Avoid contact with skin, eyes, and clothing. Do not ingest. Wash thoroughly with soap

and water after handling and before eating, drinking, or using tobacco. Air-dry contaminated clothing in a well-ventilated area before laundering. Contaminated leather articles including shoes cannot be decontaminated and should be destroyed to prevent reuse. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Do not cut, drill, grind, weld or perform similar operations on or near containers. Containers, even those that have been emptied, can contain explosive vapours. Wait 2 minutes after tank filling (for tanks such as those on road tanker vehicles) before opening hatches or manholes. Wait 30 minutes after tank filling (for large storage tanks) before opening hatches or manholes. Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air vapour mixtures can occur. Be aware of handling operations that may give rise to additional hazards that result from the accumulation of static charges. These include but are not limited to pumping (especially turbulent flow), mixing, filtering, splash filling, cleaning and filling of tanks and containers, sampling, switch loading, gauging, vacuum truck operations, and mechanical movements. These activities may lead to static discharge e.g. spark formation. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (≤ 1 m/s until fill pipe submerged to twice its diameter, then ≤ 7 m/s). Avoid splash filling. Do NOT use compressed air for filling, discharging, or handling operations. Contamination resulting from product transfer may give rise to light hydrocarbon vapour in the headspace of tanks that have previously contained gasoline. This vapour may explode if there is a source of ignition. Partly filled containers present a greater hazard than those that are full, therefore handling, transfer and sampling activities need special care.

Conditions for safe storage, including any incompatibilities

Storage

- Take suitable precautions when opening sealed containers, as pressure can build up during storage. Drums should be stacked to a maximum of 3 high. Packaged product must be kept tightly closed and stored in a diked (bunded) well-ventilated area, away from, ignition sources and other sources of heat. Tanks must be specifically designed for use with this product. Bulk storage tanks should be diked (bunded). Locate tanks away from heat and other sources of ignition. Cleaning, inspection and maintenance of storage tanks is a specialist operation, which requires the implementation of strict procedures and precautions. Keep in a cool place. The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable.

Section 8 - Exposure Controls/Personal Protection

Control parameters

Exposure Limits/Guidelines				
	Result	ACGIH	NIOSH	OSHA
Naphthalene (91-20-3)	TWAs	10 ppm TWA	10 ppm TWA; 50 mg/m ³ TWA	10 ppm TWA; 50 mg/m ³ TWA
	STELs	Not established	15 ppm STEL; 75 mg/m ³ STEL	Not established
1-Methylethylbenzene (98-82-8)	TWAs	50 ppm TWA	50 ppm TWA; 245 mg/m ³ TWA	50 ppm TWA; 245 mg/m ³ TWA
Diesel fuels (68334-30-5)	TWAs	100 mg/m ³ TWA (inhalable fraction and vapor, as total hydrocarbons)	Not established	Not established

Exposure controls

Engineering Measures/Controls

- Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use explosion-proof electrical/ventilating/lighting/equipment.

Personal Protective Equipment

Respiratory

- In case of insufficient ventilation, wear suitable respiratory equipment. Where air-

filtering respirators are suitable, select an appropriate combination of mask and filter. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. Select a filter suitable for the combination of organic gases and vapours [Type A/Type P boiling point >65°C (149°F)].

Eye/Face
Skin/Body

- Wear safety goggles.
- Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. When prolonged or frequent repeated contact occurs. Nitrile rubber. For incidental contact/ splash protection Neoprene, PVC gloves may be suitable. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced.
- Controls should be engineered to prevent release to the environment, including procedures to prevent spills, atmospheric release and release to waterways. Follow best practice for site management and disposal of waste.

Environmental Exposure Controls

Key to abbreviations

ACGIH = American Conference of Governmental Industrial Hygiene

NIOSH = National Institute of Occupational Safety and Health

OSHA = Occupational Safety and Health Administration

STEL = Short Term Exposure Limits are based on 15-minute exposures

TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

Section 9 - Physical and Chemical Properties

Information on Physical and Chemical Properties

Material Description			
Physical Form	Liquid	Appearance/Description	Light straw colored liquid with typical hydrocarbon odor.
Color	Light straw	Odor	Hydrocarbon
Odor Threshold	No data available		
General Properties			
Boiling Point	170 to 390 °C(338 to 734 °F)	Melting Point/Freezing Point	No data available
Decomposition Temperature	No data available	pH	No data available
Specific Gravity/Relative Density	= 0.84 Water=1	Water Solubility	Negligible < 0.1 %
Viscosity	2 to 4.5 Centistoke (cSt, cS) or mm ² /sec @ 40 °C(104 °F)		
Volatility			
Vapor Pressure	<= 0.4 kPa @ 38 °C(100.4 °F)	Vapor Density	No data available
Evaporation Rate	No data available		
Flammability			
Flash Point	55 to 75 °C(131 to 167 °F)	UEL	6 %
LEL	1 %	Autoignition	> 220 °C(> 428 °F)
Flammability (solid, gas)	No data available		
Environmental			
Octanol/Water Partition coefficient	No data available		

Other Information

- Low conductivity: < 100 pS/m. The conductivity of this material makes it a static accumulator. A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semi-conductive if its conductivity is below 10,000 pS/m. Whether a liquid is nonconductive or semiconductive, the precautions are the same. A number of factors, for example liquid temperature, presence of contaminants, and antistatic additives can greatly influence the conductivity of a liquid.

Section 10: Stability and Reactivity

Reactivity

- No dangerous reaction known under conditions of normal use.

Chemical stability

- Stable under normal temperatures and pressures.

Possibility of hazardous reactions

- Hazardous polymerization will not occur.

Conditions to avoid

- Avoid heat, sparks, open flames and other ignition sources. In certain circumstances product can ignite due to static electricity.

Incompatible materials

- Strong oxidising agents.

Hazardous decomposition products

- Hazardous decomposition products are not expected to form during normal storage. Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulfur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

Section 11 - Toxicological Information

Information on toxicological effects

- Other Material Information**
- Basis for assessment: Information given is based on product data, a knowledge of the components and the toxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

		Components
Diesel fuels (90% TO 100%)	68334-30-5	<p>Acute Toxicity: Ingestion/Oral-Rat LD50 • 7500 mg/kg; Ingestion/Oral-Rat LD50 • >5000 mg/kg; Inhalation-Rat LC50 • 1-5 mg/L 4 Hour(s); Skin-Rabbit LD50 • >2000 mg/kg;</p> <p>Irritation: Skin-Rabbit • 500 µL 24 Hour(s) • Severe irritation;</p> <p>Multi-dose Toxicity: Inhalation-Rat TCLo • 2 g/m³ 6 Hour(s) 3 Week(s)-Intermittent; <i>Lungs, Thorax, or Respiration:</i>Fibrosis, focal (pneumoconiosis); Lungs, Thorax, or Respiration:Other changes; <i>Blood:</i>Changes in erythrocyte (RBC) count; Skin-Rat TDLo • 14 g/kg 14 Day(s)-Intermittent; <i>Blood:</i>Normocytic anemia; Blood:Leukopenia; Nutritional and Gross Metabolic:<i>Gross Metabolite Changes:</i>Weight loss or decreased weight gain</p>
		<p>Acute Toxicity: Ingestion/Oral-Rat LD50 • 490 mg/kg; Ingestion/Oral-Mouse TDLo • 158 mg/kg; <i>Brain and Coverings:</i>Other degenerative changes; Liver:Other changes; Biochemical:Metabolism (intermediary):Lipids, including transport; Inhalation-Human TCLo • 250 mg/m³; <i>Sense Organs and Special Senses:</i><i>Eye:</i>Lacrimation; Behavioral:Headache; Skin-Rabbit LD50 • >20 g/kg; Unreported-Guinea Pig LD50 • 1200 mg/kg; <i>Behavioral:</i>Somnolence (general depressed activity);</p> <p>Irritation: Skin-Rabbit • 0.05 mL 24 Hour(s) • Severe irritation;</p> <p>Multi-dose Toxicity: Ingestion/Oral-Rat TDLo • 4500 mg/kg 10 Day(s)-Intermittent; <i>Brain and Coverings:</i>Other</p>

Naphthalene (0% TO 0.5%)	91-20-3	<p>degenerative changes; Ingestion/Oral-Rat TDLo • 500 mg/kg 10 Day(s)-Intermittent; <i>Behavioral:Sleep</i>; <i>Lungs, Thorax, or Respiration:Dyspnea</i>;</p> <p>Mutagen: Specific locus test • Inhalation-Rat • 30 ppm 13 Week(s)-Intermittent; Micronucleus test • Unreported Route-Human • Lymphocyte (Somatic cell) • 30 mg/L;</p> <p>Reproductive: Ingestion/Oral-Mouse TDLo • 2400 mg/kg (7-14D preg); <i>Reproductive Effects:Effects on Newborn:Live birth index</i>; <i>Reproductive Effects:Effects on Newborn:Viability index (e.g., # alive at day 4 per # born alive)</i>; Ingestion/Oral-Rat TDLo • 4500 mg/kg (6-15D preg); <i>Reproductive Effects:Effects on Embryo or Fetus:Fetotoxicity (except death, e.g., stunted fetus)</i>; <i>Reproductive Effects:Specific Developmental Abnormalities:Other developmental abnormalities</i>;</p> <p>Tumorigen / Carcinogen: Inhalation-Mouse TCLo • 30 ppm 6 Hour(s) 2 Year(s)-Intermittent; <i>Tumorigenic:Neoplastic by RTECS criteria</i>; <i>Lungs, Thorax, or Respiration:Tumors</i>; Inhalation-Rat TCLo • 60 ppm 6 Hour(s) 105 Week(s)-Intermittent; <i>Tumorigenic:Carcinogenic by RTECS criteria</i>; <i>Sense Organs and Special Senses:Olfaction:Tumors</i>; Inhalation-Rat TCLo • 1575 mg/kg 105 Week(s)-Intermittent; <i>Tumorigenic:Carcinogenic by RTECS criteria</i>; <i>Sense Organs and Special Senses:Olfaction:Tumors</i></p>
1-Methylethylbenzene (0% TO 0.5%)	98-82-8	<p>Acute Toxicity: Ingestion/Oral-Rat LD50 • 1400 mg/kg; <i>Gastrointestinal:Gastritis</i>; Inhalation-Rat LC50 • 39000 mg/m³ 4 Hour(s); Inhalation-Human TCLo • 200 ppm; <i>Behavioral:Somnolence (general depressed activity)</i>; <i>Behavioral:Antipsychotic</i>; <i>Behavioral:Irritability</i>; Inhalation-Mouse TCLo • 5150 mg/m³ 2 Hour(s); <i>Behavioral:General anesthetic</i>; Inhalation-Rat TCLo • 300 ppm 30 Minute(s); <i>Lungs, Thorax, or Respiration:Respiratory depression</i>; Skin-Rabbit LD50 • 12300 µL/kg;</p> <p>Irritation: Eye-Rabbit • 500 mg 24 Hour(s) • Mild irritation; Skin-Rabbit • 100 mg 24 Hour(s) • Moderate irritation;</p> <p>Multi-dose Toxicity: Inhalation-Mouse TCLo • 2000 mg/m³ 14 Week(s)-Continuous; <i>Behavioral:Somnolence (general depressed activity)</i>; Inhalation-Rabbit TCLo • 10000 mg/m³ 2 Hour(s) 24 Week(s)-Intermittent; <i>Lungs, Thorax, or Respiration:Acute pulmonary edema</i>; <i>Blood:Hemorrhage</i>; <i>Blood:Changes in leucocyte (WBC) count</i>; Inhalation-Rat TCLo • 1200 ppm 6 Hour(s) 13 Week(s)-Intermittent; <i>Sense Organs and Special Senses:Eye:Other</i>; <i>Behavioral:Changes in motor activity (specific assay)</i>; <i>Blood:Pigmented or nucleated red blood cells</i>;</p> <p>Mutagen: Mutation in microorganisms • Unreported Route-Salmonella typhimurium • 100 µg/plate 3 Hour(s)(-S9)</p>

GHS Properties	Classification
Acute toxicity	OSHA HCS 2012 • Acute Toxicity - Inhalation 4
Skin corrosion/Irritation	OSHA HCS 2012 • Skin Irritation 2
Serious eye damage/Irritation	OSHA HCS 2012 • Classification criteria not met
Skin sensitization	OSHA HCS 2012 • Classification criteria not met
Respiratory sensitization	OSHA HCS 2012 • Classification criteria not met
Aspiration Hazard	OSHA HCS 2012 • Aspiration 1
Carcinogenicity	OSHA HCS 2012 • Carcinogenicity 2
Germ Cell Mutagenicity	OSHA HCS 2012 • Classification criteria not met
Toxicity for Reproduction	OSHA HCS 2012 • Classification criteria not met
STOT-SE	OSHA HCS 2012 • Classification criteria not met
STOT-RE	OSHA HCS 2012 • Specific Target Organ Toxicity Repeated Exposure 2

Potential Health Effects

Inhalation

- Acute (Immediate)**
 - Harmful if inhaled.
- Chronic (Delayed)**
 - No data available

Skin

- Acute (Immediate)**
 - Causes skin irritation.
- Chronic (Delayed)**
 - No data available

Eye

- Acute (Immediate)**
 - Expected to be slightly irritating.

- Chronic (Delayed)**
- No data available
- Ingestion**
- Acute (Immediate)**
- Material may be aspirated into lungs during ingestion and/or subsequent vomiting. Aspiration of this material will cause severe lung injury, chemical pneumonitis, pulmonary edema or death.
- Chronic (Delayed)**
- No data available
- Other**
- Chronic (Delayed)**
- Causes damage to Blood, Liver, Thymus through prolonged or repeated exposure.
- Carcinogenic Effects**
- Repeated and prolonged exposure may cause cancer.

Carcinogenic Effects			
	CAS	IARC	NTP
1-Methylethylbenzene	98-82-8	Group 2B-Possible Carcinogen	Reasonably Anticipated to be Human Carcinogen
Naphthalene	91-20-3	Group 2B-Possible Carcinogen	Reasonably Anticipated to be Human Carcinogen
Diesel fuels	68334-30-5	Group 2B-Possible Carcinogen	Not Listed
Diesel fuels as Exhaust, diesel	NDA	Group 1-Carcinogenic	Reasonably Anticipated to be Human Carcinogen

Key to abbreviations

LC = Lethal Concentration

LD = Lethal Dose

TC = Toxic Concentration

TD = Toxic Dose

Section 12 - Ecological Information

Toxicity

- Expected to be toxic to fish. Expected to be toxic to daphnia and other aquatic invertebrates. Expected to be toxic to algae.

Persistence and degradability

- Readily biodegradable.

Bioaccumulative potential

- Contains constituents with the potential to bioaccumulate.

Mobility in Soil

- Partly evaporates from water or soil surfaces, but a significant proportion will remain after one day. If product enters soil, one or more constituents will be mobile and may contaminate groundwater. Floats on water. Large volumes may penetrate soil and could contaminate groundwater.

Other adverse effects

- Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s). Fuels are typically made from blending several refinery streams. Ecotoxicological studies have been carried out on a variety of hydrocarbon blends and streams but not those containing additives.

Section 13 - Disposal Considerations

Waste treatment methods

Product waste

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging waste

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transport Information

	UN number	UN proper shipping name	Transport hazard class (es)	Packing group	Environmental hazards
DOT	NA1993	Diesel fuel	3	III	None
TDG	UN1202	DIESEL FUEL	3	III	NDA
IMO/IMDG	UN1202	DIESEL FUEL	3	III	Marine Pollutant
IATA/ICAO	UN1202	Diesel fuel	3	III	NDA

Special precautions for user • None specified.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code • No data available

Other information

- DOT** • This material is an 'OIL' under 49 CFR Part 130 when transported in a container of 3500 gallon capacity or greater.

Section 15 - Regulatory Information**Safety, health and environmental regulations/legislation specific for the substance or mixture**

SARA Hazard Classifications • Fire, Acute, Chronic

State Right To Know			
Component	CAS	NJ	PA
1-Methylethylbenzene	98-82-8	Yes	Yes
Alkanes, C10-20 branched and linear	928771-01-1	No	No
Diesel fuels	68334-30-5	No	Yes
Fatty acids, C16-18 and C18-unsatd., Me esters	67762-38-3	No	No
Naphthalene	91-20-3	Yes	Yes

Inventory		
Component	CAS	TSCA
1-Methylethylbenzene	98-82-8	Yes
Alkanes, C10-20 branched and linear	928771-01-1	Yes
Diesel fuels	68334-30-5	Yes
Fatty acids, C16-18 and C18-unsatd., Me esters	67762-38-3	Yes
Naphthalene	91-20-3	Yes

United States

Labor

U.S. - OSHA - Process Safety Management - Highly Hazardous Chemicals

• Diesel fuels	68334-30-5	Not Listed
• Fatty acids, C16-18 and C18-unsatd., Me esters	67762-38-3	Not Listed
• Alkanes, C10-20 branched and linear	928771-01-1	Not Listed
• Naphthalene	91-20-3	Not Listed
• 1-Methylethylbenzene	98-82-8	Not Listed

Environment

U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants

• Diesel fuels	68334-30-5	Not Listed
• Fatty acids, C16-18 and C18-unsatd., Me esters	67762-38-3	Not Listed
• Alkanes, C10-20 branched and linear	928771-01-1	Not Listed
• Naphthalene	91-20-3	
• 1-Methylethylbenzene	98-82-8	

U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities

• Diesel fuels	68334-30-5	Not Listed
• Fatty acids, C16-18 and C18-unsatd., Me esters	67762-38-3	Not Listed
• Alkanes, C10-20 branched and linear	928771-01-1	Not Listed
• Naphthalene	91-20-3	100 lb final RQ; 45.4 kg final RQ
• 1-Methylethylbenzene	98-82-8	5000 lb final RQ; 2270 kg final RQ

U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs

• Diesel fuels	68334-30-5	Not Listed
• Fatty acids, C16-18 and C18-unsatd., Me esters	67762-38-3	Not Listed
• Alkanes, C10-20 branched and linear	928771-01-1	Not Listed
• Naphthalene	91-20-3	Not Listed
• 1-Methylethylbenzene	98-82-8	Not Listed

U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs

• Diesel fuels	68334-30-5	Not Listed
• Fatty acids, C16-18 and C18-unsatd., Me esters	67762-38-3	Not Listed
• Alkanes, C10-20 branched and linear	928771-01-1	Not Listed
• Naphthalene	91-20-3	Not Listed
• 1-Methylethylbenzene	98-82-8	Not Listed

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

• Diesel fuels	68334-30-5	Not Listed
• Fatty acids, C16-18 and C18-unsatd., Me esters	67762-38-3	Not Listed
• Alkanes, C10-20 branched and linear	928771-01-1	Not Listed
• Naphthalene	91-20-3	0.1 % de minimis concentration
• 1-Methylethylbenzene	98-82-8	1.0 % de minimis concentration

U.S. - CERCLA/SARA - Section 313 - PBT Chemical Listing

• Diesel fuels	68334-30-5	Not Listed
• Fatty acids, C16-18 and C18-unsatd., Me esters	67762-38-3	Not Listed
• Alkanes, C10-20 branched and linear	928771-01-1	Not Listed
• Naphthalene	91-20-3	Not Listed

• 1-Methylethylbenzene

98-82-8

Not Listed

Other Information

- California Prop 65

⚠ WARNING: This product can expose you to chemicals including Naphthalene, Cumene, and Diesel engine exhaust which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Section 16 - Other Information

Revision Date	• 19/July/2021
Last Revision Date	• 07/May/2021
Preparation Date	• 14/February/2017
Other Information	<ul style="list-style-type: none"> • Code(s): 400007102; 400007103;v400007104; 400007105; 400007106; 400007110; 400007119; 400007302; 400007303; 400007304; 400007305; 400007306; 400007307; 400007311; 400007312; 400007313; 400007314; 400007405; 400007422; 400007423; 400007570; 400007574; 400007579; 400007583; 400007586; 400007591; 400007593; 400007594; 400007599; 400007600; 400007614; 400007615; 400007616; 400007617; 400007618; 400007619; 400007620; 400007621; 400007622; 400007623; 400007624; 400007625; 400007626; 400007629; 400007630; 400007631; 400007632; 400007644; 400007645; 400007646; 400007648; 400007649; 400007650; 400007651; 400007652; 400007653; 400007654; 400007655; 400007657; 400007658; 400007659; 400007660; 400007661; 400007662; 400007663; 400007664; 400007665; 400007666; 400007669; 400007780; 400007781; 400007783; 400007784; 400009229; 400009240; 400009241; 400009243; 400009244; 400009245; 400009246; 400009250; 400009261; 400009300; 400009497; 400009567; 400009568; 400009569; 400009570; 400009571; 400009572; 400009573; 400009574; 400009575; 400009576; 400009577; 400009578; 400009580; 400009581; 400009582; 400009583; 400009584; 400009586; 400009587; 400009597; 400009608; 400009637; 400009649; 400009669; 400009670; 400009671; 400009672; 400009674; 400009707; 400009709; 400009729; 400009734; 400009747; 400009767; 400009838; 400009839; 400009842; 400009843; 400009909; 400009910.
Synonyms	<ul style="list-style-type: none"> • GN PREM MV 2D (S-15 PPM) GN TXLED MV 2D (S-15 PPM) SH TXLED MV 2D (S-15 PPM) GN TXLED NR 2D (S-15 PPM) DYED GN TXLED MV 2D BLDSTK(S-15 PPM) SH TXLED NR DIESEL 2 (S-15 PPM)DYED GN MV #2D (S-15 ppm) EXPORT ONLY SH MV 2D NITRO ENRICH(S-15 PPM) GN MV 2D FUEL ECONOMY(S-15 PPM) GN NR 2D FUEL ECONOMY(S-15 PPM) DYED GN MV 2D FUEL ECONOMY WINTERAD(S-15PPM) GN NR 2D FUEL ECO WINTRAD(S-15 PPM)DYED SH TXLED MV 2D BIO 5% (S-15 PPM) GN TXLED NR 2D BIO 5% (S-15 PPM) GN TXLED NR 2D BIO 2% (S-15 PPM)DYED SH TXLED MV 2D BIO 2% (S-15 PPM) GN TXLED MV 2D BIO 2% (S-15 PPM) SH MV 2D (S-15 PPM) GN NR 2D (S-15 PPM) DYED GN MV 2D (S-15 PPM) GN NR 2D BIO 5% (S-15 PPM) DYED GN ULS HEATING OIL 2 DYED (15PPMS) GN MV 2D BIO 2% (S-15 PPM) SH NR 2D (S-15 PPM) DYED SH MV 2D WINTERADD (S-15 PPM)

- GN MV 2D WINTERADD (S-15 PPM)
- GN NR 2D WINTERADD (S-15 PPM) DYED
- GN TXLED MV 2D BIO 5% (S-15 PPM)
- GN MV 2D BIO 5% (S-15 PPM)
- SH MV 2D BIO 5% (S-15 PPM)
- GN NR 2D WINTERAD BIO 2% (S-15 PPM)DYED
- GN MV 2D WINTERADD BIO 5% (S-15 PPM)
- SH MV 2D WINTERADD BIO 5% (S-15 PPM)
- GN MV #2D R5 (S-15 PPM)
- GN TXLED NR 2D BIO 1% (S-15 PPM) DYED
- SH TXLED MV 2D BIO 1% (S-15 PPM)
- GN TXLED MV 2D BIO 1% (S-15 PPM)
- GN TXLED NR 2D BIO 3% (S-15 PPM) DYED
- SH TXLED MV 2D BIO 3% (S-15 PPM)
- GN TXLED MV 2D BIO 3% (S-15 PPM)
- GN NR 2D TXLED S15 B0-5% DYED
- SH MV 2D TXLED S15 B0-5%
- GN MV 2D TXLED S15 B0-5%
- GN GTL MV 2D (S-15PPM)
- GN HEATING OIL B2-5% (S-15PPM) DYED
- GN NR #2 WINTERAD BIO 5% (S-15 PPM) DYED
- SH NR #2 WINTERAD BIO 5%(S-15 PPM) DYED
- GN TXLED NR #2D BIO 4% (S-15 PPM) DYED
- SH TXLED MV #2D BIO 4% (S-15 PPM)
- GN TXLED MV #2D BIO 4% (S-15 PPM)
- SH MV #2D R5 (S-15 PPM)
- GN NR #2D R5 (S-15 PPM) DYED
- GN ULSD B 0-5% R 0-5%,
- SH ULSD B 0-5% R 0-5%
- GN ULSD B 0-5% R 0-5% DYED
- GN MV #2D B2 R5 (S-15 PPM)
- SH MV #2D B2 R5 (S-15 PPM)
- GN NR #2D B2 R5 (S-15 PPM) DYED
- GN MV #2 BIO 20% (S-15 PPM)
- SH NR #2D R5 (S-15 PPM) DYED USA
- GN MV #2D R5 FUEL ECO (S-15 PPM)
- GN NR #2D R5 FUEL ECO (S-15 PPM) DYED
- GN MV #2D R5 FUEL ECO WINAD(S-15PPM)
- GN NR #2D R5 FUEL ECO WINAD(S-15PPM)DYED
- GN MV #2D R5 WINT (S-15 PPM)
- GN NR 2D R5 WINT (S-15 PPM) DYED
- SH MV #2D R5 WINT (S-15 PPM)
- UB MV #2D R5 WINT (S-15 PPM)
- SH TXLED MV DD (S-15 PPM)
- GN ULS HEATING OIL 2 (15PPMS)
- SH MV #2D AREA D B5 (S-15 PPM)
- GN NR 2D AREA D B5 (S-15 PPM) DYED
- GN MV #2D AREA D B5 (S-15 PPM)
- 76 NR 2D ULSD S15 R0-5% DYED
- 76 MV 2D TXLED S15
- 76 MV 2D TXLED S15 B5%
- 76 MV 2D ULSD S15 B5%
- 76 MV 2D TXLED S15 B0-5%
- 76 MV 2D ULSD S15 R0-5%
- 76 MV 2D ULSD S15 B0-5% R0-5%
- 76 MV 2D ULSD S15
- 76 NR 2D ULSD S15 DYED
- 76 MV 2D ULSD S15 R0-5% WINT
- 76 MV 2D ULSD S15 B5% WINT
- MOT ULSD B 0-5% R 0-5%
- MOT MV 2D (S-15 PPM)
- MOT MV 2D BIO 5% (S-15 PPM)
- MOT TXLED NR DIESEL 2 (S-15 PPM)DYED
- MOT TXLED MV 2D (S-15 PPM)
- EXC MV 2D (S-15 PPM)

- EM S15 NO2 TXLED DSL EFFICIENT B0-5%
EXC TXLED MV 2D BIO 5% (S-15 PPM)
76 ULSD B 0-5% R 0-5%
76 MV 2D ULSD S15 WINT
GN NR 2D Marine ULSD S15 Dyed
76 MV 2D ULSD S15 B0-5%
GN MV 2D ULSD S15 B0-5%
GN NR 2D ULSD S15 B0-5% DYED
GN MV 2D ULSD S15 B0-5% WINT
GN NR 2D ULSD S15 B0-5% WINT DYED
GN HEATING OIL #2 S15 B4-5% DYED
SH MV 2D ULSD S15 B0-5%
MOT MV 2D ULSD S15 B0-5%
76 MV 2D ULSD S15 B0-5% WINT
76 NR 2D ULSD S15 B0-5% DYED
SH NR 2D ULSD S15 B0-5% DYED
76 NR 2D ULSD S15 B0-5% R 0-5% DYED
MOBIL ULSD S15 EFFICIENT B0-5 R0-5 DYED
EXXON ULSD S15 EFFICIENT B0-5 R0-5 DYED
GN ULS HO 2 (S-15 PPM) B0-5 R0-5
GN ULS HO 2 (S-15 PPM) B0-5 R0-5 DYED
GN TXLED S15 B20 DYED
GN TXLED S15 B20

Disclaimer/Statement of Liability

- This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

Key to abbreviations

NDA = No Data Available