		Page: 1
<b>SAFETY DATA SHEET</b>		Revision Date: 09/07/2018
		Print Date: 9/4/2020
		SDS Number: R0091437
Valvoline™ SAE 80W-90 HP GEAR OIL		Version: 1.9
VV836		

29 CFR 1910.1200 (OSHA HazCom 2012)

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

**Product identifier**

Trade name : Valvoline™ SAE 80W-90 HP GEAR OIL


<p><b>Details of the supplier of the safety data sheet</b>  Valvoline LLC  100 Valvoline Way  Lexington, KY 40509  United States of America (USA)  1-800-TEAMVAL (1-800-832-6825)</p> <p>SDS@valvoline.com</p>	<p><b>Emergency telephone number</b>  1-800-VALVOLINE (1-800-825-8654)</p> <p><b>Regulatory Information Number</b>  1-800-TEAMVAL (1-800-832-6825)</p> <p><b>Product Information</b>  1-800-TEAMVAL (1-800-832-6825)</p>
--	--

**SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification**

Skin sensitization : Category 1

**GHS label elements**

Hazard pictograms : 

Signal Word : Warning

Hazard Statements : May cause an allergic skin reaction.

Precautionary Statements : **Prevention:**  
Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.  
Contaminated work clothing must not be allowed out of the workplace.  
Wear protective gloves.  
**Response:**  
IF ON SKIN: Wash with plenty of soap and water.  
If skin irritation or rash occurs: Get medical advice/ attention.  
Wash contaminated clothing before reuse.  
**Disposal:**

**SAFETY DATA SHEET**

Revision Date: 09/07/2018

Print Date: 9/4/2020

SDS Number: R0091437

Valvoline™ SAE 80W-90 HP GEAR OIL

Version: 1.9

VV836

Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Hazardous components**

Chemical name	CAS-No.	Classification	Concentration (%)
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	Not a hazardous substance or mixture.	>=60.00 - < 70.00
OLEFINSULFIDE	68937-96-2	Skin Sens. 1B; H317	>=1.50 - < 5.00
React. prod. of bis(2-methylpentan-2-yl)dithiophosphoricacid + phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)		Flam. Liq. 4; H227 Acute Tox. 4; H302 Eye Dam. 1; H318 Skin Sens. 1; H317	>=0.50 - < 1.00

**SECTION 4. FIRST AID MEASURES**

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : If breathed in, move person into fresh air.  
If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.  
If on skin, rinse well with water.  
First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.  
Wash contaminated clothing before re-use.
- In case of eye contact : Flush eyes with water as a precaution.



<b>SAFETY DATA SHEET</b>	Revision Date: 09/07/2018
	Print Date: 9/4/2020
	SDS Number: R0091437
Valvoline™ SAE 80W-90 HP GEAR OIL VV836	Version: 1.9

Remove contact lenses.  
Protect unharmed eye.  
If eye irritation persists, consult a specialist.

If swallowed : Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed : No symptoms known or expected.  
May cause an allergic skin reaction.

Notes to physician : No hazards which require special first aid measures.

**SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Water spray  
Foam  
Carbon dioxide (CO2)  
Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : carbon dioxide and carbon monoxide  
Hydrocarbons  
Sulphur oxides

Specific extinguishing methods :  
  
Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and : Use personal protective equipment.  
Persons not wearing protective equipment should be excluded

**SAFETY DATA SHEET**

Revision Date: 09/07/2018

Print Date: 9/4/2020

SDS Number: R0091437

Valvoline™ SAE 80W-90 HP GEAR OIL

Version: 1.9

VV836

- emergency procedures : from area of spill until clean-up has been completed.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.
- Other information : Comply with all applicable federal, state, and local regulations.

**SECTION 7. HANDLING AND STORAGE**

- Advice on safe handling : Do not breathe vapours/dust.  
Do not smoke.  
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Container hazardous when empty.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
Smoking, eating and drinking should be prohibited in the application area.  
For personal protection see section 8.  
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3	ACGIH

**SAFETY DATA SHEET**

Revision Date: 09/07/2018

Print Date: 9/4/2020

SDS Number: R0091437

Valvoline™ SAE 80W-90 HP GEAR OIL

Version: 1.9

VV836

			Inhalable fraction	
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL

**Engineering measures** : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

**Personal protective equipment**

Respiratory protection : Respiratory protection is not required under normal conditions of use.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection

: Wear as appropriate:  
Impervious clothing  
Safety shoes  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.  
Discard gloves that show tears, pinholes, or signs of wear.  
Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures

: Wash hands before breaks and at the end of workday.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Physical state : liquid

Colour : amber

Odour : No data available

Odour Threshold : No data available

pH : No data available

**SAFETY DATA SHEET**

Revision Date: 09/07/2018

Print Date: 9/4/2020

SDS Number: R0091437

Valvoline™ SAE 80W-90 HP GEAR OIL

Version: 1.9

VV836

- Melting point/freezing point : No data available
- Boiling point/boiling range : > 424.9 °F / 218.3 °C  
(1013.333 hPa)
- Flash point : 394 - 480 °F / 201 - 249 °C  
Method: Cleveland open cup
- Evaporation rate : > 1  
Ethyl Ether
- Flammability (solid, gas) : No data available
- Upper explosion limit : No data available
- Lower explosion limit : No data available
- Vapour pressure : < 0.1000000 mmHg
- Relative vapour density : > 1AIR=1
- Relative density : 0.89 (60.00 °F)
- Density : 0.8916 g/cm3 (15.56 °C)
- Solubility(ies)
  - Water solubility : No data available
  - Solubility in other solvents : No data available
- Partition coefficient: n-octanol/water : No data available
- Thermal decomposition : No data available
- Viscosity
  - Viscosity, dynamic : No data available
  - Viscosity, kinematic : 146 mm2/s (40 °C)
- Oxidizing properties : No data available

**SECTION 10. STABILITY AND REACTIVITY**

- Reactivity : No decomposition if stored and applied as directed.
- Chemical stability : Stable under recommended storage conditions.

**SAFETY DATA SHEET**

Revision Date: 09/07/2018

Print Date: 9/4/2020

SDS Number: R0091437

Valvoline™ SAE 80W-90 HP GEAR OIL

Version: 1.9

VV836

Possibility of hazardous reactions : Product will not undergo hazardous polymerization.

Conditions to avoid : None known.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : carbon dioxide and carbon monoxide  
Sodium oxides

**SECTION 11. TOXICOLOGICAL INFORMATION**

**Information on likely routes of exposure**

- Inhalation
- Skin contact
- Eye Contact
- Ingestion

**Acute toxicity**

Not classified based on available information.

**Product:**

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg  
Method: Calculation method

**Components:**

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

**OLEFINSULFIDE:**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 401  
Assessment: Not classified as acutely toxic by ingestion under GHS.  
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: Not classified as acutely toxic by dermal absorption under GHS.  
Remarks: No mortality observed at this dose.

**React. prod. of bis(2-methylpentan-2-yl)dithiophosphoricacid + phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched):**

Acute oral toxicity : LD50 (Rat): ca. 2,000 mg/kg  
Method: OECD Test Guideline 401  
Assessment: The component/mixture is classified as acute

**SAFETY DATA SHEET**

Revision Date: 09/07/2018

Print Date: 9/4/2020

SDS Number: R0091437

Valvoline™ SAE 80W-90 HP GEAR OIL

Version: 1.9

VV836

oral toxicity, category 4.

**Skin corrosion/irritation**

Not classified based on available information.

**Product:**

Remarks : May cause skin irritation in susceptible persons.

**Components:****DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Assessment : Slight, transient irritation

Result : Slight, transient irritation

**OLEFINSULFIDE:**

Result : Mild skin irritation

**Serious eye damage/eye irritation**

Not classified based on available information.

**Product:**

Remarks : Vapours may cause irritation to the eyes, respiratory system and the skin.

Remarks : Unlikely to cause eye irritation or injury.

**Components:****DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Result : No eye irritation

Assessment : No eye irritation

**OLEFINSULFIDE:**

Result : Slight, transient irritation

**React. prod. of bis(2-methylpentan-2-yl)dithiophosphoricacid + phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched):**

Result : Corrosive

**Respiratory or skin sensitisation****Skin sensitisation**

May cause an allergic skin reaction.

**Respiratory sensitisation**

Not classified based on available information.

**Product:**

Remarks : May cause allergic skin reaction.

**Components:****OLEFINSULFIDE:**

Test Type : Maximisation Test

Species : Guinea pig

Assessment : The product is a skin sensitiser, sub-category 1B.

Method : OECD Test Guideline 406



**SAFETY DATA SHEET**

Revision Date: 09/07/2018

Print Date: 9/4/2020

SDS Number: R0091437

Valvoline™ SAE 80W-90 HP GEAR OIL

Version: 1.9

VV836

**React. prod. of bis(2-methylpentan-2-yl)dithiophosphoricacid + phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched):**

Test Type : Local lymph node assay  
Species : Mouse  
Method : OECD Test Guideline 429  
Result : May cause sensitisation by skin contact.

**Germ cell mutagenicity**

Not classified based on available information.

**Components:****OLEFINSULFIDE:**

Genotoxicity in vitro : Test Type: in vitro assay  
Result: Positive results were obtained in some in vitro tests.

Genotoxicity in vivo : Test Type: Micronucleus test  
Species: Mouse  
Cell type: Bone marrow  
Method: OECD Test Guideline 474  
Result: negative

**Carcinogenicity**

Not classified based on available information.

**Components:****DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Carcinogenicity - Assessment : Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)

**IARC** No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP** No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Reproductive toxicity**

Not classified based on available information.

**STOT - single exposure**

Not classified based on available information.

**STOT - repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

**Product:**

No aspiration toxicity classification

**Components:****DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

No aspiration toxicity classification

**SAFETY DATA SHEET**

Revision Date: 09/07/2018

Print Date: 9/4/2020

SDS Number: R0091437

Valvoline™ SAE 80W-90 HP GEAR OIL

Version: 1.9

VV836

**Further information****Product:**

Remarks : No data available

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Product:**

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Acute aquatic toxicity Category 3; Harmful to aquatic life.

Long-term (chronic) aquatic hazard : Chronic aquatic toxicity Category 3; Harmful to aquatic life with long lasting effects.

**Components:**

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Toxicity to fish : LL50 (Fish): > 100 mg/l  
Exposure time: 96 hToxicity to daphnia and other aquatic invertebrates : EL50 (Aquatic invertebrates): > 10,000 mg/l  
Exposure time: 48 hToxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l  
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC (Fish): 10 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Aquatic invertebrates): 10 mg/l

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Not classified based on available information.

Long-term (chronic) aquatic hazard : Not classified based on available information.

**OLEFINSULFIDE:**

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Harmful to aquatic life.

Long-term (chronic) aquatic hazard : Harmful to aquatic life with long lasting effects.

<b>SAFETY DATA SHEET</b>	Revision Date: 09/07/2018
	Print Date: 9/4/2020
	SDS Number: R0091437
Valvoline™ SAE 80W-90 HP GEAR OIL VV836	Version: 1.9

React. prod. of bis(2-methylpentan-2-yl)dithiophosphoricacid + phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched):

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): ca. 24 mg/l  
 Exposure time: 96 h  
 Test Type: static test  
 Test substance: WAF  
 Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): ca. 91.4 mg/l  
 Exposure time: 48 h  
 Test Type: static test  
 Test substance: WAF  
 Method: OECD Test Guideline 202

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): 15 mg/l  
 End point: Growth inhibition  
 Exposure time: 96 h  
 Test Type: static test  
 Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 3.3 mg/l  
 End point: Growth inhibition  
 Exposure time: 96 h  
 Test Type: static test  
 Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.12 mg/l  
 Exposure time: 21 d  
 End point: Reproduction Test  
 Test Type: semi-static test  
 Test substance: WAF  
 Method: OECD Test Guideline 211

Ecotoxicology Assessment Short-term (acute) aquatic hazard : Toxic to aquatic life.


Long-term (chronic) aquatic hazard : Toxic to aquatic life with long lasting effects.

**Persistence and degradability**

**Components:**

**OLEFINSULFIDE:**

Biodegradability : Result: Not readily biodegradable.  
 Biodegradation: 13 %  
 Exposure time: 28 d  
 Method: OECD Test Guideline 301B

		Page: 12
<b>SAFETY DATA SHEET</b>		Revision Date: 09/07/2018
		Print Date: 9/4/2020
		SDS Number: R0091437
Valvoline™ SAE 80W-90 HP GEAR OIL		Version: 1.9
VV836		

React. prod. of bis(2-methylpentan-2-yl)dithiophosphoricacid + phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched):

Biodegradability : Result: Not readily biodegradable.  
 Biodegradation: 7.4 %  
 Exposure time: 28 d  
 Method: Modified Sturm Test

No data available

**Bioaccumulative potential**

**Components:**

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Partition coefficient: n-octanol/water : log Pow: Expected > 7

React. prod. of bis(2-methylpentan-2-yl)dithiophosphoricacid + phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched):

Partition coefficient: n-octanol/water : Remarks: No data available

No data available

**Mobility in soil**

**Components:**

No data available

**Other adverse effects**

No data available

**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.

**Components:**

---

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods**

General advice : The product should not be allowed to enter drains, water courses or the soil.  
 Do not contaminate ponds, waterways or ditches with chemical or used container.  
 Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.  
 Dispose of as unused product.  
 Empty containers should be taken to an approved waste handling site for recycling or disposal.  
 Do not re-use empty containers.



**SAFETY DATA SHEET**

Revision Date: 09/07/2018

Print Date: 9/4/2020

SDS Number: R0091437

Valvoline™ SAE 80W-90 HP GEAR OIL

Version: 1.9

VV836

**SECTION 14. TRANSPORT INFORMATION**

**International transport regulations**

**REGULATION**

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

**U.S. DOT - ROAD**

Not dangerous goods

**CFR\_RAIL\_C**

Not dangerous goods

**U.S. DOT - INLAND WATERWAYS**

Not dangerous goods

**TDG\_ROAD\_C**

Not dangerous goods

**TDG\_RAIL\_C**

Not dangerous goods

**TDG\_INWT\_C**

Not dangerous goods

**INTERNATIONAL MARITIME DANGEROUS GOODS**

Not dangerous goods

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO**

Not dangerous goods


**INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER**

Not dangerous goods

**MX\_DG**

Not dangerous goods

\*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

		Page: 14
<b>SAFETY DATA SHEET</b>		Revision Date: 09/07/2018
		Print Date: 9/4/2020
		SDS Number: R0091437
Valvoline™ SAE 80W-90 HP GEAR OIL		Version: 1.9
VV836		

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

---

## SECTION 15. REGULATORY INFORMATION

### EPCRA - Emergency Planning and Community Right-to-Know Act

#### CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Respiratory or skin sensitisation

### California Prop. 65

This product contains a chemical that is at or below California Propositions 65's "safe harbor level" for carcinogenicity as determined via a risk assessment. Therefore, the chemical is not required to be listed as a Prop 65 chemical on the SDS or label.

This product contains a chemical that is at or below California Propositions 65's "safe harbor level" for reproductive/developmental toxicity as determined via a risk assessment. Therefore, the chemical is not required to be listed as a Prop 65 chemical on the SDS or label.

#### The components of this product are reported in the following inventories:

- DSL : All components of this product are on the Canadian DSL
- AICS : On the inventory, or in compliance with the inventory
- ENCS : On the inventory, or in compliance with the inventory
- KECI : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory
- TSCA : On TSCA Inventory

#### TSCA list

No substances are subject to TSCA 12(b) export notification requirements.

---

## SECTION 16. OTHER INFORMATION

**SAFETY DATA SHEET**

Revision Date: 09/07/2018

Print Date: 9/4/2020

SDS Number: R0091437


Valvoline™ SAE 80W-90 HP GEAR OIL

Version: 1.9

VV836

**Further information**

Revision Date: 09/07/2018

NFPA:	HMIS III:						
<p style="text-align: center;">Flammability</p>  <p style="text-align: center;">Special hazard.</p>	<table border="1" style="width: 100%;"> <tr> <td style="background-color: blue; color: white;"><b>HEALTH</b></td> <td style="text-align: center;"><b>2</b></td> </tr> <tr> <td style="background-color: red; color: white;"><b>FLAMMABILITY</b></td> <td style="text-align: center;"><b>1</b></td> </tr> <tr> <td style="background-color: yellow;"><b>PHYSICAL HAZARD</b></td> <td style="text-align: center;"><b>0</b></td> </tr> </table> <p>0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	<b>HEALTH</b>	<b>2</b>	<b>FLAMMABILITY</b>	<b>1</b>	<b>PHYSICAL HAZARD</b>	<b>0</b>
<b>HEALTH</b>	<b>2</b>						
<b>FLAMMABILITY</b>	<b>1</b>						
<b>PHYSICAL HAZARD</b>	<b>0</b>						

**NFPA Flammable and Combustible Liquids Classification**

Combustible Liquid Class IIIB

**Full text of H-Statements**

- H227 Combustible liquid.
- H302 Harmful if swallowed.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).


List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

		Page: 16
<b>SAFETY DATA SHEET</b>		Revision Date: 09/07/2018
		Print Date: 9/4/2020
		SDS Number: R0091437
Valvoline™ SAE 80W-90 HP GEAR OIL		Version: 1.9
VV836		

FG : Food grade  
 GHS : Globally Harmonized System of Classification and Labeling of Chemicals.  
 H-statement : Hazard Statement  
 IATA : International Air Transport Association.  
 IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization  
 ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"  
 IMDG : International Maritime Code for Dangerous Goods  
 ISO : International Organization for Standardization  
 logPow : octanol-water partition coefficient  
 LCxx : Lethal Concentration, for xx percent of test population  
 LDxx : Lethal Dose, for xx percent of test population.  
 ICxx : Inhibitory Concentration for xx of a substance  
 Ecxx : Effective Concentration of xx  
 N.O.S.: Not Otherwise Specified  
 OECD : Organization for Economic Co-operation and Development  
 OEL : Occupational Exposure Limit  
 P-Statement : Precautionary Statement  
 PBT : Persistent , Bioaccumulative and Toxic  
 PPE : Personal Protective Equipment  
 STEL : Short-term exposure limit  
 STOT : Specific Target Organ Toxicity  
 TLV : Threshold Limit Value  
 TWA : Time-weighted average  
 vPvB : Very Persistent and Very Bioaccumulative  
 WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act  
 DOT : Department of Transportation  
 FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act  
 HMIRC : Hazardous Materials Information Review Commission  
 HMIS : Hazardous Materials Identification System  
 NFPA : National Fire Protection Association  
 NIOSH : National Institute for Occupational Safety and Health  
 OSHA : Occupational Safety and Health Administration  
 PMRA : Health Canada Pest Management Regulatory Agency  
 RTK : Right to Know  
 WHMIS : Workplace Hazardous Materials Information System