

CF-AS CJP; CF ISO 765; CF ISO 500+; CF-I ECO +; CS-F JS; CF 812 CC; CF-F ECO; CF-I 50 ECO GV;CF 125-50; CF 125-5W50; CF 126-N; CF 126; CF ISO 750; CF-I 750 B2 (-SV);CF 116-45; CF F 600; CF 116; CF-JI; CF 812; CF 812 WD; CF-I 65 ECO; CF-I XTW WD

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 09/01/2016

Revision date: 09/02/2016

Supersedes: 09/01/2016

Version: 5.2

SECTION 1: Identification

1.1. Identification

Product form	Mixture
Trade name	CF-AS CJP; CF ISO 765; CF ISO 500+; CF-I ECO +; CS-F JS; CF 812 CC; CF-F ECO; CF-I 50 ECO GV;CF 125-50; CF 125-5W50; CF 126-N; CF 126; CF ISO 750; CF-I 750 B2 (-SV);CF 116-45; CF F 600; CF 116; CF-JI; CF 812; CF 812 WD; CF-I 65 ECO; CF-I XTW WD
Product code	BU Chemicals

1.2. Relevant identified uses of the substance or mixture and uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Hilti, Inc.
 Legacy Tower, Suite 1000
 75024 Plano - USA
 T +1 9724035800
 1-800-879-8000 toll free - F +1 918 254 0522

Supplier
 Hilti, Inc.
 Legacy Tower, Suite 1000
 75024 Plano - USA
 T +1 9724035800
 1-800-879-8000 toll free - F +1 918 254 0522

Department issuing data specification sheet
 Hilti AG
 Feldkircherstraße 100
 9494 Schaan - Liechtenstein
 T +423 234 2111
chemicals.hse@hilti.com

1.4. Emergency telephone number

Emergency number	Chem-Trec Tel.: 1 800 424 9300 (USA, PR, Virgin Islands, Canada) Tel.: 703 527 3887 (Other countries) +1 918 8723000 1-800-879-8000 toll free
------------------	---

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Aerosol 1	H222 - Extremely flammable aerosol
Acute Tox. 4 (Inhalation:dust,mist)	H332 - Harmful if inhaled
Skin Irrit. 2	H315 - Causes skin irritation
Eye Irrit. 2A	H319 - Causes serious eye irritation
Resp. Sens. 1	H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled
Skin Sens. 1	H317 - May cause an allergic skin reaction
Carc. 2	H351 - Suspected of causing cancer
STOT SE 3	H335 - May cause respiratory irritation
STOT RE 2	H373 - May cause damage to organs through prolonged or repeated exposure

CF-AS CJP; CF ISO 765; CF ISO 500+; CF-I ECO +; CS-F JS; CF 812 CC; CF-F ECO; CF-I 50 ECO GV;CF 125-50; CF 125-5W50; CF 126-N; CF 126; CF ISO 750; CF-I 750 B2 (-SV);CF 116-45; CF F 600; CF 116; CF-JI; CF 812; CF 812 WD; CF-I 65 ECO; CF-I XTW WD

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H statements : see section 16

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US)



GHS02

GHS07

GHS08

Signal word (GHS-US)

Danger

Hazard statements (GHS-US)

- H222 - Extremely flammable aerosol
- H315 - Causes skin irritation
- H317 - May cause an allergic skin reaction
- H319 - Causes serious eye irritation
- H332 - Harmful if inhaled
- H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled
- H335 - May cause respiratory irritation
- H351 - Suspected of causing cancer
- H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US)

- P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking
- P211 - Do not spray on an open flame or other ignition source
- P251 - Pressurized container: Do not pierce or burn, even after use
- P260 - Do not breathe spray
- P280 - Wear eye protection, protective clothing, protective gloves
- P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

CF-AS CJP; CF ISO 765; CF ISO 500+; CF-I ECO +; CS-F JS; CF 812 CC; CF-F ECO; CF-I 50 ECO GV;CF 125-50; CF 125-5W50; CF 126-N; CF 126; CF ISO 750; CF-I 750 B2 (-SV);CF 116-45; CF F 600; CF 116; CF-JI; CF 812; CF 812 WD; CF-I 65 ECO; CF-I XTW WD

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS-US classification
4,4'-diphenylmethanediisocyanate, isomeres and homologues	(CAS No) 9016-87-9	40 - 60	Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373
tris(2-chloro-1-methylethyl) phosphate	(CAS No) 13674-84-5	10 - 25	Acute Tox. 4 (Oral), H302
Propane	(CAS No) 74-98-6	10 - 25	Flam. Gas 1, H220 Compressed gas, H280
Isobutane	(CAS No) 75-28-5	10 - 25	Flam. Gas 1, H220 Compressed gas, H280
Butane	(CAS No) 106-97-8	10 - 25	Flam. Gas 1, H220 Compressed gas, H280

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Symptoms/injuries after skin contact	Irritation. May cause an allergic skin reaction.
Symptoms/injuries after eye contact	Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

5.2. Special hazards arising from the substance or mixture

Fire hazard	Extremely flammable aerosol.
Explosion hazard	Pressurised container: May burst if heated.
Reactivity	Extremely flammable aerosol. Pressurised container: May burst if heated.

5.3. Advice for firefighters

Protection during firefighting	Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

CF-AS CJP; CF ISO 765; CF ISO 500+; CF-I ECO +; CS-F JS; CF 812 CC; CF-F ECO; CF-I 50 ECO GV;CF 125-50; CF 125-5W50; CF 126-N; CF 126; CF ISO 750; CF-I 750 B2 (-SV);CF 116-45; CF F 600; CF 116; CF-JI; CF 812; CF 812 WD; CF-I 65 ECO; CF-I XTW WD

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Propane (74-98-6)		
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
Isobutane (75-28-5)		
ACGIH	ACGIH TWA (ppm)	1000 ppm
ACGIH	ACGIH STEL (ppm)	1000 ppm
tris(2-chloro-1-methylethyl) phosphate (13674-84-5)		
Not applicable		
Butane (106-97-8)		
ACGIH	ACGIH TWA (ppm)	1000 ppm
ACGIH	ACGIH STEL (ppm)	1000 ppm

8.2. Exposure controls

Appropriate engineering controls
Personal protective equipment

Ensure good ventilation of the work station.
Protective clothing. Safety glasses. Gloves.



Hand protection
Skin and body protection
Respiratory protection
Environmental exposure controls

Protective gloves.
Wear suitable protective clothing.
In case of inadequate ventilation wear respiratory protection.
Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Appearance	Aerosol.
Colour	Mixture contains one or more component(s) which have the following colour(s): Dark amber Colourless
Odour	There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odour(s): Stuffy odour Mild odour Characteristic odour Ether-like odour Pure substance is odourless Commercial/unpurified substance: Unpleasant odour Irritating/pungent odour
Odour threshold	No data available
pH	No data available
Melting point	Not applicable
Freezing point	No data available
Boiling point	< 35 °C
Flash point	< 0 °C
Relative evaporation rate (butylacetate=1)	No data available
Flammability (solid, gas)	No data available
Explosive limits	No data available

CF-AS CJP; CF ISO 765; CF ISO 500+; CF-I ECO +; CS-F JS; CF 812 CC; CF-F ECO; CF-I 50 ECO GV;CF 125-50; CF 125-5W50; CF 126-N; CF 126; CF ISO 750; CF-I 750 B2 (-SV);CF 116-45; CF F 600; CF 116; CF-JI; CF 812; CF 812 WD; CF-I 65 ECO; CF-I XTW WD

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Explosive properties	Pressurised container: May burst if heated.
Oxidising properties	No data available
Vapour pressure	No data available
Relative density	No data available
Relative vapour density at 20 °C	No data available
Density	< 1.3 g/cm ³
Solubility	No data available
Log Pow	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Viscosity	No data available
Viscosity, kinematic	No data available
Viscosity, dynamic	No data available

9.2. Other information

VOC content	< 4 g/l EPA method 24
-------------	-----------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Heating may cause a fire or explosion.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No additional information available.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	Inhalation:dust,mist: Harmful if inhaled.
----------------	---

CF-AS CJP; CF ISO 765; CF ISO 500+; CF-I ECO +; CS-F JS; CF 812 CC; CF-F ECO; CF-I 50 ECO GV;CF 125-50; CF 125-5W50; CF 126-N; CF 126; CF ISO 750; CF-I 750 B2 (-SV);CF 116-45; CF F 600; CF 116; CF-JI; CF 812; CF 812 WD; CF-I 65 ECO; CF-I XTW WD	
ATE US (dust,mist)	3.061 mg/l/4h

CF-AS CJP; CF ISO 765; CF ISO 500+; CF-I ECO +; CS-F JS; CF 812 CC; CF-F ECO; CF-I 50 ECO GV;CF 125-50; CF 125-5W50; CF 126-N; CF 126; CF ISO 750; CF-I 750 B2 (-SV);CF 116-45; CF F 600; CF 116; CF-JI; CF 812; CF 812 WD; CF-I 65 ECO; CF-I XTW WD

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4,4'-diphenylmethanediisocyanate, isomeres and homologues (9016-87-9)	
LD50 oral rat	> 10000 mg/kg (Rat; Literature study)
LD50 dermal rabbit	> 5000 mg/kg (Rabbit; Literature study)
ATE US (gases)	4500.000 ppmv/4h
ATE US (vapours)	11.000 mg/l/4h
ATE US (dust,mist)	1.500 mg/l/4h

Propane (74-98-6)	
LC50 inhalation rat (mg/l)	513 mg/l/4h (Rat; Literature)
LC50 inhalation rat (ppm)	280000 ppm/4h (Rat; Literature)
ATE US (gases)	280000.000 ppmv/4h
ATE US (vapours)	513.000 mg/l/4h
ATE US (dust,mist)	513.000 mg/l/4h

Isobutane (75-28-5)	
LC50 inhalation rat (mg/l)	> 50 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	11000 ppm

tris(2-chloro-1-methylethyl) phosphate (13674-84-5)	
LD50 oral rat	2800 - 4200 mg/kg bodyweight (Rat; Equivalent or similar to OECD 401; Experimental value; 1011-1824 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rat	> 2000 mg/kg (Rat; Experimental value)
LD50 dermal rabbit	> 2000 mg/kg bodyweight (Rabbit; Experimental value; OECD 402: Acute Dermal Toxicity)
ATE US (oral)	500.000 mg/kg bodyweight

Butane (106-97-8)	
LC50 inhalation rat (mg/l)	658 mg/l/4h (Rat; Literature)
LC50 inhalation rat (ppm)	276000 ppm/4h (Rat; Literature)
ATE US (gases)	276000.000 ppmv/4h
ATE US (vapours)	658.000 mg/l/4h
ATE US (dust,mist)	658.000 mg/l/4h

Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/irritation	Causes serious eye irritation.
Respiratory or skin sensitisation	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified
Carcinogenicity	Suspected of causing cancer.

4,4'-diphenylmethanediisocyanate, isomeres and homologues (9016-87-9)	
IARC group	3 - Not classifiable

Reproductive toxicity	Not classified
Specific target organ toxicity (single exposure)	May cause respiratory irritation.
Specific target organ toxicity (repeated exposure)	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	Not classified
Symptoms/injuries after inhalation	May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Symptoms/injuries after skin contact	Irritation. May cause an allergic skin reaction.

CF-AS CJP; CF ISO 765; CF ISO 500+; CF-I ECO +; CS-F JS; CF 812 CC; CF-F ECO; CF-I 50 ECO GV;CF 125-50; CF 125-5W50; CF 126-N; CF 126; CF ISO 750; CF-I 750 B2 (-SV);CF 116-45; CF F 600; CF 116; CF-JI; CF 812; CF 812 WD; CF-I 65 ECO; CF-I XTW WD

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/injuries after eye contact Eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general May cause long lasting harmful effects to aquatic life.

4,4'-diphenylmethanediisocyanate, isomeres and homologues (9016-87-9)	
LC50 other aquatic organisms 1	> 1000 mg/l (96 h)
Threshold limit other aquatic organisms 1	> 1000 mg/l (96 h)
Propane (74-98-6)	
TLM fish 1	17.8 - 19.7,96 h; Pimephales promelas
Threshold limit algae 1	1.45 - 4.53,72 h; Algae
Threshold limit algae 2	8 mg/l (72 h; Algae)
Isobutane (75-28-5)	
Threshold limit algae 1	1.07 mg/l (Algae)
Threshold limit algae 2	7.15 mg/l (72 h; Algae)
tris(2-chloro-1-methylethyl) phosphate (13674-84-5)	
LC50 fish 1	98 mg/l (96 h; Pimephales promelas; GLP)
EC50 Daphnia 1	65 - 335 mg/l (48 h; Daphnia magna; GLP)
LC50 fish 2	56.2 mg/l (96 h; Brachydanio rerio)
Threshold limit algae 1	73 mg/l (96 h; Selenastrum capricornutum; Growth rate)
Butane (106-97-8)	
TLM fish 1	1000 mg/l (96 h; Pisces)
Threshold limit other aquatic organisms 1	0.6 - 0.9,504 h; Daphnia magna
Threshold limit algae 1	0.88 - 1.76,Algae

12.2. Persistence and degradability

4,4'-diphenylmethanediisocyanate, isomeres and homologues (9016-87-9)	
Persistence and degradability	Not readily biodegradable in water. Hydrolysis in water. No (test)data on mobility of the substance available.
Propane (74-98-6)	
Persistence and degradability	Readily biodegradable in water. Not applicable (gas). Photodegradation in the air.
Isobutane (75-28-5)	
Persistence and degradability	Inherently biodegradable. Biodegradable in the soil. Not applicable (gas).
tris(2-chloro-1-methylethyl) phosphate (13674-84-5)	
Persistence and degradability	Not readily biodegradable in water. No (test)data on mobility of the substance available.
Butane (106-97-8)	
Persistence and degradability	Readily biodegradable in water.

12.3. Bioaccumulative potential

4,4'-diphenylmethanediisocyanate, isomeres and homologues (9016-87-9)	
BCF fish 1	1 (Pisces)
Bioaccumulative potential	Not bioaccumulative.

CF-AS CJP; CF ISO 765; CF ISO 500+; CF-I ECO +; CS-F JS; CF 812 CC; CF-F ECO; CF-I 50 ECO GV;CF 125-50; CF 125-5W50; CF 126-N; CF 126; CF ISO 750; CF-I 750 B2 (-SV);CF 116-45; CF F 600; CF 116; CF-JI; CF 812; CF 812 WD; CF-I 65 ECO; CF-I XTW WD

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.2. UN proper shipping name

Proper Shipping Name (ADR)	AEROSOLS
Proper Shipping Name (IMDG)	AEROSOLS
Proper Shipping Name (IATA)	Aerosols, flammable
Proper Shipping Name (ADN)	AEROSOLS
Proper Shipping Name (RID)	AEROSOLS
Transport document description (ADR)	UN 1950 AEROSOLS, 2.1, (D)
Transport document description (IMDG)	UN 1950 AEROSOLS, 2.1

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR)	2.1
Danger labels (ADR)	2.1



IMDG

Transport hazard class(es) (IMDG)	2.1
Danger labels (IMDG)	2.1



IATA

Transport hazard class(es) (IATA)	2.1
Hazard labels (IATA)	2.1



ADN

Transport hazard class(es) (ADN)	2.1
Danger labels (ADN)	2.1

CF-AS CJP; CF ISO 765; CF ISO 500+; CF-I ECO +; CS-F JS; CF 812 CC; CF-F ECO; CF-I 50 ECO GV;CF 125-50; CF 125-5W50; CF 126-N; CF 126; CF ISO 750; CF-I 750 B2 (-SV);CF 116-45; CF F 600; CF 116; CF-JI; CF 812; CF 812 WD; CF-I 65 ECO; CF-I XTW WD

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations



RID

Transport hazard class(es) (RID)	2.1
Danger labels (RID)	2.1



14.4. Packing group

Packing group (ADR)	Not applicable
Packing group (IMDG)	Not applicable
Packing group (IATA)	Not applicable
Packing group (ADN)	Not applicable
Packing group (RID)	Not applicable

14.5. Environmental hazards

Dangerous for the environment	No
Marine pollutant	No
Other information	No supplementary information available

14.6. Special precautions for user

- Overland transport

Classification code (ADR)	5F
Special provisions (ADR)	190, 327, 344, 625
Limited quantities (ADR)	1I
Packing instructions (ADR)	P207, LP02
Mixed packing provisions (ADR)	MP9
Tunnel restriction code (ADR)	D

- Transport by sea

Special provisions (IMDG)	63, 190, 277, 327, 344, 959
Limited quantities (IMDG)	SP277
Packing instructions (IMDG)	P207, LP02
EmS-No. (Fire)	F-D
EmS-No. (Spillage)	S-U
Stowage category (IMDG)	None

CF-AS CJP; CF ISO 765; CF ISO 500+; CF-I ECO +; CS-F JS; CF 812 CC; CF-F ECO; CF-I 50 ECO GV;CF 125-50; CF 125-5W50; CF 126-N; CF 126; CF ISO 750; CF-I 750 B2 (-SV);CF 116-45; CF F 600; CF 116; CF-JI; CF 812; CF 812 WD; CF-I 65 ECO; CF-I XTW WD

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Stowage and segregation (IMDG)	Protected from sources of heat For AEROSOLS with a maximum capacity of 1 litre: Category A. Segregation as for class 9 but 'Separated from' class 1 except division 1.4. For AEROSOLS with a capacity above 1 litre: Category B. Segregation as for the appropriate sub-division of class 2. For WASTE AEROSOLS: Category C. Clear of living quarters. Segregation as for the appropriate sub-division of class 2.
MFAG-No	126
- Air transport	
PCA packing instructions (IATA)	203
PCA max net quantity (IATA)	75kg
Special provisions (IATA)	A145, A167, A802
- Inland waterway transport	
Classification code (ADN)	5F
Special provisions (ADN)	19, 327, 344, 625
Limited quantities (ADN)	1 L
Excepted quantities (ADN)	E0
Equipment required (ADN)	PP, EX, A
Ventilation (ADN)	VE01, VE04
Number of blue cones/lights (ADN)	1
Carriage prohibited (ADN)	No
Not subject to ADN	No
- Rail transport	
Special provisions (RID)	190, 327, 344, 625
Limited quantities (RID)	1L
Packing instructions (RID)	P207, LP02
Carriage prohibited (RID)	No

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

15.1. US Federal regulations

No additional information available

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol 1 H222;H229
 Acute Tox. 4 (Inhalation) H332
 Skin Irrit. 2 H315

CF-AS CJP; CF ISO 765; CF ISO 500+; CF-I ECO +; CS-F JS; CF 812 CC; CF-F ECO; CF-I 50 ECO GV;CF 125-50; CF 125-5W50; CF 126-N; CF 126; CF ISO 750; CF-I 750 B2 (-SV);CF 116-45; CF F 600; CF 116; CF-JI; CF 812; CF 812 WD; CF-I 65 ECO; CF-I XTW WD

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Eye Irrit. 2	H319
Resp. Sens. 1	H334
Skin Sens. 1	H317
Carc. 2	H351
STOT SE 3	H335
STOT RE 2	H373

Full text of hazard classes and H-statements : see section 16

National regulations

No additional information available

15.3. US State regulations

No additional information available

SECTION 16: Other information

Revision date 09/02/2016

Full text of H-statements:

H220	Extremely flammable gas
H222	Extremely flammable aerosol
H280	Contains gas under pressure; may explode if heated
H302	Harmful if swallowed
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335	May cause respiratory irritation
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure

SDS_US_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product