

GHS

Printing date: September 15, 2014

Revision: September 15, 2014

SECTION 1: Identification of the substance/mixture and of the company/ undertaking
· 1.1 Product identifier
· Trade name: <u>Stinger® Rubber Ball Grenade - OC</u>
<ul> <li>Article number: 1089</li> <li>1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.</li> </ul>
<ul> <li>Application of the substance / the mixture Explosive product.</li> </ul>
<ul> <li>1.3 Details of the supplier of the Safety Data Sheet</li> <li>Manufacturer/Supplier: Safariland, LLC</li> <li>13386 International Parkway</li> <li>Jacksonville, FL 32218</li> <li>Customer Care (800) 347-1200</li> <li>Further information obtainable from: Customer Care Department</li> </ul>
• <b>1.4 Emergency telephone number:</b> ChemTel Inc. (800)255-3924, +1 (813)248-0585
SECTION 2: Hazards identification
<ul> <li>• 2.1 Classification of the substance or mixture</li> <li>• Classification according to Regulation (EC) No 1272/2008         The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H412.     </li> <li>• exploding bomb</li> </ul>
Expl. 1.4 H204 Fire or projection hazard.
STOT SE 3 H335 May cause respiratory irritation.
Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.
Classification according to Directive 67/548/EEC or Directive 1999/45/EC     Xi; Irritant     R37: Irritating to respiratory system.
R5-44-52/53: Heating may cause an explosion. Risk of explosion if heated under confinement. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
• Information concerning particular hazards for human and environment: The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version. (Contd. on page 2)

(Contd. of page 1)

# Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and

GHS

Printing date: September 15, 2014

Revision: September 15, 2014

### Trade name: Stinger® Rubber Ball Grenade - OC with Safety Clip

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

#### · 2.2 Label elements

#### - Labelling according to Regulation (EC) No 1272/2008

- The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms



#### · Signal word Warning

#### Hazard statements

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H412.

H204 Fire or projection hazard.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

## Precautionary statements

The following Precautionary Statements are applicable only to the general GHS regulations and not the specific CLP regulation: P374.

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P250 Do not subject to grinding/shock/friction.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P373 DO NOT fight fire when fire reaches explosives.
- P374 Fight fire with normal precautions from a reasonable distance.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P372 Explosion risk in case of fire.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

#### · Additional information:

Can become highly flammable in use.

· Hazard description:

#### · WHMIS-symbols:

D2B - Toxic material causing other toxic effects

F - Dangerously reactive material



(Contd. on page 3)

Printing date: September 15, 2014

Revision: September 15, 2014

Trade name: Stinger® Rubber Ball Grenade - OC with Safety Clip (Contd. of page 2) · NFPA ratings (scale 0 - 4) Health = 1Fire = 0Reactivity = 3 · HMIS-ratings (scale 0 - 4) Health = 1 HEALTH FIRE Fire = 0 REACTIVITY 3 Reactivity = 3 Warning: Contains lead salt(s). Long-term health hazard. · HMIS Long Term Health Hazard Substances 7778-74-7 potassium perchlorate 2.3 Other hazards Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable. Explosive Product Notice PREVENTION OF ACCIDENTS IN THE USE OF EXPLOSIVES - The prevention of accidents in the use of explosives is a result of careful planning and observance of the best known practices. The explosives user must remember that he is dealing with a powerful force and that various devices and methods have been developed to assist him in directing this force. He should realize that this force, if misdirected, may either kill or injure both him and his fellow workers. WARNING - All explosives are dangerous and must be carefully handled and used following approved safety procedures either by or under the direction of competent, experienced persons in accordance with all applicable federal, state, and local laws, regulations, or ordinances. If you have any questions or doubts as to how to use any explosive product, DO NOT USE IT before consulting with your supervisor, or the manufacturer, if you do not have a supervisor. If your supervisor has any questions or doubts, he should consult the manufacturer before use. SECTION 3: Composition/information on ingredients · 3.2 Mixtures · Description: Mixture of substances listed below with nonhazardous additions. Dangerous components: CAS: 1309-48-4 magnesium oxide 40-60% EINECS: 215-171-9 substance with a Community workplace exposure limit Index number: 025-199-09-0 20-40% CAS: 7778-74-7 potassium perchlorate EINECS: 231-912-9 🗙 Xn R22; 🔥 O R9 Index number: 017-008-00-5 🙆 Ox. Sol. 1, H271 🔿 Acute Tox. 4, H302 (Contd. on page 4)

Printing date: September 15, 2014

Revision: September 15, 2014

# Trade name: Stinger® Rubber Ball Grenade - OC with Safety Clip

CAS: 7429-90-5	aluminium powder (pyrophoric)	(Contd. of page 10-20
EINECS: 231-072-3	F R15-17	
	Pyr. Sol. 1, H250; Water-react. 2, H261	40.00
CAS: 7439-95-4 EINECS: 231-104-6	magnesium powder (pyrophoric) A F R15-17	10-209
	Orrest View Pyr. Sol. 1, H250; Water-react. 1, H260	
CAS: 7757-79-1	potassium nitrate	5-10%
EINECS: 231-818-8	O R8	
	Ox. Sol. 2, H272	
CAS: 112945-52-5	Silicon Dioxide (Amorphous)	1-5%
CAS: 7440-50-8 EINECS: 231-159-6	copper substance with a Community workplace exposure limit	1-5%
CAS: 7440-66-6	zinc metal	0,5-29
	N R50/53	
CAS: 0004 24 C	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
CAS: 9004-34-6 EINECS: 232-674-9	substance with a Community workplace exposure limit	0,5-29
CAS: 8023-77-6		< 1,09
EINECS: 288-920-0	Xn R21/22; Xi R36/38	
CAS: 3811-04-9	Skin Irrit. 2, H315; Eye Irrit. 2, H319 potassium chlorate	. 1. 00
EINECS: 223-289-7	Xn R20/22; A O R9; B N R51/53	< 1,0%
Index number: 017-004-00-3	() Ox. Sol. 1, H271	
	Aquatic Chronic 2, H411	
	Acute Tox. 4, H302; Acute Tox. 4, H332	
CAS: 7704-34-9	sulfur	< 1,0%
EINECS: 231-722-6	Xi R38	
Index number: 016-094-00-1	V	1.00
CAS: 592-87-0 EINECS: 209-774-6	lead dithiocyanate 😡 T Repr. Cat. 1, 3 R61; 🗙 Xn R62-20/22; 🎇 N R50/53	< 1,0%
Index number: 082-001-00-6	R33	
	🚸 Repr. 1A, H360Df; STOT RE 2, H373	
	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
	Acute Tox. 4, H302; Acute Tox. 4, H332	
	the wording of the listed risk phrases refer to section 16.	
Notable Trace Components	s (≤ 0,1% w/w)	
CAS: 7758-97-6	lead chromate	
EINECS: 231-846-0 Index number: 082-004-00-2	I Carc. Cat. 2, Repr. Cat. 1, 3 R45-61; I Xn R62; I N R R33	30/53
	& Carc. 1B, H350; Repr. 1A, H360Df; STOT RE 2, H373	
	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
	· ·	(Contd. on page

(Contd. of page 4)

# Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Printing date: September 15, 2014

Revision: September 15, 2014

#### Trade name: Stinger® Rubber Ball Grenade - OC with Safety Clip

CAS: 10294-40-3 EINECS: 233-660-5 Index number: 056-002-00-7

barium chromate Xn R20/22

🚯 Acute Tox. 4, H302; Acute Tox. 4, H332

# **SECTION 4: First aid measures**

· 4.1 Description of first aid measures · General information: Immediately remove any clothing soiled by the product. Take affected persons out into the fresh air. · After inhalation: Remove victim to fresh air. Seek medical help for symptoms or if unconscious. · After skin contact: Brush off loose particles from skin. If skin irritation continues, consult a doctor. · After eye contact: Remove contact lenses if worn. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. · After swallowing: Rinse out mouth and then drink plenty of water. Do not induce vomiting; call for medical help immediately. · 4.2 Most important symptoms and effects, both acute and delayed Blast injury if mishandled. May cause respiratory irritation. **Breathing difficulty** Coughing Irritant to eyes. · Hazards Danger of blast or crush-type injuries. Danger of impaired breathing. 4.3 Indication of any immediate medical attention and special treatment needed Product may produce physical injury if mishandled. Treatment of these injuries should be based on the blast and compression effects. If necessary oxygen respiration treatment.

# **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Flood area with water. If no water is available, carbon dioxide, dry chemical or earth may be used. If the fire reaches the cargo, withdraw and let fire burn.

- · For safety reasons unsuitable extinguishing agents: None.
- **5.2 Special hazards arising from the substance or mixture** During heating or in case of fire poisonous gases are produced.

nous gases are produced.

(Contd. on page 6)

GHS

Printing date: September 15, 2014

Revision: September 15, 2014

#### Trade name: Stinger® Rubber Ball Grenade - OC with Safety Clip

(Contd. of page 5) Product may explode if burned in confined space. Individual cartridges may explode. Mass explosion of many cartridges at once is unlikely.

- 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information

Cool endangered receptacles with water spray.

Evacuate area and fight fire from from the upwind side.

In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion. Eliminate all ignition sources if safe to do so.

Flammability Classification: (defined by 29 CFR 1910.1200) Explosive. Can explode under fire conditions. Individual devices will randomly explode. Will not mass explode if multiple devices are involved. Burning material may produce toxic and irritating vapors. In unusual cases, shrapnel may be thrown from exploding devices under containment. See 2008 Emergency response Guidebook for further information.

# **SECTION 6: Accidental release measures**

· 6.1 Personal precautions, protective equipment and emergency procedures

FOR ALL TRANSPORTATION ACCIDENTS, CALL CHEMTEL AT 1-800-255-3924. Spills of this material should be handled carefully. Do not subject materials to mechanical shock or extreme heat. A spill of this material will normally not require emergency response team capabilities. Use respiratory protective device against the effects of fumes/dust/aerosol. Wear protective equipment. Keep unprotected persons away. Remove persons from danger area. Ensure adequate ventilation Protect from heat. Isolate area and prevent access. · 6.2 Environmental precautions: No special measures required. · 6.3 Methods and material for containment and cleaning up: Pick up mechanically. Dispose contaminated material as waste according to item 13. Send for recovery or disposal in suitable receptacles. Clean the affected area carefully; suitable cleaners are: Warm water and cleansing agent · 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# **SECTION 7: Handling and storage**

- 7.1 Precautions for safe handling Handle with care. Avoid jolting, friction and impact. Use only in well ventilated areas.
- Information about fire and explosion protection: Protect from heat.

(Contd. on page 7)

GHS

Printing date: September 15, 2014

Trade name: Stinger® Rubber Ball Grenade - OC with Safety Clip

Keep respiratory protective device available. Emergency cooling must be available in case of nearby fire.

## · 7.2 Conditions for safe storage, including any incompatibilities · Storage:

· Requirements to be met by storerooms and receptacles: Avoid storage near extreme heat, ignition sources or open flame.

· Information about storage in one common storage facility: Store away from foodstuffs. Store away from flammable substances.

• Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.

• 7.3 Specific end use(s) No further relevant information available.

# SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

# 

<ul> <li>8.1 Control p</li> </ul>	parameters
· Ingredients v	with limit values that require monitoring at the workplace:
1309-48-4 ma	agnesium oxide
PEL (USA)	Long-term value: 15* mg/m <sup>3</sup> fume; *total particulate
TLV (USA)	Long-term value: 10* mg/m³ *as inhalable fraction
EL (Canada)	Short-term value: 10** mg/m³ Long-term value: 10* 3** mg/m³ *inhalable fume;**respirable dust and fume
EV (Canada)	Long-term value: 10 mg/m <sup>3</sup> inhalable
7429-90-5 alu	uminium powder (pyrophoric)
PEL (USA)	Long-term value: 15*; 15** mg/m <sup>3</sup> *Total dust; ** Respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m³ as Al*Total dust**Respirable/pyro powd./welding f.
TLV (USA)	Long-term value: 1* mg/m <sup>3</sup> as Al; *as respirable fraction
EL (Canada)	Long-term value: 1,0 mg/m <sup>3</sup> respirable, as Al
EV (Canada)	Long-term value: 5 mg/m³ aluminium-containing (as aluminium)
7440-50-8 со	pper
PEL (USA)	Long-term value: 1* 0,1** mg/m <sup>3</sup> as Cu *dusts and mists **fume
	(Contd. on page 8)

(Contd. of page 6)

Revision: September 15, 2014

Printing date: September 15, 2014

Revision: September 15, 2014

# Trade name: Stinger® Rubber Ball Grenade - OC with Safety Clip

	(Contd. of page 7)
REL (USA)	Long-term value: 1* 0,1** mg/m³ as Cu *dusts and mists **fume
TLV (USA)	Long-term value: 1* 0,2** mg/m <sup>3</sup>
TLV (USA)	*dusts and mists; **fume; as Cu
EL (Canada)	Long-term value: 1* 0,2** mg/m <sup>3</sup>
(********	*dusts and mists; **fume, as Cu
EV (Canada)	Long-term value: 0,2* 1** mg/m <sup>3</sup> as copper, *fume;**dust and mists
9004-34-6 Ce	llulose
PEL (USA)	Long-term value: 15* 5** mg/m <sup>3</sup> *total dust **respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m <sup>3</sup> *total dust **respirable fraction
TLV (USA)	Long-term value: 10 mg/m <sup>3</sup>
EL (Canada)	Long-term value: 10* 3** mg/m <sup>3</sup>
	*total dust, **respirable fraction
EV (Canada)	Long-term value: 10 mg/m <sup>3</sup> paper fibre, total dust
592-87-0 lead	d dithiocyanate
PEL (USA)	Long-term value: 5 mg/m <sup>3</sup> as CN; Skin
EV (Canada)	Long-term value: 0,05 mg/m³ as Pb, Skin (organic compounds)
	rther relevant information available. Irther relevant information available.
<ul> <li>Additional in</li> </ul>	formation: The lists valid during the making were used as basis.
· 8.2 Exposure	econtrols
	otective equipment:
	ective and hygienic measures:
	ecautionary measures are to be adhered to when handling chemicals. dust / smoke / mist.
	om foodstuffs, beverages and feed.
	before breaks and at the end of work.
<ul> <li>Respiratory</li> </ul>	
	e pressure NIOSH or European EN149 vapor respirators when deploying product in large
quantities.	respiratory protective device when high concentrations are present.
· Protection of	
Prote	ective gloves
Wear gloves	when handling deployed rounds.
	aterial has to be impermeable and resistant to the product/ the substance/ the preparation. (Contd. on page 9)

GHS

Printing date: September 15, 2014

Revision: September 15, 2014

### Trade name: Stinger® Rubber Ball Grenade - OC with Safety Clip

(Contd. of page 8)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

#### · Eye protection:



Safety glasses

- · Body protection: Protective work clothing
- Limitation and supervision of exposure into the environment No further relevant information available.
- Risk management measures

See Section 7 for additional information.

Organizational measures should be in place for all activities involving this product.

No further relevant information available.

# **SECTION 9: Physical and chemical properties**

- · 9.1 Information on basic physical and chemical properties
- General Information
- · Appearance:
- Form: Solid metal container containing liquid and solid contents. Colour: According to product specification · Odour: Odourless · Odour threshold: Not determined. · pH-value: Not applicable. · Change in condition Melting point/Melting range: Not Determined. Boiling point/Boiling range: Undetermined. · Flash point: Not applicable. · Flammability (solid, gaseous): Not determined. Auto/Self-ignition temperature: Not determined. · Decomposition temperature: Not determined. · Self-igniting: Product is not self-igniting. · Danger of explosion: Heating may cause an explosion.

(Contd. on page 10)

Printing date: September 15, 2014

#### Revision: September 15, 2014

## Trade name: Stinger® Rubber Ball Grenade - OC with Safety Clip

		(Contd. of page
Explosion limits:	Not determined.	
Upper:	Not determined.	
Vapour pressure:	Not applicable.	
Density:	Not determined.	
Relative density	Not determined.	
· Vapour density	Not applicable.	
<ul> <li>Evaporation rate</li> </ul>	Not applicable.	
Solubility in / Miscibility with		
water:	Insoluble.	
Partition coefficient (n-octan	ol/water): Not determined.	
· Viscosity:		
Dynamic:	Not applicable.	
Kinematic:	Not applicable.	
9.2 Other information	No further relevant information available.	

# · 10.1 Reactivity

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

**SECTION 10: Stability and reactivity** 

No decomposition if used and stored according to specifications.

#### 10.3 Possibility of hazardous reactions

Danger of explosion.

Toxic fumes may be released if heated above the decomposition point.

Contact with acids releases toxic gases.

Acts as an oxidizing agent on organic materials such as wood, paper and fats. Reacts with strong alkali.

- 10.4 Conditions to avoid Sources of ignition, open flame, incompatible materials.
- **10.5 Incompatible materials:** No further relevant information available.
- 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide Nitrogen oxides Sulphur oxides (SOx)

# **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- · on the skin:

Not a skin irritant in unused form. Vapors/particles from used product are possibly irritating to skin.

(Contd. on page 11)

Printing date: September 15, 2014

Revision: September 15, 2014

### Trade name: Stinger® Rubber Ball Grenade - OC with Safety Clip

(Contd. of page 10)

· on the eye:

Not an eye irritant in unused form. Vapors/particles from delpoyed product are a serious eye irritant.

• Sensitization: Sensitizing effect by skin contact is possible by prolonged exposure.

Additional toxicological information:

Normal handling of the undeployed product poses little or no health hazards, One should avoid inhalation by wearing appropriate respiratory protection when exposed to the chemical ingredients of the product above listed TLV's or when exposed to the post ignition by-products. This product is a cansister which contains the various components completely sealed within. Therefore, under normal handling of this product, no exposure to any harmful materials will occur. When the product is used, particles may be generated which may be irritating to the eyes and the respiratory tract.

## · Acute effects (acute toxicity, irritation and corrosivity):

Inhalation may cause irritation to the respiratory system.

# **SECTION 12: Ecological information**

#### · 12.1 Toxicity

· Aquatic toxicity: The product contains materials that are harmful to the environment.

- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential May be accumulated in organism
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

The product contains heavy metals. Avoid transfer into the environment. Specific preliminary treatments are necessary

Harmful to aquatic organisms

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

## • 12.5 Results of PBT and vPvB assessment

- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

# **SECTION 13: Disposal considerations**

## · 13.1 Waste treatment methods

#### Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. After prior treatment product has to be disposed of in an incinerator for hazardous waste adhering to the regulations pertaining to the disposal of particularly hazardous waste.

(Contd. on page 12)

Printing date: September 15, 2014

Revision: September 15, 2014


Trade name: Stinger® Rubber Ball Grenade - OC with Safety Clip

(Contd. of page 11)

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.



(Contd. of page 12)

# Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Printing date: September 15, 2014

Revision: September 15, 2014

# Trade name: Stinger® Rubber Ball Grenade - OC with Safety Clip

· Special marking (IATA):



Cargo Aircraft Only.

· 14.6 Special precautions for user

- EMS Number:
- · 14.7 Transport in bulk according to Annex II of
- MARPOL73/78 and the IBC Code
- · UN "Model Regulation":

Not applicable. <u>F-A</u>,S-Q of Not applicable. UN0301, Ammunition Tear-producing with burster, expelling charge or propelling charge, 1.4G (6.1+8), II

# **SECTION 15: Regulatory information**

<ul> <li>15.1 Safety, health and environmental regulations/legislation spec</li> <li>United States (USA)</li> <li>SARA</li> </ul>	
<ul> <li>Section 355 (extremely hazardous substances):</li> </ul>	
None of the ingredients is listed.	
· Section 313 (Specific toxic chemical listings):	
7429-90-5 aluminium powder (pyrophoric)	
7757-79-1 potassium nitrate	
7440-50-8 copper	
7440-66-6 zinc metal	
· TSCA (Toxic Substances Control Act):	
All ingredients are listed.	
· Proposition 65 (California):	
· Chemicals known to cause cancer:	
592-87-0 lead dithiocyanate	
10294-40-3 barium chromate	
7758-97-6 lead chromate	
• Chemicals known to cause reproductive toxicity for females:	
Present in trace quantities.	
10294-40-3 barium chromate	
7758-97-6 lead chromate	
Chemicals known to cause reproductive toxicity for males: Present in trace quantities.	
10294-40-3 barium chromate	
7758-97-6 lead chromate	
Chemicals known to cause developmental toxicity:     Present in trace quantities.	
10294-40-3 barium chromate	
	(Contd. on page 1

Printing date: September 15, 2014

Revision: September 15, 2014

## Trade name: Stinger® Rubber Ball Grenade - OC with Safety Clip

7750.07	(Contd. c	f page
	6 lead chromate	
•	enic Categories	
•	ronmental Protection Agency)	
	potassium perchlorate	NL
7440-50-8		D
	zinc metal	D, I,
•	rnational Agency for Research on Cancer)	
	e ingredients is listed.	
•	shold Limit Value established by ACGIH)	
	magnesium oxide	A
7429-90-5	aluminium powder (pyrophoric)	A
· NIOSH-Ca	(National Institute for Occupational Safety and Health)	
None of th	e ingredients is listed.	
· Canada		
<ul> <li>Canadian</li> </ul>	Domestic Substances List (DSL)	
All ingredie	ents are listed.	
· Canadian	Ingredient Disclosure list (limit 0.1%)	
None of th	e ingredients is listed.	
· Canadian	Ingredient Disclosure list (limit 1%)	
1309-48-4	magnesium oxide	
	aluminium powder (pyrophoric)	
7440-50-8	copper	
· Other reg	ulations, limitations and prohibitive regulations	
This produ	ict has been classified in accordance with hazard criteria of the Controlled Products Reg DS contains all the information required by the Controlled Products Regulations.	ulatio
	es of very high concern (SVHC) according to REACH, Article 57	
NI (1	e ingredients is listed.	

# **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

## · Relevant phrases

H250 Catches fire spontaneously if exposed to air.

- H260 In contact with water releases flammable gases which may ignite spontaneously.
- H261 In contact with water releases flammable gases.
- H271 May cause fire or explosion; strong oxidiser.
- H272 May intensify fire; oxidiser.
- H302 Harmful if swallowed.
- H315 Causes skin irritation.

(Contd. on page 15)

GHS

Printing date: September 15, 2014

Trade name: Stinger® Rubber Ball Grenade - OC with Safety Clip

Revision: September 15, 2014

#### (Contd. of page 14) H319 Causes serious eve irritation. H332 Harmful if inhaled. H360Df May damage the unborn child. Suspected of damaging fertility. H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. R15 Contact with water liberates extremely flammable gases. Spontaneously flammable in air. R17 R20/22 Harmful by inhalation and if swallowed. R21/22 Harmful in contact with skin and if swallowed. R22 Harmful if swallowed. R33 Danger of cumulative effects. R36/38 Irritating to eyes and skin. R38 Irritating to skin. R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R61 May cause harm to the unborn child. R62 Possible risk of impaired fertility. R8 Contact with combustible material may cause fire. R9 Explosive when mixed with combustible material. Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association GHS: Globally Harmonized System of Classification and Labelling of Chemicals ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) WHMIS: Workplace Hazardous Materials Information System (Canada) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) Expl. 1.4: Explosives, Division 1.4 Pyr. Sol. 1: Pyorphoric Solids, Hazard Category 1 Water-react. 1: Substances and Mixtures which, in contact with water, emit flammable gases, Hazard Category 1 Water-react. 2: Substances and Mixtures which, in contact with water, emit flammable gases, Hazard Category 2 Ox. Sol. 1: Oxidising Solids, Hazard Category 1 Ox. Sol. 2: Oxidising Solids, Hazard Category 2 Acute Tox. 4: Acute toxicity, Hazard Category 4 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2 Repr. 1A: Reproductive toxicity, Hazard Category 1A STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2 Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2 (Contd. on page 16)

(Contd. of page 15)

# Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Printing date: September 15, 2014

Revision: September 15, 2014

# Trade name: Stinger® Rubber Ball Grenade - OC with Safety Clip

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3 • Sources SDS Prepared by: ChemTel Inc. 1305 North Florida Avenue Tampa, Florida USA 33602-2902 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573 Website: www.chemtelinc.com