

SAFETY DATA SHEET

Issuing Date 27-Oct 2014 Revision Date 17-Oct-2014 Revision Number 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product SDS Name Clear Epoxy Hardener - Syringe - Part B

J-B Weld FG SKU Part Numbers Covered

50112, 80112, 50112-F

J-B Weld Product Names Covered

ClearWeld™ (all)

J-B Weld Product Type

Epoxy

Recommended use of the chemical and restrictions on use

Recommended UseGeneral Purpose Adhesive

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name J-B WELD COMPANY,LLC

Supplier Address 1130 COMO ST

SULPHUR SPRINGS, TX 75482

USA

Emergency Telephone Numbers Transportation Emergencies: Chemtrec (24 hour transportation emergency response info):

800-424-9300 or 703-527-3887

Poison/Medical Emergencies: Poison Control Centers (24 hour emergency poison / medical

response info): 800-222-1222

Supplier Email <u>info@jbweld.com</u>

Supplier Phone Number 903-885-7696

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)



Page 1/12

Skin corrosion/irritation	Category 1B
Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1

GHS Label elements, including precautionary statements

Emergency Overview

Signal word Warning

Hazard Statements

Causes severe skin irritation

May cause serious eye damage / eye irritation

May cause an allergic skin reaction



Appearance Pale yellow

Physical State Gel Liquid

Odor Ammoniacal

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Use only outdoors or in a well-ventilated area

Do not breathe dust/fume/gas/mist/vapors/spray

Contaminated work clothing should not be allowed out of the workplace

Wear protective gloves

Precautionary Statements - Response

Immediately call a POISON CENTER or doctor/physician

Specific treatment (see supplemental first aid instructions on this label)

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTER or doctor/physician

Skin

Call a POISON CENTER or doctor/physician if you feel unwell

Wash contaminated clothing before reuse

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

If skin irritation or rash occurs: Get medical advice/attention

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Call a POISON CENTER or doctor/physician if you feel unwell



Page 2/12

Ingestion

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

Rinse mouth

Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

75% of the mixture consists of ingredient(s) of unknown toxicity

Other information

Harmful to aquatic life with long lasting effects

Repeated or prolonged skin contact may cause allergic reactions with susceptible persons

Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
2,4,6-Tri(dimethylaminomethyl)phenol	90-72-2	7 - 13
1-(2-Aminoethyl) piperazine	140-31-8	<5%
Benzyl alcohol	100-51-6	3 - 5
Ethylbenzene	100-41-4	<1%

4. FIRST AID MEASURES

First aid measures

General Advice

Immediate medical attention is required. Show this safety data sheet to the doctor

in attendance.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Keep eye wide open while rinsing. Do not rub affected area. Seek immediate medical attention/advice. Remove contact lenses, if present and easy

to do. Continue rinsing.

Skin Contact Immediate medical attention is required. Wash off immediately with soap and

plenty of water while removing all contaminated clothes and shoes. May cause

an allergic skin reaction.

InhalationRemove to fresh air. Get medical attention immediately if symptoms occur. If

breathing is difficult, (trained personnel should) give oxygen. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct

contact with skin. Use barrier to give mouth-to-mouth resuscitation.



Page 3/12

Ingestion

Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

Self-protection of the first aider Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. Wear personal protective clothing (see section 8). Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Effects

Most Important Symptoms and Burning sensation. Coughing and/ or wheezing. Difficulty in breathing. Itching. Rashes. Hives.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure. May cause sensitization of susceptible persons.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical

The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors. Product is or contains a sensitizer. May cause sensitization by skin contact.

Uniform Fire Code Combustible Liquid: III-B

Sensitizer: Liquid

Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact No. Sensitivity

to Static Discharge No.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.



6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Attention! Corrosive material. Avoid contact with skin, eyes or clothing. Ensure adequate

ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Avoid breathing vapors or mists.

Avoid generation of dust.

Refer to protective measures listed in Sections 7 and 8.

Other Information

Environmental Precautions

Environmental Precautions

Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Should not be released into the environment. Do not allow to

enter into soil/subsoil. Prevent product from entering drains.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Avoid breathing vapors or mists. Use only with adequate ventilation and in closed systems. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from

moisture. Store locked up. Keep out of the reach of children. Store away from other

materials.

Incompatible Products Acids. Bases. Oxidizing agent.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m³ STEL: 125 ppm STEL: 545 mg/m³

Other Exposure Guidelines See section 15 for national exposure control parameters

Appropriate engineering controls

Engineering Measures Showers

Eyewash stations



Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection Tight sealing safety goggles. Face protection shield.

Skin and Body Protection

Wear protective gloves and protective clothing. Long sleeved clothing. Chemical resistant

apron. Impervious gloves.

Respiratory Protection

No protective equipment is needed under normal use conditions. If exposure limits are

exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. For environmental protection, remove and wash all contaminated protective equipment before re-use.

None known

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical State Gel Liquid
Appearance Pale yellow

AppearancePale yellowOdorAmmoniacalColorNo information availableOdor ThresholdNo information available

No information available Cool The Short

Property
pHValues
UNKNOWNRemarks/ Method
None knownMelting / freezing pointNo data availableNone known

Boiling point / boiling range100 °C / 212 °FNone knownFlash Point140 C / 284 FNone knownEvaporation RateNo data availableNone knownFlammability (solid, gas)No data availableNone known

Flammability Limit in Air
Upper flammability limit
Lower flammability limit
No data available

No data available None known Vapor pressure Vapor density No data available None known **Specific Gravity** No data available None known Water Solubility Miscible in water None known Solubility in other solvents No data available None known Partition coefficient: n-octanol/waterNo data available None known No data available Autoignition temperature None known **Decomposition temperature** No data available None known Kinematic viscosity No data available None known

Dynamic viscosity 400

Explosive properties No data available
Oxidizing Properties No data available

Other Information

Softening Point No data available

VOC Content (%) <1%

Particle Size No data available

Particle Size Distribution



10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Exposure to air or moisture over prolonged periods. Excessive heat.

Incompatible materials

Acids. Bases. Oxidizing agent.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. Corrosive by inhalation.

(based on components). Inhalation of corrosive fumes/gases may cause coughing, choking, headache, dizziness, and weakness for several hours. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure, and increased heart rate. Inhaled corrosive substances can lead to a toxic edema of the lungs. Pulmonary edema can be fatal. May cause irritation of respiratory tract.

Harmful by inhalation.

Eye Contact Specific test data for the substance or mixture is not available. Causes burns. (based on

components). Corrosive to the eyes and may cause severe damage including blindness.

Causes serious eye damage. May cause irreversible damage to eyes.

Skin Contact Specific test data for the substance or mixture is not available. Corrosive. (based on

components). Causes burns. May be absorbed through the skin in harmful amounts.

Harmful in contact with skin.

Ingestion Specific test data for the substance or mixture is not available. Causes burns. (based on

components). Ingestion causes burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the mouth. Swelling of the throat may cause shortness of breath and choking. May cause lung damage if swallowed. May be fatal if swallowed and enters airways. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea,

vomiting and diarrhea. May be harmful if swallowed.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
---------------	-----------	-------------	-----------------



Page 7/12

2,4,6- Tri(dimethylaminomethyl)phen ol 90-72-2	= 1000 mg/kg (Rat)	= 1280 mg/kg(Rat)	-
1-(2-Aminoethyl) piperazine 140-31-8	= 2140 mg/kg(Rat)	= 880 μL/kg(Rabbit)	-
Benzyl alcohol 100- 51-6	= 1230 mg/kg(Rat)	= 2 g/kg(Rabbit)	= 8.8 mg/L (Rat)4 h
Ethylbenzene 100- 41-4	= 3500 mg/kg (Rat)	= 15354 mg/kg(Rabbit)	= 17.2 mg/L (Rat)4 h

Information on toxicological effects

Symptoms Erythema (skin redness). Burning. May cause blindness. Coughing and/ or wheezing.

Itching. Rashes. Hives.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization May cause sensitization of susceptible persons. May cause sensitization by skin

contact. May cause sensitization by inhalation.

Mutagenic Effects No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Ethylbenzene 100- 41-4	А3	Group 2B		Х

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive Toxicity No information available.

STOT - single exposureNo information available.

STOT - repeated exposureNo information available.

Chronic Toxicity

Chronic exposure to corrosive fumes/gases may cause erosion of the teeth followed by jaw necrosis. Bronchial irritation with chronic cough and frequent attacks of pneumonia are common. Gastrointestinal disturbances may also be seen. Contains a known or

suspected carcinogen.

Target Organ Effects

Respiratory system. Eyes. Skin. Gastrointestinal tract (GI). Central Nervous System (CNS).

Aspiration Hazard No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)

728.00 mg/kg

ATEmix (dermal)

1,140.00 mg/kg (ATE)

ATEmix (inhalation-gas)

18,750.00 ppm (4 hr)

ATEmix (inhalation-dust/mist)

6.20 mg/l

ATEmix (inhalation-vapor)

46.00 ATEmix



12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
1-(2-Aminoethyl) piperazine 140-31-8	72h EC50: = 495 mg/L (Pseudokirchneriella subcapitata)	96h LC50: > 1000 mg/L (Poecilia reticulata) 96h LC50: >= 100 mg/L (Oncorhynchus mykiss) 96h LC50: 1950 - 2460 mg/L (Pimephales promelas)	EC50 > 10000 mg/L 17 h	48h EC50: = 32 mg/L
Benzyl alcohol 100- 51-6	3h EC50: = 35 mg/L (Anabaena variabilis)	96h LC50: = 10 mg/L (Lepomis macrochirus) 96h LC50: = 460 mg/L (Pimephales promelas)	EC50 = 50 mg/L 5 min EC50 = 63.7 mg/L 15 min EC50 = 63.7 mg/L 5 min EC50 = 71.4 mg/L 30 min	48h EC50: = 23 mg/L
Ethylbenzene 100- 41-4	72h EC50: = 4.6 mg/L (Pseudokirchneriella subcapitata) 96h EC50: > 438 mg/L (Pseudokirchneriella subcapitata) 72h EC50: 2.6 - 11.3 mg/L (Pseudokirchneriella subcapitata) 96h EC50: 1.7 - 7.6 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 11.0 - 18.0 mg/L (Oncorhynchus mykiss) 96h LC50: = 4.2 mg/L (Oncorhynchus mykiss) 96h LC50: 7.55 - 11 mg/L (Pimephales promelas) 96h LC50: = 32 mg/L (Lepomis macrochirus) 96h LC50: 9.1 - 15.6 mg/L (Pimephales promelas) 96h LC50: = 9.6 mg/L (Poecilia reticulata)	S	48h EC50: 1.8 - 2.4 mg/L

Persistence and Degradability

No information available.

Bioaccumulation

No information available

Chemical Name	Log Pow
1-(2-Aminoethyl) piperazine 140- 31-8	-1.48
Benzyl alcohol 100- 51-6	1.1
Ethylbenzene 100- 41-4	3.118

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

Contaminated Packaging

Dispose of contents/containers in accordance with local regulations.

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Ethylbenzene 100-		Included in waste stream:		
41-4		F039		



California Hazardous Waste Codes 331

Chemical Name	California Hazardous Waste
Ethylbenzene	Toxic
100-41-4	Ignitable

14. TRANSPORT INFORMATION

DOTNOT REGULATEDProper Shipping NameNON REGULATED

Hazard Class N/A

TDG Not regulated

MEX Not regulated

<u>ICAO</u> Not regulated

IATA Not regulated

Proper Shipping Name NON REGULATED

Hazard Class N/A

IMDG/IMO Not regulated

Hazard Class N/A

RID Not regulated

ADR Not regulated

ADN Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Complies

DSL All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Ethylbenzene - 100-41-4	100-41-4	1 - 5	0.1

SARA 311/312 Hazard Categories

Acute Health Hazard Yes
Chronic Health Hazard Yes
Fire Hazard No
Sudden release of pressure hazard No
Reactive Hazard No



CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Ethylbenzene 100- 41-4	1000 lb	X	Х	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Ethylbenzene 100- 41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Ethylbenzene - 100-41-4	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
1-(2-Aminoethyl) piperazine 140- 31-8	X	X	Х		
Benzyl alcohol 100- 51-6		X	X		
Ethylbenzene 100- 41-4	Х	Х	Х	Х	Х

International Regulations

Mexico National occupational exposure limits

Component	Carcinogen Status	Exposure Limits
Ethylbenzene		Mexico: TWA 100 ppm
100-41-4 (1 - 5)		Mexico: TWA 435 mg/m ³
		Mexico: STEL 125 ppm
		Mexico: STEL 545 mg/m ³

Mexico - Occupational Exposure Limits - Carcinogens

Canada

WHMIS Hazard Class

D2A - Very toxic materials D2B - Toxic materials





16. OTHER INFORMATION

NFPA Health Hazards 3 Flammability 1 Instability 0 Physical and

HMIS Health Hazards 3 * Flammability 1 Physical Hazard 0 Personal Protection

Χ

Chronic Hazard Star Legend * = Chronic Health Hazard

Prepared By J-B Weld Company

Revision Date 17-Oct-2014

Revision Note No information available

Notice to reader

NON-WARRANTY: The information presented in this publication is based upon the research and experience of J-B Weld Company. No representation or warranty is made, however, concerning the accuracy or completeness of the information presented in this publication. J-B Weld Company makes no warranty or representation of any kind, express or implied, including without limitation any warranty of merchantability or fitness for any particular purpose, and no warranty or representation shall be implied by law or otherwise. Any products sold by J-B Weld Company are not warranted as suitable for any particular purpose to the buyer. The suitability of any products for any purpose particular to the buyers is for the buyer to determine. J-B Weld Company assumed no responsibility for the selection of products suitable to the particular purposes of any particular buyer. J-B Weld Company shall in no event be liable for any special, incidental, or consequential damages.

End of Safety Data Sheet



