according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date July 23, 2015 Revision: July 23, 2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Direct Impact® 40mm Round OC
- · Article number: 6320
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Crowd Control Device
- · Uses advised against Contact manufacturer.
- · 1.3 Details of the supplier of the Safety Data Sheet
- Manufacturer/Supplier:

Safariland, LLC

13386 International Parkway

Jacksonville, FL 32218

Customer Care (800) 347-1200

- Further information obtainable from: Customer Care Department
- · 1.4 Emergency telephone number:

ChemTel Inc.

(800)255-3924, +1 (813)248-0585

Poison Control Centres:

In the United Kingdom: 844 892 0111

In Australia: 131126

In New Zealand: +0800 764 766

TM

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Classifications listed are applicable to the OSHA GHS Hazard Communication Standard (29CFR1910.1200).



exploding bomb

Expl. 1.4 H204 Fire or projection hazard.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

· Additional information:

There are no other hazards not otherwise classified that have been identified.

0 % of the mixture consists of component(s) of unknown toxicity.

(Cont'd. on page 2)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date July 23, 2015 Revision: July 23, 2015

Trade name: Direct Impact® 40mm Round - OC

(Cont'd. from page 1)

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is additionally classified and labelled according to the Globally Harmonized System within the United States (GHS).

The product is classified and labelled according to the CLP regulation.

Hazard pictograms





GHS01 GHS07

· Signal word Warning

· Hazard-determining components of labelling:

Nitrocellulose, colloided, granular

Oleoresin Capsicum

· Hazard statements

H204 Fire or projection hazard.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

Precautionary statements

The following Precautionary Statements are applicable only to the general GHS regulations and not the specific CLP regulation: P374.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P250 Do not subject to grinding/shock/friction.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P373 DO NOT fight fire when fire reaches explosives.

P374 Fight fire with normal precautions from a reasonable distance.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P372 Explosion risk in case of fire.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

Can become highly flammable in use.

· NFPA ratings (scale 0 - 4)



Health = 1 Fire = 3 Reactivity = 3

HMIS-ratings (scale 0 - 4)

Warning: Contains lead salt(s). Long-term health hazard.

(Cont'd. on page 3)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date July 23, 2015 Revision: July 23, 2015

Trade name: Direct Impact® 40mm Round - OC

(Cont'd. from page 2)



HMIS Long Term Health Hazard Substances 122-39-4 diphenylamine 15245-44-0 lead 2,4,6-trinitro-m-phenylene dioxide

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- **Explosive Product Notice**

PREVENTION OF ACCIDENTS IN THE USE OF EXPLOSIVES - The prevention of accidents in the use of explosives is a result of careful planning and observance of the best known practices. The explosives user must remember that he is dealing with a powerful force and that various devices and methods have been developed to assist him in directing this force. He should realize that this force, if misdirected, may either kill or injure both him and his fellow workers.

WARNING - All explosives are dangerous and must be carefully handled and used following approved safety procedures either by or under the direction of competent, experienced persons in accordance with all applicable federal, state, and local laws, regulations, or ordinances. If you have any questions or doubts as to how to use any explosive product, DO NOT USE IT before consulting with your supervisor, or the manufacturer, if you do not have a supervisor. If your supervisor has any questions or doubts, he should consult the manufacturer before use.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · **Description**: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 1309-48-4 EINECS: 215-171-9 Index number: 025-199-09-0	magnesium oxide substance with a Community workplace exposure limit	60-80%
CAS: 112945-52-5	Silicon Dioxide (Amorphous)	5-10%
CAS: 7757-69-9 EINECS: 231-817-2	carbonic acid, magnesium salt	1-5%
CAS: 9004-70-0 EC number: 603-037-0	Nitrocellulose, colloided, granular Expl. 1.1, H201	1-5%
CAS: 8023-77-6 EINECS: 288-920-0	Oleoresin Capsicum Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Irrit. 2, H315	< 1,0%
CAS: 85-98-3 EINECS: 201-645-2	1,3-diethyldiphenylurea Acute Tox. 4, H302 Aquatic Chronic 3, H412	< 1,0%
	(Cont'd	on page 4)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date July 23, 2015 Revision: July 23, 2015

Trade name: Direct Impact® 40mm Round - OC

(Cont'd. from page 3)

· Additional information:

For the wording of the listed Hazard Statements refer to section 16.

For the listed ingredient(s), th	ne identity and exact percentages are being withheld as a trade secret.
Notable Trace Components	s (≤ 0,1% w/w)
	lead 2,4,6-trinitro-m-phenylene dioxide Unst. Expl., H200 Carc. 1B, H350; Repr. 1A, H360Df; STOT RE 2, H373 Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Acute Tox. 4, H302; Acute Tox. 4, H332
CAS: 122-39-4 EINECS: 204-539-4 Index number: 612-026-00-5	diphenylamine Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331 STOT RE 2, H373 Aquatic Acute 1, H400; Aquatic Chronic 1, H410

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Take affected persons out into the fresh air.

· After inhalation:

Remove victim to fresh air.

Seek medical help for symptoms or if unconscious.

· After skin contact:

Brush off loose particles from skin.

If skin irritation continues, consult a doctor.

· After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

Blast injury if mishandled.

May cause respiratory irritation.

Coughing

Breathing difficulty

Slight irritant effect on skin and mucous membranes.

Irritant to eyes.

· Hazards

Danger of blast or crush-type injuries.

Danger of impaired breathing.

4.3 Indication of any immediate medical attention and special treatment needed

Product may produce physical injury if mishandled. Treatment of these injuries should be based on the blast and compression effects.

(Cont'd. on page 5)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date July 23, 2015 Revision: July 23, 2015

Trade name: Direct Impact® 40mm Round - OC

(Cont'd. from page 4)

If necessary oxygen respiration treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

Flood area with water. If no water is available, carbon dioxide, dry chemical or earth may be used. If the fire reaches the cargo, withdraw and let fire burn.

- · For safety reasons unsuitable extinguishing agents: None.
- · 5.2 Special hazards arising from the substance or mixture

Fire or projection hazard.

During heating or in case of fire poisonous gases are produced.

Product may explode if burned in confined space. Individual cartridges may explode. Mass explosion of many cartridges at once is unlikely.

- 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

· Additional information

Eliminate all ignition sources if safe to do so.

Cool endangered receptacles with water spray.

Evacuate area and fight fire from from the upwind side.

Flammability Classification: (defined by 29 CFR 1910.1200) Explosive. Can explode under fire conditions. Individual devices will randomly explode. Will not mass explode if multiple devices are involved. Burning material may produce toxic and irritating vapors. In unusual cases, shrapnel may be thrown from exploding devices under containment. See 2008 Emergency response Guidebook for further information.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

FOR ALL TRANSPORTATION ACCIDENTS, CALL CHEMTEL AT 1-800-255-3924. Spills of this material should be handled carefully. Do not subject materials to mechanical shock or extreme heat. A spill of this material will normally not require emergency response team capabilities.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

Remove persons from danger area.

Ensure adequate ventilation

Protect from heat.

Isolate area and prevent access.

· 6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Pick up mechanically.

Dispose contaminated material as waste according to section 13.

Send for recovery or disposal in suitable receptacles.

(Cont'd. on page 6)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date July 23, 2015 Revision: July 23, 2015

Trade name: Direct Impact® 40mm Round - OC

(Cont'd. from page 5)

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Handle with care. Avoid jolting, friction and impact.

Use only in well ventilated areas.

Information about fire - and explosion protection:

Protect from heat.

Keep respiratory protective device available.

Emergency cooling must be available in case of nearby fire.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:

Avoid storage near extreme heat, ignition sources or open flame.

- Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see section 7.
- · 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:
1309-48-4 magnesium oxide
PEL (USA) Long-term value: 15* mg/m ³

fume; *total particulate

iume, total particulate

TLV (USA) Long-term value: 10* mg/m³

*as inhalable fraction

EL (Canada) | Short-term value: 10** mg/m³

Long-term value: 10* 3** mg/m3

*inhalable fume; ** respirable dust and fume

EV (Canada) Long-term value: 10 mg/m³

inhalable

15245-44-0 lead 2,4,6-trinitro-m-phenylene dioxide

EV (Canada) Long-term value: 0,05 mg/m³

as Pb, Skin (organic compounds)

- **DNELs** No further relevant information available.
- · PNECs No further relevant information available.
- · Additional information: The lists valid during the making were used as basis.

(Cont'd. on page 7)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date July 23, 2015 Revision: July 23, 2015

Trade name: Direct Impact® 40mm Round - OC

(Cont'd. from page 6)

- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Do not inhale dust / smoke / mist.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

· Respiratory protection:

Wear positive pressure NIOSH or European EN149 vapor respirators when deploying product in large quantities.

Use suitable respiratory protective device when high concentrations are present.

Protection of hands:



Protective gloves

Wear gloves when handling deployed rounds.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Safety glasses

· Limitation and supervision of exposure into the environment

No further relevant information available.

· Risk management measures

See Section 7 for additional information.

Organizational measures should be in place for all activities involving this product.

No further relevant information available.

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Solid metal container containing liquid and solid contents.

(Cont'd. on page 8)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date July 23, 2015 Revision: July 23, 2015

Trade name: Direct Impact® 40mm Round - OC

(Cont'd. from page 7)

Colour: According to product specification

Odour:OdourlessOdour threshold:pH-value:Not applicable.

· Change in condition

Melting point/Melting range:
Boiling point/Boiling range:
Undetermined.

Flash point:
Not applicable.

Flammability (solid, gaseous):
Auto/Self-ignition temperature:
Not determined.

Not determined.

Not determined.

· **Self-igniting:** Product is not self-igniting.

• **Danger of explosion:** Heating may cause an explosion.

· Explosion limits:

Lower: Not determined.
Upper: Not determined.

Vapour pressure: Not applicable.

Density: Not determined.
Relative density Not determined.
Vapour density Not applicable.
Evaporation rate Not applicable.

· Solubility in / Miscibility with

water: Insoluble.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not applicable. **Kinematic:** Not applicable.

• 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

Risk of explosion if heated under confinement.

10.3 Possibility of hazardous reactions

Fire or projection hazard.

Toxic fumes may be released if heated above the decomposition point.

Reacts with strong acids and alkali.

(Cont'd. on page 9)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date July 23, 2015 Revision: July 23, 2015

Trade name: Direct Impact® 40mm Round - OC

(Cont'd. from page 8)

Reacts violently with oxidising agents.

- 10.4 Conditions to avoid Sources of ignition, open flame, incompatible materials.
- · 10.5 Incompatible materials: Oxidizers
- · 10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Nitrogen oxides

Sulphur oxides (SOx)

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity
- LD/LC50 values relevant for classification:

15245-44-0 lead 2,4,6-trinitro-m-phenylene dioxide

Oral LD50 650 mg/kg (rat)

- Primary irritant effect:
- · Skin corrosion/irritation

Not a skin irritant in unused form. Vapors/particles from used product are possibly irritating to skin. Causes skin irritation.

· Serious eye damage/irritation

Not an eye irritant in unused form. Vapors/particles from used product are possibly irritating to eyes. Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:

Normal handling of the undeployed product poses little or no health hazards, One should avoid inhalation by wearing appropriate respiratory protection when exposed to the chemical ingredients of the product above listed TLV's or when exposed to the post ignition by-products. This product is a cansister which contains the various components completely sealed within. Therefore, under normal handling of this product, no exposure to any harmful materials will occur. When the product is used, particles may be generated which may be irritating to the eyes and the respiratory tract.

· Acute effects (acute toxicity, irritation and corrosivity):

Inhalation may cause irritation to the respiratory system.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction):
- · Germ cell mutagenicity

Based on available data, the classification criteria are not met.

· Carcinogenicity

Based on available data, the classification criteria are not met.

· Reproductive toxicity

Based on available data, the classification criteria are not met.

· STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

· Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: Toxic for aquatic organisms

(Cont'd. on page 10)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA **GHS**

Printing date July 23, 2015 Revision: July 23, 2015

Trade name: Direct Impact® 40mm Round - OC

(Cont'd. from page 9)

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential May be accumulated in organism
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Also poisonous for fish and plankton in water bodies.

The product contains heavy metals. Avoid transfer into the environment. Specific preliminary treatments are necessary

Toxic for aquatic organisms

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

- 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

After prior treatment product has to be disposed of in an incinerator for hazardous waste adhering to the regulations pertaining to the disposal of particularly hazardous waste.

Must not be disposed together with household garbage. Do not allow product to reach sewage system. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to local official regulations.

SECTION 14: Transport information

· 14.1 UN-Number

· DOT. ADR. IMDG. IATA

14.2 UN proper shipping name

· DOT, IATA

· ADR

UN0301

Ammunition Tear-producing with burster, expelling charge or propelling charge

0301 Ammunition Tear-producing with burster,

expelling

charge or propelling charge, ENVIRONMENTALLY

HAZARDOÙS

(Cont'd. on page 11)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date July 23, 2015 Revision: July 23, 2015

Trade name: Direct Impact® 40mm Round - OC

(Cont'd. from page 10)

Ammunition Tear-producing with burster, expelling charge or propelling charge, MARINE POLLUTANT

· 14.3 Transport hazard class(es)

· DOT

· IMDG



· Class 1.4

· **Label** 1.4G+6.1+8

· ADR, IMDG



· Class 1.4

· **Label** 1.4G+6.1+8

· IATA



· Class 1.4

· **Label** 1.4G+6.1+8

· 14.4 Packing group

· DOT, ADR, IMDG, IATA

· 14.5 Environmental hazards:

· Marine pollutant: Yes

Symbol (fish and tree)
• Special marking (ADR):

Symbol (fish and tree)

Special marking (IATA):



Cargo Aircraft Only.

• 14.6 Special precautions for user Not applicable.

• EMS Number: $\underline{F-A}$,S-Q

· 14.7 Transport in bulk according to Annex II of

Marpol and the IBC Code Not applicable.

• UN "Model Regulation":

UN0301, Ammunition Tear-producing with burster, expelling charge or propelling charge,

ENVIRONMENTALLY HAZARDOUS, 1.4G (6.1+8), II

(Cont'd. on page 12)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date July 23, 2015 Revision: July 23, 2015

Trade name: Direct Impact® 40mm Round - OC

(Cont'd. from page 11)

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- United States (USA)
- ·SARA
- · Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65 (California):
- · Chemicals known to cause cancer:

Present in trace quantities.

15245-44-0 lead 2,4,6-trinitro-m-phenylene dioxide

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

Present in trace quantities.

15245-44-0 lead 2,4,6-trinitro-m-phenylene dioxide

- Carcinogenic Categories
- EPA (Environmental Protection Agency)

None of the ingredients are listed.

IARC (International Agency for Research on Cancer)

None of the ingredients are listed.

TLV (Threshold Limit Value established by ACGIH)

1309-48-4 magnesium oxide

A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

- · Canada
- · Canadian Domestic Substances List (DSL)

All ingredients are listed.

· Canadian Ingredient Disclosure list (limit 0.1%)

None of the ingredients are listed.

· Canadian Ingredient Disclosure list (limit 1%)

1309-48-4 magnesium oxide

(Cont'd. on page 13)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date July 23, 2015 Revision: July 23, 2015

Trade name: Direct Impact® 40mm Round - OC

(Cont'd. from page 12)

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I

None of the ingredients are listed.

· Other regulations, limitations and prohibitive regulations

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

Substances of very high concern (SVHC) according to REACH, Article 57

15245-44-0 lead 2,4,6-trinitro-m-phenylene dioxide

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H201 Explosive; mass explosion hazard.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H412 Harmful to aquatic life with long lasting effects.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Expl. 1.1: Explosives, Division 1.1

Expl. 1.4: Explosives, Division 1.4

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

· Sources

SDS Prepared by:

ChemTel Inc.

(Cont'd. on page 14)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date July 23, 2015 Revision: July 23, 2015

Trade name: Direct Impact® 40mm Round - OC

(Cont'd. from page 13)

1305 North Florida Avenue Tampa, Florida USA 33602-2902 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573 Website: www.chemtelinc.com