

**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 1/6/2020

SDS Number: 000000158928

Version: 1.2

Premium Blue™ Diesel Exhaust Fluid
™ Trademark, Valvoline or its subsidiaries, registered in various countries
729566

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**Product identifier**

Trade name : Premium Blue™ Diesel Exhaust Fluid

™ Trademark, Valvoline or its subsidiaries, registered in various countries

Details of the supplier of the safety data sheet

Valvoline LLC
100 Valvoline Way
Lexington, KY 40509
United States of America (USA)
1-800-TEAMVAL

Emergency telephone number

1-800-VALVOLINE (1-800-825-8654)

Regulatory Information Number

1-800-TEAMVAL

Product Information

1-800-TEAMVAL

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

GHS label elements

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**Hazardous components**

Chemical name	CAS-No.	Classification	Concentration (%)
UREA	57-13-6		32.50

SECTION 4. FIRST AID MEASURES

General advice : No hazards which require special first aid measures.

If inhaled : If breathed in, move person into fresh air.

**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 1/6/2020

SDS Number: 000000158928

Version: 1.2

Premium Blue™ Diesel Exhaust Fluid
™ Trademark, Valvoline or its subsidiaries, registered in various
countries
729566

If unconscious, place in recovery position and seek medical advice.

If symptoms persist, call a physician.

In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.

In case of eye contact : Remove contact lenses.
Protect unharmed eye.

If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed : Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:
stomach or intestinal upset (nausea, vomiting, diarrhea)
irritation (nose, throat, airways)
Headache
Dizziness

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Water spray

Foam

Carbon dioxide (CO₂)

Dry chemical

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : acid vapors
Ammonia
carbon dioxide and carbon monoxide
Nitrogen oxides (NO_x)

Specific extinguishing methods :

Product is compatible with standard fire-fighting agents.

Further information : Standard procedure for chemical fires.



SAFETY DATA SHEET

Revision Date: 05/19/2017

Print Date: 1/6/2020

SDS Number: 000000158928

Version: 1.2

Premium Blue™ Diesel Exhaust Fluid
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 729566

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.
- Methods and materials for containment and cleaning up : Keep in suitable, closed containers for disposal.
- Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
- Materials to avoid : No materials to be especially mentioned.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
UREA	57-13-6	TWA	10 mg/m3	US WEEL

Engineering measures : General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.

**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 1/6/2020

SDS Number: 000000158928

Version: 1.2

Premium Blue™ Diesel Exhaust Fluid
™ Trademark, Valvoline or its subsidiaries, registered in various
countries
729566

- Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.
- Skin and body protection : Wear as appropriate:
Safety shoes
Wear resistant gloves (consult your safety equipment supplier).
- Hygiene measures : General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state : liquid
- Colour : colourless
- Odour : ammoniacal
- Odour Threshold : No data available
- pH : 10
- Melting point/freezing point : No data available
- Boiling point/boiling range : No data available
- Flash point : Not applicable
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Upper explosion limit : No data available
- Lower explosion limit : No data available
- Vapour pressure : 293.309 hPa
- Relative vapour density : No data available
- Relative density : 1.09 (20 °C)
- Density : 1.09 g/cm³ (20 °C)

**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 1/6/2020

SDS Number: 000000158928

Version: 1.2

Premium Blue™ Diesel Exhaust Fluid
™ Trademark, Valvoline or its subsidiaries, registered in various
countries
729566

Solubility(ies)
Water solubility : soluble

Solubility in other solvents : No data available

Partition coefficient: n-
octanol/water : No data available

Thermal decomposition : No data available

Viscosity
Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous
reactions : Product will not undergo hazardous polymerization.

Conditions to avoid : None known.

Incompatible materials : Acids
Chlorine
nitrates
strong bases
Strong oxidizing agents

Hazardous decomposition
products : acid vapors
carbon dioxide and carbon monoxide
Nitrogen oxides (NOx)
Ammonia

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of
exposure : Inhalation
Skin contact
Eye Contact
Ingestion

**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 1/6/2020

SDS Number: 000000158928

Version: 1.2

Premium Blue™ Diesel Exhaust Fluid
™ Trademark, Valvoline or its subsidiaries, registered in various
countries
729566

Acute toxicity

Not classified based on available information.

Components:

UREA:

Acute oral toxicity : LD50 (Rat): 14,300 mg/kg
Method: OECD Test Guideline 401

Skin corrosion/irritation

Not classified based on available information.

Components:

UREA:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

UREA:

Species: Rabbit

Result: No eye irritation

Method: OECD Test Guideline 405

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:

UREA:

Assessment: Does not cause skin sensitisation.

Germ cell mutagenicity

Not classified based on available information.

Components:

UREA:

Genotoxicity in vitro : Test Type: Ames test
Test species: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative

: Test Type: Ames test
Test species: Escherichia coli
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative

Carcinogenicity

**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 1/6/2020

SDS Number: 000000158928

Version: 1.2

Premium Blue™ Diesel Exhaust Fluid
™ Trademark, Valvoline or its subsidiaries, registered in various countries
729566

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

Components:

UREA:

Effects on foetal development

: Species: Rat

Application Route: Oral

Developmental Toxicity: Lowest observed adverse effect level:
500 mg/kg bw/day

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Repeated dose toxicity**Components:**

UREA:

Species: Rat

NOAEL: 2,250 mg/kg

Application Route: Oral

Aspiration toxicity

Not classified based on available information.

Further information**Product:**

Remarks: No data available

Carcinogenicity:**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Product:**

Toxicity to fish

: LC50 (Fish): > 9,100 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

: EC50 (Daphnia magna (Water flea)): >= 10,000 mg/l

SAFETY DATA SHEET

Revision Date: 05/19/2017

Print Date: 1/6/2020

SDS Number: 000000158928

Version: 1.2

Premium Blue™ Diesel Exhaust Fluid
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 729566

aquatic invertebrates Exposure time: 24 h

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Components:

UREA:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): > 6,810 mg/l
 Exposure time: 96 h

LC50 (Poecilia reticulata (guppy)): 17,500 mg/l
 Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Water flea (Daphnia magna)): > 10,000 mg/l
 Exposure time: 24 h
 Test Type: static test
 Method: DIN 38412
 Remarks: Intoxication

Toxicity to algae : EC10 (Microcystis aeruginosa (blue-green algae)): 47 mg/l
 End point: Biomass
 Exposure time: 192 h
 Test Type: static test

NOEC (Microcystis aeruginosa (blue-green algae)): 47 mg/l
 End point: Biomass
 Exposure time: 192 h
 Test Type: static test

Persistence and degradability

Product:

Biodegradability : Result: Inherently biodegradable.

Components:

UREA:

Biodegradability : Result: Readily biodegradable.
 Biodegradation: 96 %
 Exposure time: 16 d
 Method: OECD Test Guideline 302B

No data available

Bioaccumulative potential

Components:

UREA:

Partition coefficient: n-octanol/water : log Pow: 1.73 (20 °C)

No data available



SAFETY DATA SHEET

Revision Date: 05/19/2017

Print Date: 1/6/2020

SDS Number: 000000158928

Version: 1.2

Premium Blue™ Diesel Exhaust Fluid
™ Trademark, Valvoline or its subsidiaries, registered in various countries
729566

Mobility in soil

Components:

No data available

Other adverse effects

No data available

Product:

Additional ecological information : No data available

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods

CFR_RAIL_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TDG_ROAD_C

Not dangerous goods

TDG_RAIL_C

Not dangerous goods



SAFETY DATA SHEET

Revision Date: 05/19/2017

Print Date: 1/6/2020

SDS Number: 000000158928

Version: 1.2

Premium Blue™ Diesel Exhaust Fluid
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 729566

TDG_INWT_C

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG

Not dangerous goods

***ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

**EPCRA - Emergency Planning and Community Right-to-Know Act
 CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
AMMONIUM HYDROXIDE ((NH4)(OH))	1336-21-6	1000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : No SARA Hazards

SARA 313 This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop 65 This product does not contain any chemicals known to State

SAFETY DATA SHEET

Revision Date: 05/19/2017

Print Date: 1/6/2020

SDS Number: 000000158928

Version: 1.2

Premium Blue™ Diesel Exhaust Fluid
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 729566

of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

- TSCA : On TSCA Inventory
- DSL : All components of this product are on the Canadian DSL
- AICS : On the inventory, or in compliance with the inventory
- ENCS : On the inventory, or in compliance with the inventory
- KECI : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information


Revision Date: 05/19/2017

<p>NFPA:</p>  <p style="text-align: center;">Special hazard.</p>	<p>HMIS III:</p> <table border="1" style="width: 100%;"> <tr> <td style="background-color: blue; color: white;">HEALTH</td> <td style="text-align: center; font-weight: bold;">0</td> </tr> <tr> <td style="background-color: red; color: white;">FLAMMABILITY</td> <td style="text-align: center; font-weight: bold;">0</td> </tr> <tr> <td style="background-color: yellow;">PHYSICAL HAZARD</td> <td style="text-align: center; font-weight: bold;">0</td> </tr> </table> <p>0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	0	FLAMMABILITY	0	PHYSICAL HAZARD	0
HEALTH	0						
FLAMMABILITY	0						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification

Not applicable

Full text of H-Statements

	Page: 12
SAFETY DATA SHEET	Revision Date: 05/19/2017
	Print Date: 1/6/2020
	SDS Number: 000000158928
Premium Blue™ Diesel Exhaust Fluid ™ Trademark, Valvoline or its subsidiaries, registered in various countries 729566	Version: 1.2

Sources of key data used to compile the Safety Data Sheet
 Valvoline internal data including own and sponsored test reports
 The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.


The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists
 BEI : Biological Exposure Index
 CAS : Chemical Abstracts Service (Division of the American Chemical Society).
 CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
 FG : Food grade
 GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
 H-statement : Hazard Statement
 IATA : International Air Transport Association.
 IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization
 ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
 IMDG : International Maritime Code for Dangerous Goods
 ISO : International Organization for Standardization
 logPow : octanol-water partition coefficient
 LCxx : Lethal Concentration, for xx percent of test population
 LDxx : Lethal Dose, for xx percent of test population.
 ICxx : Inhibitory Concentration for xx of a substance
 Ecxx : Effective Concentration of xx
 N.O.S.: Not Otherwise Specified
 OECD : Organization for Economic Co-operation and Development
 OEL : Occupational Exposure Limit
 P-Statement : Precautionary Statement
 PBT : Persistent , Bioaccumulative and Toxic
 PPE : Personal Protective Equipment
 STEL : Short-term exposure limit
 STOT : Specific Target Organ Toxicity
 TLV : Threshold Limit Value
 TWA : Time-weighted average
 vPvB : Very Persistent and Very Bioaccumulative
 WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act

	Page: 13
SAFETY DATA SHEET	Revision Date: 05/19/2017
	Print Date: 1/6/2020
	SDS Number: 000000158928
Premium Blue™ Diesel Exhaust Fluid ™ Trademark, Valvoline or its subsidiaries, registered in various countries 729566	Version: 1.2

DOT : Department of Transportation
 FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
 HMIRC : Hazardous Materials Information Review Commission
 HMIS : Hazardous Materials Identification System
 NFPA : National Fire Protection Association
 NIOSH : National Institute for Occupational Safety and Health
 OSHA : Occupational Safety and Health Administration
 PMRA : Health Canada Pest Management Regulatory Agency
 RTK : Right to Know
 WHMIS : Workplace Hazardous Materials Information System