

SAFETY DATA SHEET

Revision date 04-Jan-2018 Version 13 Supersedes Date: 12-Jun-2017

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Code 069.00A1120.076

Product Name AVP ENML BRT RED 6UC

Other means of identification

No information available

Recommended use of the chemical and restrictions on use

Aerosol, Paint

Details of the supplier of the safety data sheet

See section 16 for more information

The Valspar Corporation PO Box 1461 Minneapolis, MN 55440

<u>E-mail address</u> <u>msds@valspar.com</u>

Emergency telephone number
United States of America 1-888-345-5732

Section 2: HAZARDS IDENTIFICATION

Classification

Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1A
Carcinogenicity	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Flammable aerosols	Category 2
Gases under pressure	Liquefied gas

Label elements



Signal word

WARNING

HAZARD STATEMENTS

Flammable aerosol
Contains gas under pressure; may explode if heated
Causes serious eye irritation
May cause an allergic skin reaction
Suspected of causing cancer
Suspected of damaging fertility or the unborn child
May cause drowsiness or dizziness

PREVENTION

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Wash face, hands and any exposed skin thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing should not be allowed out of the workplace. Use only outdoors or in a well-ventilated area. P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

RESPONSE

IF exposed or concerned: Get medical advice/attention.

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skir

IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Ingestion

Do NOT induce vomiting. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

STORAGE

Store locked up. Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding $50 \, ^{\circ}\text{C}/122 \, ^{\circ}\text{F}$. Protect from sunlight.

DISPOSAL

Dispose of contents/containers in accordance with local regulations.

HAZARDS NOT OTHERWISE CLASSIFIED (HNOC)

No information available.

OTHER HAZARDS

Propellant is classified as a simple asphyxiant if released in large quantities: May displace oxygen and cause rapid suffocation. Not applicable.

UNKNOWN ACUTE TOXICITY

0% of the mixture consists of ingredient(s) of unknown toxicity.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	weight-%
---------------	--------	----------

Acetone	67-64-1	25 - 50
Propane	74-98-6	10 - 25
n-Butyl acetate	123-86-4	5 - 10
Ethylene glycol monopropyl ether	2807-30-9	3 - 5
Zirconium ethyl hexoate	22464-99-9	0.1 - 0.3
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	136-52-7	0.1 - 0.3

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

Section 4: FIRST AID MEASURES

First Aid Measures

General advice

IF exposed or concerned: Get medical advice/attention.

Eve contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin Contact

IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Ingestion

Do NOT induce vomiting. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

Section 5: FIRE FIGHTING MEASURES

Suitable extinguishing media

Dry chemical, CO2, water spray or alcohol-resistant foam.

Not to be used for safety reasons: Strong water jet

Specific hazards arising from the chemical

Burning produces heavy smoke. Fire may produce irritating and/or toxic gases. In the event of fire and/or explosion do not breathe fumes. May cause sensitization by skin contact.

Special protective equipment for fire-fighters

Wear self-contained breathing apparatus and protective suit. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire-fighting to enter drains or water courses.

Section 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions

Avoid breathing vapors or mists. Remove all sources of ignition. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Keep people away from and upwind of spill/leak.

For emergency responders

Use personal protection recommended in Section 8.

Environmental precautions

Do not allow into any sewer, on the ground or into any body of water. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Prevent further leakage or spillage if safe to do so.

Methods and material for containment and cleaning up

Methods for containment

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Dispose of waste product or used containers according to local regulations. Clean with detergents. Avoid solvent cleaners. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Take up mechanically, placing in appropriate containers for disposal. Pick up and transfer to properly labeled containers.

Section 7: HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits. Use personal protection recommended in Section 8. Never use pressure to empty container. Comply with the health and safety at work laws. Prevent product from entering drains. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Do not breathe dust/fume/gas/mist/vapors/spray. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

General Hygiene Considerations

Avoid contact with skin, eyes or clothing. When using do not eat, drink or smoke. Wash contaminated clothing before reuse.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep/store only in original container. Store in accordance with local regulations. Keep unauthorized personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Protect from sunlight. Store in a well-ventilated place.

Incompatible materials

Strong oxidizing agents.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Limits

If S* appears in the OEL table, it indicates this chemical contains a skin notation.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone	STEL: 500 ppm	TWA: 1000 ppm	IDLH: 2500 ppm
67-64-1	TWA: 250 ppm	TWA: 2400 mg/m ³	TWA: 250 ppm
			TWA: 590 mg/m ³
Propane	TWA: 1000 ppm	TWA: 1000 ppm	IDLH: 2100 ppm
74-98-6	See Appendix F: Minimal Oxygen	TWA: 1800 mg/m ³	TWA: 1000 ppm
	Content	_	TWA: 1800 mg/m ³
n-Butyl acetate	STEL: 150 ppm	TWA: 150 ppm	IDLH: 1700 ppm
123-86-4	TWA: 50 ppm	TWA: 710 mg/m ³	TWA: 150 ppm
			TWA: 710 mg/m ³
			STEL: 200 ppm
			STEL: 950 mg/m ³
Zirconium ethyl hexoate	STEL: 10 mg/m ³ Zr	TWA: 5 mg/m³ Zr	IDLH: 25 mg/m³ Zr
22464-99-9	TWA: 5 mg/m ³ Zr		TWA: 5 mg/m³ except Zirconium
			tetrachloride Zr
			STEL: 10 mg/m ³ Zr

Appropriate engineering controls

Engineering Controls

Ensure adequate ventilation, especially in confined areas. Provide local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tight sealing safety goggles.

Skin and body protection

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Wear suitable protective clothing. Personnel should wear anti-static clothing made of natural fiber or of high temperature resistant synthetic fiber.

Hand Protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical / chemical damage and poor maintenance. Wear protective gloves.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Thermal Protection

No information available

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Aerosol

Appearance No information available

Odor Solvent Color red

Odor Threshold No information available PH value No information available Melting point/freezing point No information available

Boiling point / boiling range No information available °C / °F

flash point -35 °C / -31 °F

evaporation rate

Flammability (solid, gas)

No information available
No information available

Flammability Limit in Air

Upper flammability limit:
Lower flammability limit:
Vapor Pressure
vapor density

No information available
No information available
No information available

Density (lbs per US gallon) 6.35

specific gravity

No information available

Solubility(ies) Not Determined

Partition coefficientNo information availableAutoignition temperatureNo information availableDecomposition temperatureNo information availableKinematic viscosityNo information availableDynamic viscosityNo information available

Other information

Section 10: STABILITY AND REACTIVITY

Reactivity No information available.

Chemical stability Stable under normal conditions.

Possibility of Hazardous Reactions None under normal processing.

Hazardous polymerizationNone under normal processing.

Conditions to avoid Heat, flames and sparks.

Incompatible materials Strong oxidizing agents.

Hazardous Decomposition Products Carbon monoxide. Carbon dioxide (CO2). Chlorine gas.

Section 11: TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Eye contact

Causes serious eye irritation

Skin Contact

May cause an allergic skin reaction

Ingestion Not applicable

Inhalation

May cause drowsiness or dizziness

Numerical measures of toxicity - Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone 67-64-1	= 5800 mg/kg (Rat)	> 15700 mg/kg (Rabbit)	= 50100 mg/m³ (Rat) 8 h
Propane 74-98-6	-	-	= 658 mg/L (Rat) 4 h
n-Butyl acetate 123-86-4	= 10768 mg/kg (Rat)	> 17600 mg/kg (Rabbit)	= 390 ppm (Rat) 4 h
Ethylene glycol monopropyl ether 2807-30-9	= 3089 mg/kg (Rat)	= 870 mg/kg(Rabbit)= 960 μL/kg (Rabbit)	= 1530 ppm (Rat) 7 h
Zirconium ethyl hexoate 22464-99-9	-	-	-
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1) 136-52-7	-	> 5000 mg/kg(Rabbit)	> 10 mg/L (Rat)1 h

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (dermal) 29325 Mg/kg

ATEmix (inhalation-dust/mist) 13.9 ATEmix (inhalation-vapor) 102

UNKNOWN ACUTE TOXICITY 0% of the mixture consists of ingredient(s) of unknown toxicity.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Chemical Name	ACGIH	IARC	NTP	OSHA
Hexanoic acid, 2-ethyl-,		Group 2B		X
cobalt(2+) salt (2:1)				
136-52-7				

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans.

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present.

Skin corrosion/irritation Not applicable

Serious eye damage/eye irritation Causes serious eye irritation

Skin sensitization May cause an allergic skin reaction

Respiratory sensitization Not applicable
Germ cell mutagenicity Not applicable
Carcinogenicity Suspected of causing cancer

Reproductive Toxicity Suspected of damaging fertility or the unborn child

Specific target organ toxicity (single exposure) May cause drowsiness or dizziness

Specific target organ toxicity (repeated exposure) Not applicable

Aspiration hazard Not applicable

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity

Environmental precautions Prevent product from entering drains.

Persistence and degradability

No information available

Bioaccumulation

No information available

Mobility

No information available

Other adverse effects No information available

Section 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Improper disposal or reuse of this container may be dangerous and illegal. Empty

containers must be scrapped or reconditioned.

Section 14: TRANSPORT INFORMATION

 DOT
 IMDG
 IATA

 14.1 UN/ID no
 ORM-D
 UN1950
 UN1950

14.2 Proper shipping name CONSUMER COMMODITY Aerosols, flammable Aerosols, flammable

14.3 Hazard Class 2.1 2.1

14.4 Packing Group

14.5 Environmental hazard Not applicable

14.6 Special Provisions

Emergency Response Guide EmS-No Number F-D, S-U

126

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No information available

The supplier may apply one of the following exceptions: Combustible Liquid (49 CFR 173.150(f)); Consumer Commodity (49 CFR 173.150(c), ICAO/IATA SP A112); Limited Quantity (49 CFR 173.150(b), ICAO Part 3 Chapter 4, IATA 2.7, IMDG Chapter 3.4); Viscous Liquid (49 CFR 173.121(b), IMDG 2.3.2.2, IATA 3.3.3.1.1, ICAO 3.2.2, ADR 2.2.3.1.5); Does Not Sustain Combustion (49 CFR 173.120(a), IATA 3.3.1.3, ICAO 3.1.3, IMDG 2.3.1.3, ADR 2.2.3.1.1 Note 1); or others as allowed under hazardous materials/dangerous goods regulations.

Section 15: REGULATORY INFORMATION

International Inventories

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL - Canadian Domestic Substances List

All components are listed or exempt from listing.

All components are listed or exempt

from listing

US Federal Regulations

Chemical Name	SARA 313 - Threshold Values %	Metals	Hazardous air pollutants (HAPs) content
Ethylene glycol monopropyl ether 2807-30-9 3 - 5	1		Present
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1) 136-52-7 0.1 - 0.3	1	Cobalt	Present

SARA 311/312 Hazard Categories

Acute health hazard Yes
Chronic Health Hazard Yes
Fire hazard Yes
Sudden release of pressure hazard Yes
Reactive Hazard No

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
n-Butyl acetate 123-86-4	5000 lb			Х

	Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
ı	Acetone	5000 lb		RQ 5000 lb final RQ
	67-64-1			RQ 2270 kg final RQ
-	n-Butyl acetate	5000 lb		RQ 5000 lb final RQ
	123-86-4			RQ 2270 kg final RQ

US State Regulations

Rule 66 status of product

Not photochemically reactive.

California Proposition 65

WARNING! This product contains a chemical known in the State of California to cause cancer.

U.S. EPA Label information

EPA Pesticide registration number Not applicable

U.S. State Right-to-Know Regulations

Chemical Name
Acetone
67-64-1
Propane
74-98-6
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Butane
106-97-8
n-Butyl acetate
123-86-4
Ethylene glycol monopropyl ether
2807-30-9
Zirconium ethyl hexoate
22464-99-9
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)
136-52-7

Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal

Repeated or prolonged overexposure to solvents may cause permanent damage to the nervous system

Section 16: OTHER INFORMATION

HMIS

Health hazards

* = Chronic Health Hazard

Flammability

Physical hazards

Personal Protection

2*

4

Chronic Health Hazard

A

V

X

Supplier Address

Valspar Consumer
Headquarters
The Valspar Corporation
Valspar Plasti-Kote
1636 Shawson Dr.

8725 W. Higgins Rd. Suite Grand Rapids, MI 49512 Mississauga, Ontario L4W 1N7

1000 800-253-3957 905-671-8333

Chicago, IL 60631 773-628-5500

Prepared By Product Stewardship

Revision date 04-Jan-2018

Revision Note No information available

Disclaimer

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.

End of Safety Data Sheet