



SAFETY DATA SHEET

1. Identification

Product identifier QD® Contact Cleaner

Other means of identification
Product Code No. 03130 (Item# 1003407)

Recommended use Electronic cleaner

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information
Manufactured or sold by:
Company name CRC Industries, Inc.
Address 885 Louis Dr.
 Warminster, PA 18974 US

Telephone
General Information 215-674-4300
Technical Assistance 800-521-3168
Customer Service 800-272-4620
24-Hour Emergency (CHEMTREC) 800-424-9300 (US)
Website www.crcindustries.com

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1
 Gases under pressure Liquefied gas

Health hazards Skin corrosion/irritation Category 2
 Specific target organ toxicity, single exposure Category 3 narcotic effects
 Aspiration hazard Category 1

Environmental hazards Hazardous to the aquatic environment, acute hazard Category 1
 Hazardous to the aquatic environment, long-term hazard Category 1

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

Precautionary statement
Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights, and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist/vapor. Wash thoroughly after handling. Wear protective gloves. Avoid release to the environment.

Response	If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. Collect spillage.
Storage	Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.
Disposal	Dispose of contents/container in accordance with local/regional/national regulations.
Hazard(s) not otherwise classified (HNOC)	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
naphtha (petroleum), hydrotreated light		64742-49-0	30 - 40
1,1-difluoroethane		75-37-6	20 - 30
n-heptane		142-82-5	10 - 20
3-methylhexane		589-34-4	5 - 10
methylcyclohexane		108-87-2	5 - 10
2,2,4-trimethylpentane		540-84-1	3 - 5
2-methylhexane		591-76-4	3 - 5
2,3-dimethylpentane		565-59-3	1 - 3
3-ethylpentane		617-78-7	1 - 3
3,3-dimethylpentane		562-49-2	< 1

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Skin irritation. May cause redness and pain.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may rupture when exposed to heat or flame. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire-fighting equipment/instructions

In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.

General fire hazards

Extremely flammable aerosol. Contents under pressure. Pressurized container may rupture when exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Remove all possible sources of ignition in the surrounding area. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapor. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. Prevent product from entering drains. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling

Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, see the product label.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Avoid spark promoters. These alone may be insufficient to remove static electricity. Store in tightly closed container. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
2,2,4-trimethylpentane (CAS 540-84-1)	PEL	2350 mg/m3
		500 ppm
methylcyclohexane (CAS 108-87-2)	PEL	2000 mg/m3
		500 ppm
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	PEL	400 mg/m3

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
n-heptane (CAS 142-82-5)	PEL	100 ppm 2000 mg/m3 500 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
2,3-dimethylpentane (CAS 565-59-3)	STEL	500 ppm
	TWA	400 ppm
2-methylhexane (CAS 591-76-4)	STEL	500 ppm
	TWA	400 ppm
3,3-dimethylpentane (CAS 562-49-2)	STEL	500 ppm
	TWA	400 ppm
3-ethylpentane (CAS 617-78-7)	STEL	500 ppm
	TWA	400 ppm
3-methylhexane (CAS 589-34-4)	STEL	500 ppm
	TWA	400 ppm
methylcyclohexane (CAS 108-87-2)	TWA	400 ppm
n-heptane (CAS 142-82-5)	STEL	500 ppm
	TWA	400 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
2,2,4-trimethylpentane (CAS 540-84-1)	Ceiling	1800 mg/m3
		385 ppm
	TWA	350 mg/m3 75 ppm
methylcyclohexane (CAS 108-87-2)	TWA	1600 mg/m3 400 ppm
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	TWA	400 mg/m3
		100 ppm
n-heptane (CAS 142-82-5)	Ceiling	1800 mg/m3
		440 ppm
	TWA	350 mg/m3 85 ppm

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value
1,1-difluoroethane (CAS 75-37-6)	TWA	2700 mg/m3 1000 ppm

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.
Individual protection measures, such as personal protective equipment	
Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin protection	
Hand protection	Wear protective gloves such as: Polyvinyl alcohol (PVA). Viton/butyl.
Other	Wear appropriate chemical resistant clothing.
Respiratory protection	If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state	Liquid.
Form	Aerosol.
Color	Colorless.

Odor Hydrocarbon-like.

Odor threshold Not available.

pH Not available.

Melting point/freezing point -195.9 °F (-126.6 °C) estimated

Initial boiling point and boiling range 179.6 °F (82 °C) estimated

Flash point 15.8 °F (-9 °C) estimated

Evaporation rate Very fast.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) 0.9 % estimated

Flammability limit - upper (%) 12 % estimated

Vapor pressure 2003.8 hPa estimated

Vapor density > 1 (air = 1)

Relative density 0.75 estimated

Solubility(ies)

Solubility (water) Negligible.

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature 509 °F (265 °C) estimated

Decomposition temperature Not available.

Viscosity Not available.

Percent volatile 98.1 % estimated

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions No dangerous reaction known under conditions of normal use.

Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Components	Species	Test Results
2,2,4-trimethylpentane (CAS 540-84-1)		
Acute		
Inhalation		
LC50	Rat	118 mg/l, 4 Hours
3-methylhexane (CAS 589-34-4)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
LC50	Rat	> 20 mg/l, 4 hours
Oral		
LD50	Rat	> 2000 mg/kg
methylcyclohexane (CAS 108-87-2)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Oral		
LD50	Rat	> 4000 mg/kg
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
LC50	Rat	61 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg
n-heptane (CAS 142-82-5)		
Acute		
Dermal		
LD50	Rabbit	3000 mg/kg
Inhalation		
<i>Vapor</i>		
LC50	Rat	> 73.5 mg/l, 4 hours

Components	Species	Test Results
Oral LD50	Rat	25000 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Not classifiable as to carcinogenicity to humans.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
Not listed.		
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)		
Not regulated.		
US. National Toxicology Program (NTP) Report on Carcinogens		
Not listed.		
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	May be fatal if swallowed and enters airways.	
Chronic effects	Prolonged inhalation may be harmful.	

12. Ecological information

Ecotoxicity	Very toxic to aquatic life with long lasting effects.
Persistence and degradability	No data is available on the degradability of any ingredients in the mixture.
Bioaccumulative potential	
Partition coefficient n-octanol / water (log Kow)	
1,1-difluoroethane	0.75
2,2,4-trimethylpentane	5.18
methylcyclohexane	3.61
n-heptane	4.66
Bioconcentration factor (BCF)	
naphtha (petroleum), hydrotreated light	10 - 25000
Mobility in soil	No data available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	If discarded, this product is considered a RCRA ignitable waste, D001. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable regulations.
Hazardous waste code	D001: Waste Flammable material with a flash point <140 F
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT	
UN number	UN1950
UN proper shipping name	Aerosols, flammable, Limited Quantity

Transport hazard class(es)

Class 2.1
Subsidiary risk -
Label(s) 2.1

Packing group Not applicable.

Environmental hazards

Marine pollutant Yes, but exempt from the regulations.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions N82

Packaging exceptions 306

Packaging non bulk None

Packaging bulk None

IATA

UN number UN1950

UN proper shipping name Aerosols, flammable, Limited Quantity

Transport hazard class(es)

Class 2.1
Subsidiary risk -

Packing group Not applicable.

ERG Code 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo aircraft Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1950

UN proper shipping name AEROSOLS, Limited Quantity

Transport hazard class(es)

Class 2.1
Subsidiary risk -

Packing group Not applicable.


Environmental hazards

Marine pollutant Yes, but exempt from the regulations.


EmS F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

DOT; IMDG



IATA



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

2,2,4-trimethylpentane (CAS 540-84-1) Listed.

CERCLA Hazardous Substances: Reportable quantity

2,2,4-trimethylpentane (CAS 540-84-1) 1000 LBS

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

2,2,4-trimethylpentane (CAS 540-84-1)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

1,1-difluoroethane (CAS 75-37-6)

Safe Drinking Water Act (SDWA) Not regulated.

Food and Drug Administration (FDA) Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Classified hazard categories Flammable (gases, aerosols, liquids, or solids)
Gas under pressure
Acute toxicity (any route of exposure)
Skin corrosion or irritation
Specific target organ toxicity (single or repeated exposure)
Aspiration hazard
Hazard not otherwise classified (HNOC)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

SARA 313 (TRI reporting)
Not regulated.

US state regulations

US. New Jersey Worker and Community Right-to-Know Act

1,1-difluoroethane (CAS 75-37-6)
2,2,4-trimethylpentane (CAS 540-84-1)
2,3-dimethylpentane (CAS 565-59-3)
3-methylhexane (CAS 589-34-4)
methylcyclohexane (CAS 108-87-2)
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)
n-heptane (CAS 142-82-5)

US. Massachusetts RTK - Substance List

1,1-difluoroethane (CAS 75-37-6)
2,2,4-trimethylpentane (CAS 540-84-1)
2,3-dimethylpentane (CAS 565-59-3)
2-methylhexane (CAS 591-76-4)
3-methylhexane (CAS 589-34-4)
methylcyclohexane (CAS 108-87-2)
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)
n-heptane (CAS 142-82-5)

US. Pennsylvania Worker and Community Right-to-Know Law

2,2,4-trimethylpentane (CAS 540-84-1)

2,3-dimethylpentane (CAS 565-59-3)
 2-methylhexane (CAS 591-76-4)
 3,3-dimethylpentane (CAS 562-49-2)
 3-methylhexane (CAS 589-34-4)
 methylcyclohexane (CAS 108-87-2)
 naphtha (petroleum), hydrotreated light (CAS 64742-49-0)
 n-heptane (CAS 142-82-5)

US. Rhode Island RTK

2,2,4-trimethylpentane (CAS 540-84-1)
 methylcyclohexane (CAS 108-87-2)
 naphtha (petroleum), hydrotreated light (CAS 64742-49-0)
 n-heptane (CAS 142-82-5)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 2016 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

2,2,4-trimethylpentane (CAS 540-84-1)
 naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR 51.100(s)) 74.9 %
Consumer products (40 CFR 59, Subpt. C) Not regulated

State

Consumer products This product is regulated as an Electronic Cleaner. This product is compliant for use in all 50 states.
VOC content (CA) 74.9 %
VOC content (OTC) 74.9 %

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
 A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 09-29-2014
Revision date 12-18-2018
Prepared by Allison Yoon
Version # 05
Further information CRC # 1750971

Disclaimer

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries, Inc..

Revision information

This document has undergone significant changes and should be reviewed in its entirety.