

CRAVE YELLOW

Date: 08/17/09

MATERIAL SAFETY DATA SHEET  
(For Coatings, Resins & Related Materials)

Page: 1

PICCO COATINGS COMPANY, INC.

HMIS INFO  
F-3 H-2 R-0

Section I -- PRODUCT IDENTIFICATION

Manufacturer's Name: PICCO COATINGS COMPANY, INC.  
Street Address : 11601 MCKINLEY  
City, State, Zip Code: HOUSTON, TX 77038

Emergency Telephone No.: (800) 633-8253 (Pers)  
Information Telephone #: (281) 447-8877

Product Class: MISC. PAINT PRODUCTS  
Manufacturers Code Identification: 72-46

Trade Name: P&H YELLOW HS URETHANE (SW-037)

Section II -- HAZARDOUS INGREDIENTS

Ingredient	CAS Registration	Percent	ppm	TLV	Mg/M3	LEL	Vapor Pres.
T-BUTYL ACETATE	540-88-5	5-15	200	950.00			
METHYL ISOAMYL KETONE	110-12-3	5-15	50		1.05	4.5	
METHYL N-AMYL KETONE	110-43-0	<5	50			2.2	

TLV-Threshold Limit Value as established by the ACGIH (American Conference of Governmental Industrial Hygienist) for exposure per 8 hour workday in parts per million of air (PPM) or milligrams per cubic meter of air (mg/M3).  
LEL-Lower Explosive Limit (vapor volume as a % in air)  
Vapor Pressure is measured @ 68 Deg. F in mm of Hg

Section III -- PHYSICAL DATA

Boiling Range: 248 -396 Deg. F  
Evaporation Rate = Slower Than Ether [X]  
Vapor Density = Heavier Than Air [X]  
Percent Volatile by Volume: 38.0 %  
Weight/Gallon : 11.20 #'s  
Volatile Organic Comp'd: 1.77 #/g

Section IV -- FIRE AND EXPLOSION HAZARD DATA

HMIS Code = 3

Flammability Classification : (DOT) FLAMMABLE LIQUID UN-1263  
Flash Point : 68 Deg. F TCC  
LEL : (see Section II)

Extinguishing Media : Use National Fire Protection Association (NFPA) Class B Fire Extinguisher or dry chemical, foam, or carbon dioxide. Water fog may also be used.

Unusual Fire and Explosion Hazards: Keep containers tightly closed and away from heat, sparks, electrical equipment and open flame. Closed containers may explode when exposed to extreme heat and resultant pressure build up.

Special Firefighting Procedures: Fight as volatile liquid fire. Use water fog to keep fire exposed containers cool to reduce pressure.

Section V -- HEALTH HAZARD DATA

HMIS Code = 2

Threshold Limit Value : (see Section II)

-----  
Section V -- HEALTH HAZARD DATA (Cont.)  
-----

## EFFECTS OF OVER EXPOSURE.

Acute: Inhalation- Temporary dizziness, headache, possible nausea. Symptoms disappear when exposure ceases.

Eye or skin contact- May cause discomfort by defatting action of solvent.

Chronic: Repeated contact to skin may cause dermatitis.

EMERGENCY AND FIRST AID PROCEDURES: Remove patient to fresh air. Flush eyes with clean water for 15 minutes. Wash skin thoroughly and remove saturated clothing. If symptoms persist, seek medical attention.

Ingestion: Keep person warm and quiet. Do not induce vomiting. Call physician immediately.

  
-----

## Section VI -- REACTIVITY DATA

HMIS Code = 0

STABILITY:  STABLE  UNSTABLE

CONDITIONS TO AVOID : Not Applicable

INCOMPATIBILITY (Materials To Avoid): Avoid contact with strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Usual products of combustion- CO, CO2 and possibly acrolein.

HAZARDOUS POLYMERIZATIONS:  MAY OCCUR  WILL NOT OCCURCONDITIONS TO AVOID: Not Applicable  
  
-----

## Section VII -- SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove sources of ignition and provide ventilation. Large spills may be scooped up with nonsparking tools. Provide respiratory protection if required. Small quantities may be picked up with absorbent material. See disposal precautions below.

WASTE DISPOSAL METHOD: Place in closed containers. See other precautions below. Dispose of in accordance with local, state and federal regulations.

---

-----  
Section VIII -- SPECIAL PROTECTION INFORMATION  
-----

RESPIRATORY PROTECTION: NIOSH or MSHA approved mask or respirator for organic vapors as necessary.

VENTILATION: Designed and maintained to provide fresh air volume and pattern to prevent vapor concentration in excess of Threshold Limit Value (TLV) or Lower Explosive Limit (LEL).

PROTECTIVE GLOVES: Neoprene rubber gloves

EYE PROTECTION: Goggles or side shield spectacles

OTHER PROTECTIVE EQUIPMENT: Eye wash station and safety showers should be available.  
  
-----

## Section IX -- SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store away from heat, sparks and open flame. Avoid prolonged skin contact. Do not breathe spray mist.

DOT (29 CFR) STORAGE CATEGORY: FLAMMABLE LIQUID CLASS I-B

DOT (49 CFR) SHIPPING CATEGORY: Flammable Liquid, 3, UN1263, II

OTHER PRECAUTIONS: Ground containers when pouring and limit free fall to a few inches to prevent static sparks.

Avoid spontaneous combustion of contaminated rags or other easily ignitable organic materials by immediate immersion in water. Emptied containers may retain hazardous properties. Do not cut, weld, puncture on or near container.

  
-----

While PICCO COATINGS CO. believes that the data herein is accurate and derived from qualified sources, this data is not to be taken as a warrantee or representation of fact for which PICCO COATINGS CO. assumes legal responsibility. They are offered solely for your consideration, investigation and verification.