MATERIAL SAFETY DATA SHEET

	This MSDS complies with OSHA'S Hazar	ra Communi	cation Standard 29 CFR 1	910.1200	and OSHA F	orm 174	
			BUTOR'S INFORMAT				
FPA Rating: Health-2; Flammability-2; Reactivity-0; Special HMIS Rating: Health-2; Flammability-2; Reactivity-0; Personal Protection-B							
Manufactured For:	Lagasse Brothers, Inc.	DC	DOT Hazard Classification: ORM-D				
Address:	1525 Kuebel Street	Ide	Identity (trade name as used on label):				
Address:	New Orleans, LA 70123		System Clean Dust Mop Treatment /SYC2080				
			MSDS Number: A06412 Revision- 11				
			Date Prepared: 01/15/07 Prepared by: IB				
NOTICE: JUDGEMENT I	BASED ON INDIRECT TEST DATA		ormation Calls: (770)422-				
		RIAL IDEN	TIFICATION AND INF				
	IAMES AND COMMON NAMES		CAS Number	SARA	OSHA PEL	ACGIH	Carcinogen
(Hazardous Components 1% or greater; Carcinogens 0.1% or greater)			0050 44 0	III LIST	(ppm)	TLV (ppm)	Ref. Source **
PETROLEUM DISTILLATE			8052-41-3	No	500	100	d
PETROLEUM DISTILLATE			64742-54-7 /	No	5mg/M3	5mg/M3	d
IOODUTANE (PRODANE DI END			64742-53-6	NI-	000	000	.l
ISOBUTANE / PROPANE BLEND			75-28-5	No	800	800	d
			74-98-6	No	1000	1000	d
		(010 11 (01					
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS							
Boiling Point: N/A Specific Gravity (H2O=1): Concentrate Only = 0.93							
Vapor Pressure: PSIG @ 70°F (Aerosols): Max. 50 Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A Vapor Density (Air = 1): N/E Evaporation Rate (= 1): N/E							
Solubility in Water: Emulsifia							
	e, creamy spray with pine fragrance.		ater reactive. No				
		IRE AND E	XPLOSION HAZARD	DATA			
FLAMMABILITY as per US	SA FLAME PROJECTION TEST		gnition Temperature		nability I imit	s in Air by %	in Volume:
(aerosols): less than 18" pr		7 1010	N/E		: N/E		.: N/E
	ORIZED AS FLAMMABLE						
FLASH POINT AND METHOD USED (non-aerosols): N/A SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus. EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide, water.							
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.							
SECTION 4 - REACTIVITY HAZARD DATA							
STABILITY [X] STABLE [] UNSTABLE HAZARDOUS POLYMERIZATION [] WILL [X] WILL NOT OCCUR							
Incompatibility (Mat. to avoid): Strong oxidizers. Conditions to Avoid: Open flame, welding arcs, heat, sparks.							
Hazardous Decomposition Products: CO, CO2.							
SECTION 5 - HEALTH HAZARD DATA							
PRIMARY ROUTES OF ENTRY: [X]INHALATION []INGESTION [X]SKIN ABSORPTION []EYE []NOT HAZARDOUS							
ACUTE EFFECTS:							
Inhalation: Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects and possible unconsciousness.							
Eye Contact: Irritation Skin Contact: Irritation							
Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea.							
CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) Dermatitis.							
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.							
EMERGENCY FIRST AID PROCEDURES							
Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.							
Skin Contact: Wash with soap and water. If irritated, seek medical attention.							
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.							
Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.							
SECTION 6 - CONTROL AND PROTECTIVE MEASURES							
Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by NIOSH for organic vapor.							
Protective Gloves: Disposable Latex or Nitrile. Eye Protection: Safety glasses.							
Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.							
Other Protective Clothing & Equipment: Eyewash station recommended.							
Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.							
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE							
Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or Federal regulations. DO NOT FLUSH TO SEWER.							
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.							
Other Precautions &/or S	In Handling & Storage: Do not pun Special Hazards: KEEP OUT OF RE						
prolonged breathing of spr	ay mist. hts. technical information and recommendation	ions contain	nd harain ara raliabla, but	thou are a	ivon without v	varranty or aua	rantoo of any kind

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only

THIS MSDS IS CURRENT AS OF January 3, 2010. The DATE PREPARED section is the original date assembled and remains current until a change is necessary. This is tracked internally at the manufacturer by these date codes and therefore must remain as the originating date.