Valvoline.	Page: 1
SAFETY DATA SHEET	Revision Date: 04/05/2019
	Print Date: 6/23/2021
	SDS Number: R0257033
SynPower™ SYNTHETIC GREASE SYNTHETIC GREASE	Version: 1.3
VV98510	

29 CFR 1910.1200 (OSHA HazCom 2012)

# **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

**Product identifier** 

Trade name : SynPower™ SYNTHETIC GREASE

SYNTHETIC GREASE

Details of the supplier of the safety data sheet

Valvoline LLC 100 Valvoline Way Lexington, KY 40509 United States of America (USA) 1-800-TEAMVAL (1-800-832-6825) Emergency telephone number

1-800-VALVOLINE (1-800-825-8654)

Regulatory Information Number 1-800-TEAMVAL (1-800-832-6825)

**Product Information** 

1-800-TEAMVAL (1-800-832-6825)

# **SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification** 

Eye irritation : Category 2A

**GHS** label elements

Hazard pictograms :

Signal Word : Warning

Hazard Statements : Causes serious eye irritation.

Precautionary Statements : Prevention:

Wash skin thoroughly after handling. Wear eye protection/ face protection.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

If eye irritation persists: Get medical advice/ attention.

Other hazards

None known.

Valvoline.	Page: 2
SAFETY DATA SHEET	Revision Date: 04/05/2019
	Print Date: 6/23/2021
	SDS Number: R0257033
SynPower™ SYNTHETIC GREASE SYNTHETIC GREASE	Version: 1.3
VV98510	

## **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Hazardous components** 

Chemical name	CAS-No.	Classification	Concentration (%)
Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters,		Skin Irrit. 2; H315	2.50
zinc salts		Eye Dam. 1; H318	
MOLYBDENUM DISULFIDE		Not a hazardous substance or mixture.	2.50

#### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If breathed in, move person into fresh air.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : If on skin, rinse well with water.

First aid is not normally required. However, it is

recommended that exposed areas be cleaned by washing

with soap and water.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eye.

If swallowed : Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

: Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through

the skin may include:

stomach or intestinal upset (nausea, vomiting, diarrhea)

irritation (nose, throat, airways) Causes serious eye irritation.

Notes to physician : No hazards which require special first aid measures.

Valvoline.	Page: 3
SAFETY DATA SHEET	Revision Date: 04/05/2019
	Print Date: 6/23/2021
	SDS Number: R0257033
SynPower™ SYNTHETIC GREASE SYNTHETIC GREASE	Version: 1.3
VV98510	

## **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray Foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: carbon dioxide and carbon monoxide

Oxides of phosphorus

Specific extinguishing

methods

: Product is compatible with standard fire-fighting agents.

Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus.

## **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Valvoline	Page: 4
SAFETY DATA SHEET	Revision Date: 04/05/2019
	Print Date: 6/23/2021
	SDS Number: R0257033
SynPower™ SYNTHETIC GREASE SYNTHETIC GREASE	Version: 1.3
VV98510	

Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

## **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Do not breathe vapours/dust.

Do not smoke.

Container hazardous when empty. Avoid contact with skin and eyes.

Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

# **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

Components with workplace control parameters

Components	CAS-No.	Value type (Form of	Control parameters / Permissible	Basis
		exposure)	concentration	
MOLYBDENUM DISULFIDE	1317-33-5	TWA	15 mg/m3 total dust (Molybdenum)	OSHA Z-1
		TWA	10 mg/m3 Inhalable fraction (Molybdenum)	ACGIH
		TWA	3 mg/m3 Respirable fraction (Molybdenum)	ACGIH
		TWA	10 mg/m3 Total dust (Molybdenum)	OSHA P0
		PEL	10 mg/m3 Total dust (Molybdenum)	CAL PEL
		PEL	3 mg/m3 respirable dust	CAL PEL

Valvoline.	Page: 5
SAFETY DATA SHEET	Revision Date: 04/05/2019
	Print Date: 6/23/2021
	SDS Number: R0257033
SynPower™ SYNTHETIC GREASE SYNTHETIC GREASE	Version: 1.3
VV98510	

fraction	
(Molybdenum)	

**Engineering measures** 

 Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

## Personal protective equipment

Respiratory protection

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Wear chemical splash goggles when there is the potential for

exposure of the eyes to liquid, vapor or mist.

Skin and body protection : Wear as appropriate:

Impervious clothing

Safety shoes

Choose body protection according to the amount and concentration of the dangerous substance at the work place. Discard gloves that show tears, pinholes, or signs of wear. Wear resistant gloves (consult your safety equipment

supplier).

Hygiene measures : Wash hands before breaks and at the end of workday.

When using do not eat or drink. When using do not smoke.

# **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : paste

Colour : dark grey

Odour : No data available

Odour Threshold : No data available

Valvoline	Page: 6
SAFETY DATA SHEET	Revision Date: 04/05/2019
	Print Date: 6/23/2021
	SDS Number: R0257033
SynPower™ SYNTHETIC GREASE SYNTHETIC GREASE	Version: 1.3
VV98510	

pH : No data available

Melting point/freezing point : 500 °F / 260 °C

Boiling point/boiling range : 700 °F / 371 °C

Flash point :  $419 \, ^{\circ}\text{F} / 215 \, ^{\circ}\text{C}$ 

Evaporation rate :

No data available

Flammability (solid, gas) : No data available

Self-ignition : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure :

No data available

Relative vapour density : No data available

Relative density:

No data available

Density : 0.919 g/cm3 (68 °F / 20 °C)

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Ignition temperature :  $> 599 \, ^{\circ}\text{F} / > 315 \, ^{\circ}\text{C}$ 

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Valvoline.	Page: 7
SAFETY DATA SHEET	Revision Date: 04/05/2019
	Print Date: 6/23/2021
	SDS Number: R0257033
SynPower™ SYNTHETIC GREASE SYNTHETIC GREASE	Version: 1.3
VV98510	

Viscosity, kinematic : > 20.5 mm2/s (104 °F / 40 °C)

Oxidizing properties : No data available

## **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous

reactions

: Product will not undergo hazardous polymerization.

Conditions to avoid : None known.

None known.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products carbon dioxide and carbon monoxide

## **SECTION 11. TOXICOLOGICAL INFORMATION**

#### Information on likely routes of exposure

Inhalation Skin contact Eye Contact Ingestion

# Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : LD50 (Rat): 93,458 mg/kg

Method: Acute toxicity estimate

Acute dermal toxicity : LD50 (Rabbit): 2,599 mg/kg

Method: Acute toxicity estimate

## **Components:**

## Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts:

Acute oral toxicity : LD50 (Rat): > 2,000 - 5,000 mg/kg

Remarks: Information given is based on data obtained from

similar substances.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Remarks: Information given is based on data obtained from

similar substances.

Valvoline	Page: 8
SAFETY DATA SHEET	Revision Date: 04/05/2019
	Print Date: 6/23/2021
	SDS Number: R0257033
SynPower™ SYNTHETIC GREASE SYNTHETIC GREASE	Version: 1.3
VV98510	

**MOLYBDENUM DISULFIDE:** 

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 2.82 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: No adverse effect has been observed in acute

inhalation toxicity tests.

Skin corrosion/irritation

Not classified based on available information.

Product:

Result : No skin irritation

Remarks : May cause skin irritation in susceptible persons.

**Components:** 

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts:

Result : Irritating to skin.

MOLYBDENUM DISULFIDE:

Result : No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks : Vapours may cause irritation to the eyes, respiratory system

and the skin.

Causes serious eye irritation.

**Components:** 

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts:

Result : Corrosive

MOLYBDENUM DISULFIDE:

Result : No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC No component of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA**No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

Valvoline	Page: 9
SAFETY DATA SHEET	Revision Date: 04/05/2019
	Print Date: 6/23/2021
	SDS Number: R0257033
SynPower™ SYNTHETIC GREASE SYNTHETIC GREASE	Version: 1.3
VV98510	

NTP No component of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

**Aspiration toxicity** 

Not classified based on available information.

**Further information** 

Product:

Remarks : No data available

## **SECTION 12. ECOLOGICAL INFORMATION**

## **Ecotoxicity**

## **Product:**

Ecotoxicology Assessment

Short-term (acute) aquatic

hazard

: Acute aquatic toxicity Category 3; Harmful to aquatic life.

Long-term (chronic) aquatic

hazard

: Chronic aquatic toxicity Category 3; Harmful to aquatic life

with long lasting effects.

Components:

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts:

Toxicity to fish : LC50 (Fish): > 1 - 10 mg/l

Exposure time: 96 h

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Aquatic invertebrates): > 10 - 100 mg/l

Exposure time: 48 h

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to algae : EC50 (green algae): > 10 - 100 mg/l

Exposure time: 72 h

Remarks: Information given is based on data obtained from

similar substances.

# Persistence and degradability

Components:

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts:

Biodegradability : Biodegradation: 1.5 %

Exposure time: 28 d

Valvoline	Page: 10
SAFETY DATA SHEET	Revision Date: 04/05/2019
	Print Date: 6/23/2021
	SDS Number: R0257033
SynPower™ SYNTHETIC GREASE SYNTHETIC GREASE	Version: 1.3
VV98510	

Method: OECD Test Guideline 301B

No data available

**Bioaccumulative potential** 

**Components:** 

No data available

Mobility in soil

Components:

No data available

Other adverse effects

No data available

**Product:** 

Additional ecological

information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life

with long lasting effects.

Components:

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

## **Disposal methods**

General advice : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and

federal regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Empty containers should be taken to an approved waste

handling site for recycling or disposal. Do not re-use empty containers.

#### **SECTION 14. TRANSPORT INFORMATION**

# International transport regulations

#### **REGULATION**

KEGGEATION					
ID NUMBER	PROPER SHIPPING NAME	*HAZARD	SUBSIDIARY	PACKING	MARINE
		CLASS	HAZARDS	GROUP	POLLUTANT /
					LTD. QTY.

#### **U.S. DOT - ROAD**

Not dangerous goods	

# CFR\_RAIL\_C

Valvoline.	Page: 11
SAFETY DATA SHEET	Revision Date: 04/05/2019
	Print Date: 6/23/2021
	SDS Number: R0257033
SynPower™ SYNTHETIC GREASE SYNTHETIC GREASE	Version: 1.3
VV98510	
Not dangerous goods	

	Not dangerous goods
U.S. DOT - INL	AND WATERWAYS
	Not dangerous goods
TDG_ROAD_C	;
	Not dangerous goods
TDG_RAIL_C	
	Not dangerous goods
TDG_INWT_C	
	Not dangerous goods
INTERNATION	AL MARITIME DANGEROUS GOODS
	Not dangerous goods
	· · ·
INTERNATION	AL AIR TRANSPORT ASSOCIATION - CARGO
	Not dangerous goods
	· · ·
INTERNATION	AL AIR TRANSPORT ASSOCIATION - PASSENGER
	Not dangerous goods
	· · ·
MX DG	
_	Not dangerous goods

# \*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

# **SECTION 15. REGULATORY INFORMATION**

Valvoline	Page: 12
SAFETY DATA SHEET	Revision Date: 04/05/2019
	Print Date: 6/23/2021
	SDS Number: R0257033
SynPower™ SYNTHETIC GREASE SYNTHETIC GREASE	Version: 1.3
VV98510	

# **EPCRA - Emergency Planning and Community Right-to-Know Act**

#### **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Serious eye damage or eye irritation

# California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

## The components of this product are reported in the following inventories:

TSCA : On the inventory, or in compliance with the inventory

DSL : This product contains the following components that are not

on the Canadian DSL nor NDSL.

AICS : Not in compliance with the inventory

ENCS : Not in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

KECI : Not in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

#### **TSCA list**

No substances are subject to TSCA 12(b) export notification requirements.

#### Inventories


AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

#### **SECTION 16. OTHER INFORMATION**

## **Further information**

Revision Date: 04/05/2019

Valvoline	Page: 13
SAFETY DATA SHEET	Revision Date: 04/05/2019
	Print Date: 6/23/2021
	SDS Number: R0257033
SynPower™ SYNTHETIC GREASE SYNTHETIC GREASE	Version: 1.3
VV98510	



NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

#### **Full text of H-Statements**

H315 Causes skin irritation.H318 Causes serious eye damage.

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet:

ACGIH: American Conference of Industrial Hygienists

BEI: Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

Valvoline.	Page: 14
SAFETY DATA SHEET	Revision Date: 04/05/2019
	Print Date: 6/23/2021
	SDS Number: R0257033
SynPower™ SYNTHETIC GREASE SYNTHETIC GREASE	Version: 1.3
VV98510	

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic

PPE: Personal Protective Equipment STEL: Short-term exposure limit STOT: Specific Target Organ Toxicity

TLV : Threshold Limit Value TWA : Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

DOT: Department of Transportation

FIFRA: Federal Insecticide, Fungicide, and Rodenticide Act HMIRC: Hazardous Materials Information Review Commission

HMIS: Hazardous Materials Identification System NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health OSHA: Occupational Safety and Health Administration

PMRA: Health Canada Pest Management Regulatory Agency

RTK: Right to Know

WHMIS: Workplace Hazardous Materials Information System