CR®

SAFETY DATA SHEET

1. Identification

Product identifier FiberLock® Head Gasket & Block Repair - 1 qt

Other means of identification

Product Code No. 401224 (Item# 1008135)

Recommended use Seals leaks in engine block

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc.

Address 885 Louis Dr.

Warminster, PA 18974 US

Telephone

 General Information
 215-674-4300

 Technical Assistance
 800-521-3168

 Customer Service
 800-272-4620

 24-Hour Emergency
 800-424-9300 (US)

(CHEMTREC)

Website www.crcindustries.com

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2A
Carcinogenicity Category 2
Hazardous to the aquatic environment, acute Category 3

hazard

Hazardous to the aquatic environment, Category 3

long-term hazard

OSHA defined hazards Not classified.

Label elements

Environmental hazards





Signal word Warning

Hazard statement Causes skin irritation. Causes serious eye irritation. Suspected of causing cancer.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wash thoroughly after handling. Wear

protective gloves/protective clothing/eye protection/face protection.

Response IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye

irritation persists: Get medical advice/attention. If exposed or concerned: Get medical

advice/attention.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Material name: FiberLock® Head Gasket & Block Repair - 1 qt No. 401224 (Item# 1008135) Version #: 01 Issue date: 02-03-2021 None known.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
water		7732-18-5	80 - 90
sodium silicate		1344-09-8	5 - 10
cellulose		9004-34-6	1 - 3
Refractories, fibers, aluminosilicate	,	142844-00-6	1 - 3
bentonite		1302-78-9	0.1 - 1
distillates (petroleum), solvent-dewaxed heavy paraffinic		64742-65-0	0.1 - 1
sodium nitrate		7631-99-4	0.1 - 1
copper		7440-50-8	≤ 0.1

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get Skin contact

medical advice/attention. Wash contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

vision. Skin irritation. May cause redness and pain.

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

Rinse mouth. Get medical attention if symptoms occur. Ingestion

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware

of the material(s) involved, and take precautions to protect themselves.

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

General information

media

the chemical

Specific hazards arising from

During fire, gases hazardous to health may be formed.

Special protective equipment

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Move containers from fire area if you can do so without risk. Use standard firefighting procedures

and precautions for firefighters Fire-fighting

equipment/instructions

General fire hazards

and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Prevent product from entering drains.

Small Spills; Wipe up with absorbent material (e.g. cloth, fleece), Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Material name: FiberLock® Head Gasket & Block Repair - 1 qt

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, see the product label.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

Components	Туре	Value	Form
cellulose (CAS 9004-34-6)	PEL	5 mg/m3	Respirable fraction
		15 mg/m3	Total dust.
copper (CAS 7440-50-8)	PEL	1 mg/m3	Dust and mist.
		0.1 mg/m3	Fume.
distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	PEL	5 mg/m3	Mist.
,		2000 mg/m3	
		500 ppm	
US. ACGIH Threshold Limit Values			
Components	Туре	Value	Form
cellulose (CAS 9004-34-6)	TWA	10 mg/m3	
copper (CAS 7440-50-8)	TWA	1 mg/m3	Dust and mist.
		0.2 mg/m3	Fume.
distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	TWA	5 mg/m3	Inhalable fraction.
US. NIOSH: Pocket Guide to Chemical	Hazards		
Components	Туре	Value	Form
cellulose (CAS 9004-34-6)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
copper (CAS 7440-50-8)	TWA	1 mg/m3	Dust and mist.
		0.1 mg/m3	Fume.
distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	Ceiling	1800 mg/m3	
	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Refractories, fibers, aluminosilicate (CAS 142844-00-6)	TWA	3 fibers/cm3	Fibrous dust.
,		3 fibers/cm3	Fiber.
		5 mg/m3	fibers, total dust
		5 mg/ms	libers, total dust

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). Eye/face protection

Skin protection

Hand protection Wear protective gloves such as: Neoprene. Nitrile.

Other Wear suitable protective clothing.

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a Respiratory protection

> NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

211.9 °F (100 °C) estimated

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid.

Fibrous liquid. **Form**

Color Beige. Odor Bland.

Not available. **Odor threshold**

11.2 pН

Melting point/freezing point Not available.

Initial boiling point and boiling

range

Flash point None.

Evaporation rate Slow.

Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

0.0007 hPa estimated Vapor pressure

Not available. Vapor density

Relative density 1.07

Solubility(ies)

Not available. Solubility (water) Partition coefficient Not available.

(n-octanol/water)

400 °F (204.4 °C) estimated **Auto-ignition temperature**

Decomposition temperature Not available. Viscosity Not available. 84.9 % estimated Percent volatile

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. **Chemical stability**

Material name: FiberLock® Head Gasket & Block Repair - 1 gt No. 401224 (Item# 1008135) Version #: 01 Issue date: 02-03-2021 Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid

Heat, flames and sparks. Contact with incompatible materials.

Incompatible materials

Strong oxidizing agents.

Hazardous decomposition

مامامه مامم ۱۸م

products

Aldehydes. Alcohols. Ethers. Hydrocarbons. Ketones. Organic acids. Hydrogen. Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Causes skin irritation.

Eye contact Causes serious eye irritation.

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity Not known.

Components Species Test Results

sodium nitrate (CAS 7631-99-4)

Acute

Dermal

LD50 Rat > 5000 mg/kg

Inhalation

Vapor

LC50 Rat 0.527 mg/l, 4 hours

Oral

LD50 Rat > 2000 mg/kg

sodium silicate (CAS 1344-09-8)

Acute Oral

Solid

LD50 Rat 1500 - 3200 mg/kg

Skin corrosion/irritation

Serious eye damage/eye

Causes serious eye irritation.

Causes skin irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

distillates (petroleum), solvent-dewaxed heavy paraffinic 3 Not classifiable as to carcinogenicity to humans.

(CAS 64742-65-0)

Refractories, fibers, aluminosilicate (CAS 142844-00-6) 2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - Not classified.

single exposure

This product is not expected to eduse reproductive or developmental enects.

Material name: FiberLock® Head Gasket & Block Repair - 1 qt

No. 401224 (Item# 1008135) Version #: 01 Issue date: 02-03-2021

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Components Species Test Results

sodium nitrate (CAS 7631-99-4)

Aquatic

Acute Crustace:

Crustacea EC50 Water flea (Daphnia magna) 8600 mg/l, 24 hours
Fish LC50 Bluegill (Lepomis macrochirus) 2000 mg/l, 96 hours

Rainbow trout, donaldson trout 994.4 - 1107 mg/l, 96 hours

(Oncorhynchus mykiss)

Persistence and degradability

Bioaccumulative potential

No data is available on the degradability of any ingredients in the mixture.

Mobility in soil No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions This product is not a RCRA hazardous waste (See 40 CFR Part 261.20 – 261.33). Empty

containers may be recycled. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all

applicable regulations.

Hazardous waste code Not regulated.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

copper (CAS 7440-50-8) sodium nitrate (CAS 7631-99-4)

CERCLA Hazardous Substance List (40 CFR 302.4)

copper (CAS 7440-50-8)

CERCLA Hazardous Substances: Reportable quantity

copper (CAS 7440-50-8) 5000 LBS

Material name: FiberLock® Head Gasket & Block Repair - 1 qt No. 401224 (Item# 1008135) Version #: 01 Issue date: 02-03-2021 Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Contains component(s) regulated under the Safe Drinking Water Act.

Food and Drug Administration (FDA) Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Classified hazard Skin corrosion or irritation

categories Serious eye damage or eye irritation

Carcinogenicity

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
sodium nitrate	7631-99-4	0.1 - 1	

US state regulations

US. New Jersey Worker and Community Right-to-Know Act

cellulose (CAS 9004-34-6)

copper (CAS 7440-50-8)

Refractories, fibers, aluminosilicate (CAS 142844-00-6)

sodium nitrate (CAS 7631-99-4)

US. Massachusetts RTK - Substance List

cellulose (CAS 9004-34-6)

copper (CAS 7440-50-8)

Refractories, fibers, aluminosilicate (CAS 142844-00-6)

sodium nitrate (CAS 7631-99-4)

US. Pennsylvania Worker and Community Right-to-Know Law

cellulose (CAS 9004-34-6)

copper (CAS 7440-50-8)

Refractories, fibers, aluminosilicate (CAS 142844-00-6)

sodium nitrate (CAS 7631-99-4)

US. Rhode Island RTK

cellulose (CAS 9004-34-6)

copper (CAS 7440-50-8)

distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)

Refractories, fibers, aluminosilicate (CAS 142844-00-6)

sodium nitrate (CAS 7631-99-4)

California Proposition 65



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

California Proposition 65 - CRT: Listed date/Carcinogenic substance

1,4-dioxane (CAS 123-91-1)

acetaldehyde (CAS 75-07-0)

crystalline silica, tridymite (CAS 15468-32-3)

ethylene oxide (CAS 75-21-8)

poly(p-phenylenediamine terephthalamide)

Listed: January 1, 1988

Listed: April 1, 1988

Listed: October 1, 1988

Listed: July 1, 1987

Listed: July 1, 1990

(CAS 26125-61-1)

quartz (CAS 14808-60-7) Listed: October 1, 1988

California Proposition 65 - CRT: Listed date/Developmental toxin

ethylene oxide (CAS 75-21-8) Listed: August 7, 2009

Material name: FiberLock® Head Gasket & Block Repair - 1 qt No. 401224 (Item# 1008135) Version #: 01 Issue date: 02-03-2021

California Proposition 65 - CRT: Listed date/Female reproductive toxin

ethylene oxide (CAS 75-21-8) Listed: February 27, 1987

California Proposition 65 - CRT: Listed date/Male reproductive toxin

ethylene oxide (CAS 75-21-8) Listed: August 7, 2009

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

copper (CAS 7440-50-8)

distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR

0.1 %

51.100(s))

Consumer products (40 CFR 59, Subpt. C) Not regulated

Inventory name

State

Not regulated **Consumer products**

VOC content (CA) 0.1 % VOC content (OTC) 0.1 %

International Inventories

Philippines

Taiwan

Country(s) or region

Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No

(PICCS)

Taiwan Chemical Substance Inventory (TCSI) United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

Philippine Inventory of Chemicals and Chemical Substances

16. Other information, including date of preparation or last revision

Issue date 02-03-2021 Prepared by Allison Yoon

Version # 01

CRC # 479/1002474 **Further information**

The information contained in this document applies to this specific material as supplied. It may not Disclaimer

> be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety

professional, or CRC Industries, Inc.,

Revision information This document has undergone significant changes and should be reviewed in its entirety.

Material name: FiberLock® Head Gasket & Block Repair - 1 gt

No

No

On inventory (yes/no)*

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).