

Version 1.3 Revision Date: 05/19/2017

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Startex Sander Deglosser

Recommended use of the chemical and restrictions on use

Recommended use : Solvent.

Manufacturer or supplier's details

Company: Nexeo Solutions LLC - STARTEX™Address3 Waterway Square Place Suite 1000

The Woodlands, TX. 77380 United States of America

Emergency telephone number:

Health North America: 1-855-NEXEO4U (1-855-639-3648) Health International: 1-855-NEXEO4U (1-855-639-3648) Transport North America: CHEMTREC (1-800-424-9300)

Additional Information: : Responsible Party: Product Safety Group

E-Mail: msds@nexeosolutions.com SDS Requests: 1-855-429-2661 SDS Requests Fax: 1-281-500-2370 Website: www.nexeosolutions.com

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 2

Acute toxicity (Inhalation) : Category 4

Skin irritation : Category 2

Eye irritation : Category 2A

Specific target organ toxicity

- single exposure

: Category 3 (Respiratory system, Central nervous system)

Specific target organ toxicity

- repeated exposure

: Category 2 (Liver, Kidney, Central nervous system)

Aspiration hazard : Category 1

GHS Label element

Hazard pictograms :







Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.

SDS Number: 100000007952 1 / 17 Startex Sander Deglosser



Version 1.3 Revision Date: 05/19/2017

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs (Liver, Kidney, Central nervous system) through prolonged or repeated exposure.

Precautionary statements

Prevention:

P210 Keep away from heat/sparks/open flames/hot surfaces.

No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P314 Get medical advice/ attention if you feel unwell.

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/ attention

P337 + P313 If eye irritation persists: Get medical advice/ attention

P362 Take off contaminated clothing and wash before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.



Version 1.3 Revision Date: 05/19/2017

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

CAS-No.	Chemical Name	Weight %
1330-20-7	Mixed xylenes	50 - 70
64742-47-8 /	Distillates (pet), hydrotreated light AND/OR Sol-	20 - 30
64742-88-7	vent naphtha (pet), med aliph.	
100-41-4	**Ethylbenzene	10 - 20
67-63-0	Isopropyl alcohol	5 - 10
8052-41-3	Stoddard solvent	5 - 10
108-88-3	**Toluene	1 - 5
1330-20-7	**Mixed Xylenes	1 - 5
98-82-8	**Cumene	0.1 - 1

Any Concentration shown as a range is due to batch variation.

Special Notes: : ** Other substances in the product which may present a

health or environmental hazard.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later.

Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.

If unconscious place in recovery position and seek medical

advice.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.



Version 1.3 Revision Date: 05/19/2017

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during fire-

fighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod-

ucts

: No hazardous combustion products are known

Specific extinguishing meth-

ods

: Use a water spray to cool fully closed containers.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

For safety reasons in case of fire, cans should be stored sepa-

rately in closed containments.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if nec-

essary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

Personal precautions, protec- : Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

 Do not spray on a naked flame or any incandescent material.
 Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only

SDS Number: 100000007952 4 / 17 Startex Sander Deglosser



Version 1.3 Revision Date: 05/19/2017

explosion-proof equipment. Keep away from open flames, hot

surfaces and sources of ignition.

Advice on safe handling : Avoid formation of aerosol.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : No smoking.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

CAS-No.	Components	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
1330-20-7	Mixed xylenes	TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
		TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
64742-47-8 / 64742-88-7	Distillates (pet), hydrotreated light AND/OR Solvent naphtha (pet), med aliph.	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	200 mg/m3 (total hydrocarbon vapor)	ACGIH
		TWA	400 ppm 1,600 mg/m3	OSHA P0
100-41-4	**Ethylbenzene	TWA	20 ppm	ACGIH
		TWA	100 ppm 435 mg/m3	NIOSH REL
		ST	125 ppm 545 mg/m3	NIOSH REL
		TWA	100 ppm 435 mg/m3	OSHA Z-1



Version 1.3 Revision Date: 05/19/2017

		TWA	100 ppm 435 mg/m3	OSHA P0
		STEL	125 ppm 545 mg/m3	OSHA P0
67-63-0	Isopropyl alcohol	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m3	NIOSH REL
		ST	500 ppm 1,225 mg/m3	NIOSH REL
		TWA	400 ppm 980 mg/m3	OSHA Z-1
		TWA	400 ppm 980 mg/m3	OSHA P0
		STEL	500 ppm 1,225 mg/m3	OSHA P0
8052-41-3	Stoddard solvent	TWA	100 ppm	ACGIH
		TWA	350 mg/m3	NIOSH REL
		С	1,800 mg/m3	NIOSH REL
		TWA	500 ppm 2,900 mg/m3	OSHA Z-1
		TWA	100 ppm 525 mg/m3	OSHA P0
108-88-3	**Toluene	TWA	20 ppm	ACGIH
		TWA	100 ppm 375 mg/m3	NIOSH REL
		ST	150 ppm 560 mg/m3	NIOSH REL
		TWA	200 ppm	OSHA Z-2
		CEIL	300 ppm	OSHA Z-2
		Peak	500 ppm	OSHA Z-2
		TWA	100 ppm 375 mg/m3	OSHA P0
		STEL	150 ppm 560 mg/m3	OSHA P0
1330-20-7	**Mixed Xylenes	TWA	100 ppm 435 mg/m3	OSHA Z-1
		STEL	150 ppm 655 mg/m3	OSHA P0
		TWA	100 ppm 435 mg/m3	OSHA P0
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
98-82-8	**Cumene	TWA	50 ppm	ACGIH
		TWA	50 ppm 245 mg/m3	NIOSH REL
		TWA	50 ppm 245 mg/m3	OSHA Z-1
		TWA	50 ppm 245 mg/m3	OSHA P0

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally re-

SDS Number: 100000007952 6 / 17 Startex Sander Deglosser



Version 1.3 Revision Date: 05/19/2017

quired.

In the case of vapour formation use a respirator with an ap-

proved filter.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concen-

tration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : Clear, Colorless

Odour : alcohol-like

Odour Threshold : No data available

pH : No data available

Freezing Point : No data available

Boiling Point (Boiling point/boiling range)

: 91 - 197 °C (196 - 387 °F)

Flash point : 13 °C (55 °F)

Method: Tag closed cup

Evaporation rate : 0.401

(Butyl Acetate = 1)

Flammability (solid, gas) : No data available

Upper explosion limit : No data available

Lower explosion limit : 1.1 %(V)

Vapour pressure : 0.0743 PSI @ 20 °C (68 °F)

Relative vapour density : 3.7(Air = 1.0)

SDS Number: 100000007952 7 / 17 Startex Sander Deglosser



Version 1.3 Revision Date: 05/19/2017

Relative density : 0.824 @ 20 °C (68 °F)

Reference substance: (water = 1)

Density : 0.8226 g/cm3 @ 20 °C (68 °F)

Solubility(ies)

Water solubility : slightly soluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : 276 °C

Thermal decomposition : No data available

VOC : 100.0 % / 862.75 g/l / 7.20 lb/gal

Non VOC : 0.0 % / 0.00 g/l / 0.00 lb/gal

VOC Vapor Pressure

Hazardous Air Pollutants

(HAPS)

: 0.0743 PSI : 0.0 % / 0.00 g/l / 0.00 lb/gal

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

: No hazards to be specially mentioned.

Conditions to avoid : Keep away from heat, flame, sparks and other ignition

sources.

Incompatible materials : Strong oxidizing agents

Strong acids

Hazardous decomposition

products

: carbon dioxide and carbon monoxide

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

SDS Number: 100000007952 8 / 17 Startex Sander Deglosser



Version 1.3 Revision Date: 05/19/2017

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 12637 ppm

Exposure time: 4 h
Test atmosphere: gas

Acute dermal toxicity : Acute toxicity estimate: 2,075 mg/kg

Components:

1330-20-7:

Acute inhalation toxicity : LC50 (Rat, male): 6700 ppm

Exposure time: 4 h

Assessment: The component/mixture is moderately toxic after

short term inhalation.

Acute dermal toxicity : LD50 (Rabbit): 1,700 mg/kg

Assessment: The component/mixture is moderately toxic after

single contact with skin.

64742-47-8 / 64742-88-7:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : LD50 (Rabbit, male and female): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Skin corrosion/irritation

Components:

1330-20-7:

Species: Rabbit Exposure time: 24 h Result: Irritating to skin.

64742-47-8 / 64742-88-7:

Species: Rabbit Exposure time: 24 h Result: Irritating to skin.

67-63-0:

Species: Rabbit

Result: Irritating to skin.

Serious eye damage/eye irritation

Components:

1330-20-7:

Species: Rabbit

Result: Irritating to eyes.

64742-47-8 / 64742-88-7:

SDS Number: 100000007952 9 / 17 Startex Sander Deglosser



Version 1.3 Revision Date: 05/19/2017

Species: Rabbit

Result: Irritating to eyes.

67-63-0:

Species: Rabbit

Result: Irritating to eyes.

Respiratory or skin sensitisation

Components:

64742-47-8 / 64742-88-7:

Test Type: Buehler Test Species: Guinea pig

Result: Did not cause sensitisation on laboratory animals.

Germ cell mutagenicity

Components:

64742-47-8 / 64742-88-7:

Germ cell mutagenicity -

Assessment

: Tests on bacterial or mammalian cell cultures did not show

mutagenic effects.

8052-41-3:

Germ cell mutagenicity -

Assessment

: Positive result(s) from mutagenicity tests in mammals. Evidence that the substance has potential to cause mutations to

germ cells

Carcinogenicity

Components:

64742-47-8 / 64742-88-7:

Carcinogenicity - Assess-

ment

: Not classifiable as a human carcinogen.

8052-41-3:

Carcinogenicity - Assess-

ment

: Possible human carcinogen

IARC Group 2B: Possibly carcinogenic to humans

100-41-4 **Ethylbenzene

98-82-8 **Cumene

OSHA No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential carcino-

gen by OSHA.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

ACGIH Confirmed animal carcinogen with unknown relevance to hu-

SDS Number: 100000007952 10 / 17 Startex Sander Deglosser



Version 1.3 Revision Date: 05/19/2017

mans

100-41-4 **Ethylbenzene

Reproductive toxicity

Components:

64742-47-8 / 64742-88-7:

Reproductive toxicity - As-

sessment

Animal testing did not show any effects on fertility.

Teratogenicity - Assessment : Embryotoxicity classification not possible from current data.

8052-41-3:

Reproductive toxicity - As-

sessment

Fertility classification not possible from current data.

Teratogenicity - Assessment : Embryotoxicity classification not possible from current data.

STOT - single exposure

Components:

64742-47-8 / 64742-88-7:

Exposure routes: Inhalation

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness., The substance or mixture is classified as

specific target organ toxicant, single exposure, category 3 with narcotic effects.

67-63-0:

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

STOT - repeated exposure

Components:

8052-41-3:

Target Organs: Central nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated

exposure, category 1.

Aspiration toxicity

Components:

64742-47-8 / 64742-88-7:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vom-

SDS Number: 100000007952 11 / 17 Startex Sander Deglosser



Revision Date: 05/19/2017 Version 1.3

iting.

Concentrations substantially above the TLV value may cause narcotic effects.

Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

64742-47-8 / 64742-88-7:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l

> Exposure time: 96 h Test Type: semi-static test

aquatic invertebrates

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): 1.4 mg/l

Exposure time: 48 h Test Type: static test

Toxicity to algae : EL50 (Pseudokirchneriella subcapitata (green algae)): 1 mg/l

> End point: Growth rate Exposure time: 72 h Test Type: static test

Acute aquatic toxicity- As-

sessment

: Toxic to aquatic life.

Chronic aquatic toxicity- As-

sessment

: Toxic to aquatic life with long lasting effects.

Persistence and degradability

Components:

64742-47-8 / 64742-88-7:

Biodegradability : aerobic

> Biodegradation: 61 % Exposure time: 28 d

Remarks: Readily biodegradable

Bioaccumulative potential

Components:

108-88-3:

Partition coefficient: n-

: log Pow: 2.73

octanol/water

1330-20-7: Partition coefficient: n-

octanol/water

: log Pow: 2.77 - 3.15

98-82-8:

SDS Number: 10000007952 12 / 17 **Startex Sander Deglosser**



Version 1.3 Revision Date: 05/19/2017

Partition coefficient: n-

octanol/water

: log Pow: 3.55 (23 °C)

Mobility in soil

No data available

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Pro-

tection of Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological informa-

tion

: An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with all applicable local, state and

federal regulations.

For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact NEXEO's Environmental Services Group at 800-637-7922.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

DOT (Department of Transportation):

UN1993, Flammable liquids, n.o.s., 3, II

IATA (International Air Transport Association):

UN1993, FLAMMABLE LIQUID, N.O.S., 3, II

IMDG (International Maritime Dangerous Goods):

UN1993, FLAMMABLE LIQUID, N.O.S., 3, II, Marine Pollutant (MIXED XYLENES, ETHYLBENZENE), Flash

Point:13 °C(55 °F)

SECTION 15. REGULATORY INFORMATION

SDS Number: 100000007952 13 / 17 Startex Sander Deglosser



Version 1.3 Revision Date: 05/19/2017

WHMIS Classification : B2: Flammable liquid

D2B: Toxic Material Causing Other Toxic Effects

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
Mixed xylenes	1330-20-7	100	189
**Ethylbenzene	100-41-4	1000	6261

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Fire Hazard

Immediate (Acute) Health Hazard Chronic (Delayed) Health Hazard

Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

100-41-4 **Ethylbenzene 108-88-3 **Toluene 1330-20-7 **Mixed Xylenes

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489):

1330-20-7 Mixed xylenes 100-41-4 **Ethylbenzene 67-63-0 Isopropyl alcohol 108-88-3 **Toluene 1330-20-7 **Mixed Xylenes

Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

1330-20-7 Mixed xylenes 100-41-4 **Ethylbenzene 108-88-3 **Toluene 1330-20-7 **Mixed Xylenes 91-20-3 **Naphthalene 71-43-2 **Benzene

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

1330-20-7 Mixed xylenes 100-41-4 **Ethylbenzene 108-88-3 **Toluene 1330-20-7 **Mixed Xylenes 91-20-3 **Naphthalene 71-43-2 **Benzene

This product contains the following toxic pollutants listed under the U.S. Clean Water Act Section 307

100-41-4 **Ethylbenzene 108-88-3 **Toluene

US State Regulations



Version 1.3	Revision Date: 05/19/2017

31011 1.3		I/EN2IO	11 Date. 03/19/2017
Massachusett	s Right To Know	v	
accac.raccii	1330-20-7	Mixed xylenes	50 - 70 %
	100-41-4	**Ethylbenzene	10 - 20 %
	67-63-0	Isopropyl alcohol	5 - 10 %
	8052-41-3	Stoddard solvent	5 - 10 %
	108-88-3	**Toluene	1 - 5 %
	1330-20-7	**Mixed Xylenes	1 - 5 %
	71-43-2	**Benzene	0 - 0.1 %
Pennsylvania	Right To Know		
-	1330-20-7	Mixed xylenes	50 - 70 %
	64742-47-8 /	Distillates (pet), hydrotreated light AND/OR	20 - 30 %
	64742-88-7	Solvent naphtha (pet), med aliph.	
	100-41-4	**Ethylbenzene	10 - 20 %
	67-63-0	Isopropyl alcohol	5 - 10 %
	8052-41-3	Stoddard solvent	5 - 10 %
	108-88-3	**Toluene	1 - 5 %
	1330-20-7	**Mixed Xylenes	1 - 5 %
	98-82-8	**Cumene	0.1 - 1 %
	95-63-6	**1,2,4-trimethylbenzene	0.1 - 1 %
	91-20-3	**Naphthalene	0 - 0.1 %
	71-43-2	**Benzene	0 - 0.1 %
New Jersey Ri	ight To Know		
	1330-20-7	Mixed xylenes	50 - 70 %
	64742-47-8 / 64742-88-7	Distillates (pet), hydrotreated light AND/OR Solvent naphtha (pet), med aliph.	20 - 30 %
	100-41-4	**Ethylbenzene	10 - 20 %
	67-63-0	Isopropyl alcohol	5 - 10 %
	8052-41-3	Stoddard solvent	5 - 10 %
	108-88-3	**Toluene	1 - 5 %
	1330-20-7	**Mixed Xylenes	1 - 5 %
California Prop 65		WARNING! This product contains a chemica State of California to cause cancer.	I known to the
	100-41-4 98-82-8 91-20-3 71-43-2	**Ethylbenzene **Cumene **Naphthalene **Benzene WARNING! This product contains a chemica State of California to cause birth defects or o	
	108-88-3 71-43-2	harm. **Toluene **Benzene	

The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

SDS Number: 100000007952 15 / 17 Startex Sander Deglosser



Version 1.3 Revision Date: 05/19/2017

NZIoC : On the inventory, or in compliance with the inventory

ENCS : Not in compliance with the inventory

ISHL : Not in compliance with the inventory


KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

SECTION16. OTHER INFORMATION

NFPA:



Special hazard.

HMIS III:

HEALTH	2*
FLAMMABILITY	3
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 =Extreme, * = Chronic

The information accumulated is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made become available subsequently to the date hereof, we do not assume any responsibility for the results of its use. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by NEXEO™ Solutions EHS Product Safety Department (1-855-429-2661) MSDS@nexeosolutions.com.

Revision Date : 05/19/2017

Material number:

16057668, 16061021, 16057665, 16057664, 16057663, 16057666

Key or legend to abbreviations and acronyms used in the safety data sheet				
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%	
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level	
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency	



Version 1.3 Revision Date: 05/19/2017

NDSL	Canada, Non-Domestic Sub-	NIOSH	National Institute for Occupational Safety
	stances List		& Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50 Lethal Concentration 50%			entration 50%