

SAFETY DATA SHEET

Version 6.3 Revision Date 01/15/2020 Print Date 11/20/2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 **Product identifiers**

Product name : Acetone

Product Number : 320110 Brand **SIGALD**

Index-No. : 606-001-00-8 : 67-64-1 CAS-No.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company Sigma-Aldrich Inc.

> 3050 Spruce Street ST. LOUIS MO 63103

UNITED STATES

Telephone : +1 314 771-5765 : +1 800 325-5052 Fax

Emergency telephone number

800-424-9300 CHEMTREC (USA) +1-703-Emergency Phone #

527-3887 CHEMTREC (International) 24

Hours/day; 7 Days/week

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225

Eye irritation (Category 2A), H319

Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word Danger

SIGALD - 320110 Page 1 of 11



Hazard statement(s) H225 H319 H336	Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness.
Precautionary statement(s) P210	Keep away from heat/sparks/open flames/hot surfaces. No
P233 P240	smoking. Keep container tightly closed. Ground/bond container and receiving equipment.
P241 P242	Use explosion-proof electrical/ ventilating/ lighting equipment. Use only non-sparking tools.
P243 P261	Take precautionary measures against static discharge. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264 P271	Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area.
P280 P303 + P361 + P353	Wear protective gloves/ eye protection/ face protection. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 P370 + P378	If eye irritation persists: Get medical advice/ attention. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P403 + P233 P403 + P235	Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool.
P405 P501	Store locked up. Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

Repeated exposure may cause skin dryness or cracking.

SECTION 3: Composition/information on ingredients

3.1 Substances

Component	Classification	Concentration
Acetone		
	Flam. Liq. 2; Eye Irrit. 2A; STOT SE 3; H225, H319, H336 Concentration limits: >= 20 %: STOT SE 3, H336;	<= 100 %

SIGALD - 320110 Page 2 of 11



SECTION 4: First aid measures

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Dry powder Dry sand

Unsuitable extinguishing media

Do NOT use water jet.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

SIGALD - 320110 Page 3 of 11



Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge. For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
Acetone	67-64-1	TWA	250 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Upper Resp Eye irritation Substances or Indices (is a Biological Exposure Index
		STEL	500 ppm	USA. ACGIH Threshold Limit Values (TLV)
		Central Nervous System impairment Upper Respiratory Tract irritation Eye irritation Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen		

SIGALD - 320110 Page 4 of 11



TWA	250 ppm 590 mg/m3	USA. NIOSH Recommended Exposure Limits
TWA	1,000 ppm 2,400 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
The value in mg/m3 is approximate.		
STEL	750 ppm 1,780 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
С	3,000 ppm	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
PEL	500 ppm 1,200 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

Biological occupational exposure limits

biological occupational exposure innits					
Component	CAS-No.	Parameters	Value	Biological specimen	Basis
Acetone	67-64-1	Acetone	25 mg/l	Urine	ACGIH - Biological Exposure Indices (BEI)
	Remarks	End of shift (As soon as possible after exposure ceases)			

Predicted No Effect Concentration (PNEC)

Tredicted No Effect concentration (TNEC)			
Compartment	Value		
Soil	33.3 mg/kg		
Marine water	1.06 mg/l		
Fresh water	10.6 mg/l		
Marine sediment	3.04 mg/kg		
Fresh water sediment	30.4 mg/kg		
Onsite sewage treatment plant	100 mg/l		

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact

SIGALD - 320110 Page 5 of 11



with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: butyl-rubber

Minimum layer thickness: 0.3 mm Break through time: 480 min

Material tested:Butoject® (KCL 897 / Aldrich Z677647, Size M)

Splash contact

Material: butyl-rubber

Minimum layer thickness: 0.3 mm Break through time: 480 min

Material tested:Butoject® (KCL 897 / Aldrich Z677647, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail

sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Impervious clothing, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Appearance Form: clear, liquid

Colour: colourless

b) Odour pungent, weakly aromatic

c) Odour Threshold No data available

d) pH 5 - 6 at 395 g/l at 20 °C (68 °F)

e) Melting point/range: -94 °C (-137 °F) - lit.

point/freezing point

f) Initial boiling point 56 °C 133 °F at 1013 hPa - lit. and boiling range

g) Flash point -17.0 °C (1.4 °F) - closed cup

h) Evaporation rate No data available

SIGALD - 320110 Page 6 of 11



i) Flammability (solid, No data available

gas)

j) Upper/lower Upper explosion limit: 13 %(V) flammability or explosive limits Upper explosion limit: 2 %(V)

k) Vapour pressure 533.3 hPa at 39.5 °C (103.1 °F)

245.3 hPa at 20.0 °C(68.0 °F)

I) Vapour density No data available

m) Relative density 0.791 g/cm3 at 25 °C (77 °F)
n) Water solubility soluble, in all proportions

o) Partition coefficient: No data available

n-octanol/water

p) Auto-ignition 465.0 °C (869.0 °F) temperature

q) Decomposition Distillable in an undecomposed state at normal pressure.

temperature

r) Viscosity No data availables) Explosive properties No data availablet) Oxidizing properties No data available

9.2 Other safety information

Conductivity 0.01 μ S/cm at 20 °C (68 °F) Surface tension 23.2 mN/m at 20.0 °C (68.0 °F)

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Bases, Oxidizing agents, Reducing agents, Acetone reacts violently with phosphorous oxychloride. Strong oxidizing agents

10.6 Hazardous decomposition products

Other decomposition products - No data available Hazardous decomposition products formed under fire conditions. - Carbon oxides In the event of fire: see section 5

SIGALD - 320110 Page 7 of 11



SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - female - 5,800 mg/kg

Remarks: (ECHA)

LC50 Inhalation - Rat - 4 h - 76 mg/l

Remarks: Unconsciousness Drowsiness Dizziness

LD50 Dermal - Rabbit - 20,000 mg/kg

Remarks: (IUCLID) No data available

Skin corrosion/irritation

Skin - Rabbit

Result: Mild skin irritation - 24 h

(Draize Test) Remarks: (RTECS)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Eye irritation - 24 h

(Draize Test)
Remarks: (RTECS)
Risk of corneal clouding.

Respiratory or skin sensitisation

Maximisation Test - Guinea pig

Result: negative Remarks: (ECHA)

Chronic exposure may cause dermatitis.

Germ cell mutagenicity

Mutagenicity (mammal cell test): chromosome aberration.

Chinese hamster ovary cells

Result: negative Ames test

Salmonella typhimurium

Result: negative
In vitro mammalian cell gene mutation test

Mouse lymphoma test

Result: negative

Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

IARC: No component of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Acute oral toxicity - Stomach/intestinal disorders, Risk of aspiration upon vomiting.,

Pulmonary failure possible after aspiration of vomit.

Acute inhalation toxicity - mucosal irritations

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Additional Information

RTECS: AL3150000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Kidney - Irregularities - Based on Human Evidence Skin - Dermatitis - Based on Human Evidence Kidney - Irregularities - Based on Human Evidence Skin - Dermatitis - Based on Human Evidence

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish flow-through test LC50 - Pimephales promelas (fathead minnow) -

6,210 mg/l - 96 h

(OECD Test Guideline 203)

Toxicity to daphnia

and other aquatic

invertebrates

static test LC50 - Daphnia pulex (Water flea) - 8,800 mg/l - 48 h

Remarks: (ECHA)

Toxicity to algae static test NOEC - M.aeruginosa - 530 mg/l - 8 d

(DIN 38412)

Remarks: (maximum permissible toxic concentration)(IUCLID)

Toxicity to bacteria static test EC50 - activated sludge - 61.15 mg/l - 30 min

(OECD Test Guideline 209)

12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 28 d

Result: 91 % - Readily biodegradable.

(OECD Test Guideline 301B)

Biochemical Oxygen 1,850 mg/g

Demand (BOD) Remarks: (IUCLID)

Chemical Oxygen 2,070 mg/g

Demand (COD) Remarks: (IUCLID)

Theoretical oxygen 2,200 mg/g demand Remarks: (Lit.)

12.3 Bioaccumulative potential

Does not bioaccumulate.

Millipore

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

Additional ecological No data available information

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Contact a licensed professional waste disposal service to dispose of this material. Offer surplus and non-recyclable solutions to a licensed disposal company. Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable.

Contaminated packaging

Dispose of as unused product.

SECTION 14: Transport information

DOT (US)

UN number: 1090 Class: 3 Packing group: II

Proper shipping name: Acetone Reportable Quantity (RQ): 5000 lbs Poison Inhalation Hazard: No

IMDG

UN number: 1090 Class: 3 Packing group: II EMS-No: F-E, S-D

Proper shipping name: ACETONE

IATA

UN number: 1090 Class: 3 Packing group: II

Proper shipping name: Acetone

SECTION 15: Regulatory information

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

SIGALD - 320110 Page 10 of 11

Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

Pennsylvania Right To Know Components

Acetone CAS-No. Revision Date 67-64-1 1993-02-16

SECTION 16: Other information

Further information

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.3 Revision Date: 01/15/2020 Print Date: 11/20/2020

SIGALD - 320110 Page 11 of 11

