

Version	22
version	Z.Z

Revision Date 06/18/2018

Print Date 06/16/2020

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name	:	A07326 ZEP 45 017401 20N17
Material number	:	00000000000017401
Manufacturer or supplier's o	leta	ils
Company	:	Zep Inc.
Address	:	350 Joe Frank Harris Parkway, SE Emerson, GA 30137
Telephone	:	404-352-1680

Emergency telephone numbers

For SDS Information	:	Compliance Services 1-877-428-9937
For a Medical Emergency	:	877-541-2016 Toll Free - All Calls Recorded
For a Transportation	:	CHEMTREC: 800-424-9300 - All Calls Recorded.
Emergency		In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

Recommended use : Lubricant

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a compressed gas	
Colour	brown	
Odour	characteristic	

GHS Classification

Gases under pressure	:	Compressed gas
Skin irritation	:	Category 2
Eye irritation	:	Category 2A
Skin sensitisation	:	Category 1
Carcinogenicity	:	Category 1B
Specific target organ toxicity - single exposure	:	Category 3 (Central nervous system)
GHS label elements		
Hazard pictograms	:	$\wedge \wedge \wedge$

:	\diamond	<u>(</u> !
:	Danger	•

Signal word

Hazard statements

H280 Contains gas under pressure; may explode if heated.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.



Version 2.2	Revision Date 06/18/2018	Print Date 06/16/2020
	H336 May cause drowsiness o H350 May cause cancer.	r dizziness.
Precautionary statements	and understood. P261 Avoid breathing dust/ fum P264 Wash skin thoroughly aft P271 Use only outdoors or in a P272 Contaminated work cloth the workplace. P280 Wear protective gloves/ p protection/ face protection. Response: P302 + P352 IF ON SKIN: Was P304 + P340 + P312 IF INHAL and keep comfortable for breat CENTER/doctor if you feel unw	fety precautions have been read ne/ gas/ mist/ vapours/ spray. er handling. a well-ventilated area. ing should not be allowed out of protective clothing/ eye sh with plenty of soap and water ED: Remove person to fresh air hing. Call a POISON vell. ES: Rinse cautiously with water ontact lenses, if present and ncerned: Get medical advice/ rash occurs: Get medical ersists: Get medical advice/ othing and wash before reuse. place. ight. Store in a well-ventilated

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
trichloroethylene	79-01-6	>= 30 - < 50
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 20 - < 30
Distillates (petroleum), straight-run middle	64741-44-2	>= 5 - < 10
2-(2-butoxyethoxy)ethanol	112-34-5	>= 1 - < 5
carbon dioxide	124-38-9	>= 1 - < 5
pentyl acetate	628-63-7	>= 1 - < 5
2-methylbutyl acetate	624-41-9	>= 1 - < 5

The exact percentages of disclosed substances are withheld as trade secrets.



Version 2.2

Revision Date 06/18/2018

Print Date 06/16/2020

TION 4. FIRST AID MEASUR	RES
General advice	: Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	: Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.
In case of skin contact	 If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes. In case of contact, immediately flush skin with plenty of wate for at least 15 minutes while removing contaminated clothing and shoes.
In case of eye contact	 In case of contact, immediately flush eyes with plenty of wat for at least 15 minutes. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	 Do NOT induce vomiting. Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.
Most important symptoms and effects, both acute and delayed	 Effects are immediate and delayed. Symptoms may include irritation, redness, pain, and rash. Symptoms may include central nervous system depression, resulting in headache, nausea and/or dizziness. Chronic effects are delayed and symptoms may not be observed during an exposure. Causes skin irritation. Causes serious eye irritation. Review section 2 of SDS to see all potential hazards.
Notes to physician	: Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during	:	Do not allow run-off from fire fighting to enter drains or water



Version 2.2	Revision Date 06/18/2018	Print Date 06/16/2020
firefighting	courses.	
Hazardous combustion products	: Carbon dioxide (CO2) Carbon monoxide Smoke Chlorine compounds	
Specific extinguishing methods	: Use extinguishing measures that a circumstances and the surroundin	
Further information	: Collect contaminated fire extinguis must not be discharged into drains Fire residues and contaminated fir be disposed of in accordance with For safety reasons in case of fire, separately in closed containments Use a water spray to cool fully closed	s. re extinguishing water must local regulations. cans should be stored s.
Special protective equipment for firefighters	: Wear self-contained breathing app necessary.	paratus for firefighting if

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up or vacuum up spillage and collect in suitable container for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	 Do not breathe vapours or spray mist. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations. Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not



Version 2.2	Revision Date 06/18/2018	Print Date 06/16/2020
	be employed in any process in whi used. Always replace cap after use.	ch this mixture is being
Conditions for safe storage	 BEWARE: Aerosol is pressurized. exposure and temperatures over 56 or throw into fire even after use. Do red-hot objects. No smoking. Keep in a cool, well-ventilated plac Observe label precautions. Electrical installations / working ma the technological safety standards. 	0 °C. Do not open by force o not spray on flames or e. Iterials must comply with
Materials to avoid	: Oxidizing agents	

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
trichloroethylene	79-01-6	TWA	10 ppm	ACGIH
		STEL	25 ppm	ACGIH
		TWA	100 ppm	OSHA Z-2
		CEIL	200 ppm	OSHA Z-2
		Peak	300 ppm	OSHA Z-2
		TWA	50 ppm 270 mg/m3	OSHA P0
		STEL	200 ppm 1,080 mg/m3	OSHA P0
		STEL	100 ppm 537 mg/m3	CAL PEL
		С	300 ppm	CAL PEL
		PEL	25 ppm 135 mg/m3	CAL PEL
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m3	ACGIH
2-(2-butoxyethoxy)ethanol	112-34-5	TWA (Inhalable fraction and vapor)	10 ppm	ACGIH
carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m3	NIOSH REL
		ST	30,000 ppm 54,000 mg/m3	NIOSH REL
		TWA	5,000 ppm	OSHA Z-1



ersion 2.2	Revision	Revision Date 06/18/2018		Print Date 06/16/2020	
		Í	9,000 mg/m3		
		TWA	10,000 ppm 18,000 mg/m3	OSHA P0	
		STEL	30,000 ppm 54,000 mg/m3	OSHA P0	
		PEL	5,000 ppm 9,000 mg/m3	CAL PEL	
		STEL	30,000 ppm 54,000 mg/m3	CAL PEL	
pentyl acetate	628-63-7	TWA	100 ppm 525 mg/m3	NIOSH REL	
		TWA	100 ppm 525 mg/m3	OSHA Z-1	
		TWA	100 ppm 525 mg/m3	OSHA P0	
2-methylbutyl acetate	624-41-9	TWA	50 ppm	ACGIH	
		STEL	100 ppm	ACGIH	

Biological occupational exposure limits

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
TRICHLOROETHENE	79-01-6	Trichloroace tic acid	Urine	End of shift at end of workwee k	15 mg/l	ACGIH BEI
TRICHLOROETHENE		Trichloroeth anol	In blood	End of shift at end of workwee k	0.5 mg/l	ACGIH BEI
TRICHLOROETHENE		Trichloroeth ylene	In end- exhaled air	End of shift at end of workwee k		ACGIH BEI

Engineering measures	:	effective ventilation in all	processing areas
	-		p

Personal protective equipment

Respiratory protection	:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Hand protection Material Remarks		Protective gloves The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	:	Tightly fitting safety goggles Wear face-shield and protective suit for abnormal processing problems.
Skin and body protection	:	Impervious clothing Choose body protection according to the amount and



Version 2.2	Revision Date 06/18/2018	Print Date 06/16/2020
	concentration of the dangerous su	bstance at the work place.
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at	the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Aerosol containing a compressed gas
Colour	: brown
Odour	: characteristic
Odour Threshold	: No data available
рН	: Not applicable
Boiling point	: 87.22 °C
Flash point	: Nationalizable
	Not applicable
Evaporation rate	: <1
Flammability (solid, gas)	: Not classified as a flammability hazard
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Vapour pressure	: Not applicable
Relative vapour density	: No data available
Density	: 1.137 g/cm3
Solubility(ies)	
Water solubility	: insoluble
Partition coefficient: n- octanol/water	: No data available
Auto-ignition temperature	: not determined
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: Not applicable
Heat of combustion	: 20.59 kJ/g

SECTION 10. STABILITY AND REACTIVITY

: Stable



Version 2.2	Revision Date 06/18/2018	Print Date 06/16/2020
Chemical stability	: Stable under normal conditions.	
Possibility of hazardous reactions	: Vapours may form explosive mixture No decomposition if stored and applie	
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct set	unlight.
Incompatible materials	: Metals Oxidizing agents	
Hazardous decomposition products	: Carbon monoxide, carbon dioxide and hydrocarbons (smoke). Chlorine Phosgene Hydrogen chloride gas	d unburned

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

	Aggravated Medical Condition	: None known.	
	Symptoms of Overexposure	 Effects are immediate and delayed. Symptoms may include irritation, redness, pain, and responses may include central nervous system depreses resulting in headache, nausea and/or dizziness. Chronic effects are delayed and symptoms may not b observed during an exposure. 	ssion,
	Carcinogenicity:		
	IARC	Group 1: Carcinogenic to humans	
	ACGIH	trichloroethylene Suspected human carcinogen	79-01-6
		trichloroethylene	79-01-6
	OSHA	No component of this product present at levels greater the equal to 0.1% is on OSHA's list of regulated carcinogens	
	NTP	Known to be human carcinogen	
		trichloroethylene	79-01-6
Αςι	ute toxicity		
	Product:		
	Acute oral toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method	
	Components:		
	trichloroethylene:		
	Acute oral toxicity	: LD50 Oral Rat: 4,920 mg/kg	



Version 2.2	_	Revision Date 06/18/2018	Print Date 06/16/2020
Acute inhalation toxicity	:	LC50 Mouse: 8450 ppm Exposure time: 4 h	
Acute dermal toxicity	:	LD50 Dermal Rabbit: > 20,000 mg/kg	
Distillates (petroleum), hydr Acute oral toxicity		eated heavy naphthenic: LD50 Rat: > 5,000 mg/kg	
Acute inhalation toxicity	:	LC50 Rat: > 5 mg/l Exposure time: 4 h	
Acute dermal toxicity	:	LD50 Rabbit: > 5,000 mg/kg	
Skin corrosion/irritation			
Product:			
Remarks: Irritating to skin.			
Serious eye damage/eye irritatio	n		
Product:			
Remarks: Severe eye irritation	۱		
Respiratory or skin sensitisatior	۱		
Product:			
Remarks: Causes sensitisatio	n.		
Germ cell mutagenicity			
No data available			
Carcinogenicity			
No data available			
Reproductive toxicity			
No data available			
STOT - single exposure			
No data available			
STOT - repeated exposure			
No data available			
Aspiration toxicity			
No data available			
Further information			
Product:			

SAFETY DATA SHEET



A07326 ZEP 45 017401 20N17

Version 2.2

Revision Date 06/18/2018

Print Date 06/16/2020

Remarks: No data available

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available **Bioaccumulative potential**

Product:

Flouuci.	
Partition coefficient: n- octanol/water <u>Components:</u> trichloroethylene :	: Remarks: No data available
Partition coefficient: n- octanol/water 2-(2-butoxyethoxy)ethanol :	: log Pow: 2.29
Partition coefficient: n- octanol/water pentyl acetate :	: Pow: 1
Partition coefficient: n- octanol/water	: log Pow: 2.3
Mobility in soil	
No data available	
Other adverse effects	
No data available Product:	
Regulation	40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks	This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).
Additional ecological information	: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.



Version 2.2

Revision Date 06/18/2018

Print Date 06/16/2020

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of in accordance with local regulations.
Contaminated packaging	 Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): UN1950, AEROSOLS, 2.2, (6.1), - Limited quantity

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, 2.2, (6.1),

Transportation Regulation: IATA (Cargo Air): UN1950, Aerosols, non-flammable, containing substances in Division 6.1, Packing Group III, 2.2, (6.1),

Transportation Regulation: IATA (Passenger Air): UN1950, Aerosols, non-flammable, containing substances in Division 6.1, Packing Group III, 2.2, (6.1),

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, 2.2, (6.1),

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

 TSCA list
 : The following substance(s) is/are subject to TSCA 12(b) export notification requirements: trichloroethylene

 79-01-6

No substances are subject to a Significant New Use Rule.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

SAFETY DATA SHEET



A07326 ZEP 45 017401 20N17

ersion 2.2		Revision Date 06/18	8/2018	Print Date 06	6/16/2020
Components		CAS-No.	Component RQ (lbs)	Calculated pro (lbs)	duct RQ
trichloroethylene		79-01-6	100	212	
SARA 304 Extremely Hazar	rdous	Substances Repor	rtable Quantity		
This material does not conta	in any	components with a	section 304 EHS	RQ.	
SARA 311/312 Hazards	Sł Se Re Ca	ases under pressure kin corrosion or irrita erious eye damage espiratory or skin se arcinogenicity becific target organ t	ation or eye irritation ensitisation	repeated exposu	ıre)
SARA 302		chemicals in this n quirements of SAR			g
SARA 313	es tri 2-	ne following compon stablished by SARA chloroethylene (2-butoxyethoxy)eth butoxyethanol	Title III, Section 3	313: 79-01-6 12-34-5 4	47 % 4.3931 % 0.0669 %
California Prop. 65					



WARNING: This product can expose you to chemicals including trichloroethylene, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

DSL	All components of this product are on the Canadian DSL
TSCA	On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION




Version 2.2

Revision Date 06/18/2018

Print Date 06/16/2020

Further information



HMIS III:

HEALTH	2*
FLAMMABILITY	2
PHYSICAL HAZARD	3

0 = not significant, 1 =Slight,

2 = Moderate, 3 = High 4 = Extreme, * = Chronic

OSHA - GHS Label Information:

Hazard pictograms	
Signal word	
Signal word Hazard statements	 Danger: Contains gas under pressure; may explode if heated. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness. May cause cancer.
Precautionary statements	
	 Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/ protective clothing/ eye protection/ face protection. Response: IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/ attention. If skin irritation or rash occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash before reuse. Storage: Store in a well-ventilated place. Protect from sunlight. Store in a well-ventilated place. Disposal: Dispose of contents/container in accordance with local regulation.

Version:	2.2
Revision Date:	06/18/2018
Print Date:	06/16/2020

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.



Version 2.2

Revision Date 06/18/2018

Print Date 06/16/2020

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®,Zep Professional®, Enforcer®, National Chemical[™], Selig[™], Misty®, Next Dimension[™], Petro®, i-Chem®, TimeMist®, TimeWick[™], MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National[™], FC Forward Chemicals®,Rexodan®, Mykal[™], and a number of private labeled brands.